11-10

TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API number: 15-065-22,748 150'N. SE NE SW /4 SEC. 02 , 10 S, 21 W 1800 feet from S section line 2970 feet from E section line
Operator license#_4058_	Lease_ <u>Vera_White</u> well #_2_
Operator: American Warrior, Inc.	County Graham
Address: P.O. Box 399 Garden City, Kansas 67846	Well total depth 3816 feet Conductor Pipe: 0 inch 0 0 feet Surface pipe 8 5/8 Inch 0 228 feet
Aband. oil well, Gas well, Inp	out well, SWD, D & A _X
Plugging contractor: Discovery Drillir	License# 31548
Address:	
Company to plug at: Hour: P.M. Day:	8 Month: November Year: 94
Plugging proposal received from: Tom P	alm
Company: <u>Discovery Drilling</u>	Phone:
Were: Order 215 sxs. 60/40 posmix - Spot all plugs through drill plugs.	6% gel - 2 sxs. celloflake. pipe with heavy mud between all
Plugging Propogal Pagained have Rd Gab	
Plugging Proposal Received by: <u>Ed Sch</u> Plugging operations attended by agent?	All[], Part[], None[X]
Completed: Hour: 2:30A.M, Day: 10, Mo	nth: November , Year: 94
Actual plugging report:	KANSAS CORPORATION COMMISSION DEC 0 994
1st. plug at 3805' w/20 sxs. 2nd. plug at 1745' w/20 sxs.	DEC 0 8 1994
3rd. plug at 970' w/100 sxs.	DEC 00 199W
3rd. plug at 970' w/100 sxs. 4th. plug at 280' w/40 sxs. 5th. plug at 40' w/10 sxs.	0 /90%
5th. plug at 40' w/10 sxs.	
15 sxs. in rathole. 10 sxs. in mouseh Arbuckle 3803'.	CONSERVATION DIVISION Ole. WICHTA, KS
Remarks:Halliburton Cementing. Condition of casing(in hole):GOOD_X_B Bottom plug(in place):YES,CALC_Plugged through TUBING, CASING	,NODakota plug:YES_X_,NO Elevation:2268GL
DATE 129-94	(agent) Form CP-2/3
MV. 100 4104 1-10 JAN 19 1995	