

Operator Name: Town Oil Company, Inc. Lease Name: Eversmeyer Well #: A-5
 Sec. 8 Twp. 16 S. R. 21 East West County: Franklin

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

| | |
|--|---|
| Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: GAMMA RAY NEUTRON COMPLETION LOG | <input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample Name Top Datum (SEE ATTACHED COPY) |
|--|---|

| CASING RECORD <input type="checkbox"/> New <input type="checkbox"/> Used | | | | | | | |
|---|-------------------|---------------------------|------------------|---------------|----------------|--------------|----------------------------|
| Report all strings set-conductor, surface, intermediate, production, etc. | | | | | | | |
| Purpose of String | Size Hole Drilled | Size Casing Set (In O.D.) | Weight Lbs. / Ft | Setting Depth | Type of Cement | # Sacks Used | Type and Percent Additives |
| Surface | 9 5/8" | 7" | | 20' | Portland | 3sx | |
| Completion | 5 5/8" | 2 7/8" upset | | 700' | Portland | 111sx | 50/50 Poz Mix 2% Gel |

| ADDITIONAL CEMENTING / SQUEEZE RECORD | | | | |
|--|------------------|----------------|-------------|----------------------------|
| Purpose: | Depth Top Bottom | Type of Cement | #Sacks Used | Type and Percent Additives |
| <input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone | | | | |

| Shots Per Foot | PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated | Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used) | Depth |
|----------------|---|---|-------|
| 2 | 652-662 (40 shots) | | |
| | | | |
| | | | |
| | | | |

| | | | | |
|--|-----------|---|-------------|--|
| TUBING RECORD | Size | Set At | Packer At | Liner Run <input type="checkbox"/> Yes <input type="checkbox"/> No |
| Date of First, Resumerd Production, SWD or Enhr. | | Producing Method <input type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain) | | |
| Estimated Production Per 24 Hours | Oil Bbls. | Gas Mcf | Water Bbls. | Gas-Oil Ratio Gravity |

Disposition of Gas Vented Sold Used on Lease *(If vented, Submit ACO-18.)*

METHOD OF COMPLETION Open Hole Perf. Dually Comp. Commingled Other (Specify) _____

Production Interval _____



CONSOLIDATED
Oil Well Services, LLC

REMIT TO
Consolidated Oil Well Services, LLC
Dept. 970
P.O. Box 4346
Houston, TX 77210-4346

MAIN OFFICE
P.O. Box 884
Chanute, KS 66720
620/431-9210 • 1-800/467-8676
FAX 620/431-0012

INVOICE

Invoice # 231512

Invoice Date: 10/09/2009 Terms: 0/30,n/30

Page 1

TOWN OIL COMPANY
16205 W. 287 STREET
PAOLA KS 66071
(785)294-2125

EVERSMEYER A-5
20129
SW 8-16-21 FR
10/06/2009
KS

| Part Number | Description | Qty | Unit Price | Total |
|-------------|-------------------------|--------|------------|---------|
| 1118B | PREMIUM GEL / BENTONITE | 268.00 | .1600 | 42.88 |
| 1124 | 50/50 POZ CEMENT MIX | 109.00 | 9.2500 | 1008.25 |
| 4402 | 2 1/2" RUBBER PLUG | 1.00 | 22.0000 | 22.00 |

| Description | Hours | Unit Price | Total |
|---------------------------------|--------|------------|--------|
| 368 CEMENT PUMP | 1.00 | 870.00 | 870.00 |
| 368 EQUIPMENT MILEAGE (ONE WAY) | 15.00 | 3.45 | 51.75 |
| 368 CASING FOOTAGE | 700.00 | .00 | .00 |
| 510 MIN. BULK DELIVERY | 1.00 | 296.00 | 296.00 |

RECEIVED
KANSAS CORPORATION COMMISSION

DEC 21 2009

CONSERVATION DIVISION
WICHITA, KS

Parts: 1073.13 Freight: .00 Tax: 72.98 AR 2363.86
Labor: .00 Misc: .00 Total: 2363.86
Sublt: .00 Supplies: .00 Change: .00

Signed _____

Date _____

BARTLESVILLE, OK
918/338-0808

ELDORADO, KS
316/322-7022

EUREKA, KS
620/583-7664

GILLETTE, WY
307/686-4914

MCALISTER, OK
918/426-7667

OTTAWA, KS
785/242-4044

THAYER, KS
620/839-5269

WORLAND, WY
307/347-4577

TOWN OIL COMPANY, INC.

"Drilling and Production"

16205 W 287th Street
Paola, Kansas 66071

Fax# 913-294-4823

PHONE: 913-557-5482
913-294-2125

WELL: Eversmeyer A-5

LEASE OWNER: Town Oil Company, Inc.

WELL LOG

| Thickness of Strata | Formation | Total Depth |
|------------------------|------------------|----------------|
| 0-11 | soil/clay | 11 |
| 24 | lime | 35 |
| 7 | shale | 42 |
| 10 | lime | 52 |
| 5 | shale | 57 |
| 20 | lime | 77 |
| 10 | shale | 87 |
| 3 | red bed | 90 |
| 25 | shale | 115 |
| 23 | lime | 138 |
| 15 | sand | 153 |
| 58 | shale | 211 |
| 23 | lime | 234 |
| 7 | shale | 241 |
| 3 | sand | 244 |
| 14 | sandy shale | 258 |
| 6 | lime/green shale | 264 |
| 23 | sandy shale | 287 |
| 5 | lime | 292 |
| 12 | shale | 304 |
| 2 | lime | 306 |
| 15 | shale | 321 |
| 23 | lime | 344 |
| 8 | shale/slate | 352 |
| 23 | lime | 375 |
| 4 | shale/slate | 379 |
| 5 | lime | 384 |
| 4 | shale | 388 |
| 5 | lime | 393 |
| 114 | sandy shale | 507 |
| 13 | sand | 520 |
| 28 | shale | 548 |
| 3 | lime | 551 |
| 6 | sandy shale | 557 |
| 7 | lime | 564 |
| 5 | shale | 569 |
| 11 | lime | 580 |
| 6 | coal/slate | 586 |
| 2 | shale | 588 |
| 6 | lime | 594 |
| 13 | shale | 607 |

RECEIVED
KANSAS CORPORATION COMMISSION

DEC 21 2009

CONSERVATION DIVISION
WICHITA, KS

TOWN OIL COMPANY, INC.

"Drilling and Production"

16205 W 287th Street
Paola, Kansas 66071

Fax# 913-294-4823

PHONE: 913-557-5482
913-294-2125

WELL: Eversmeyer A-5

LEASE OWNER: Town Oil Company, Inc.

WELL LOG (CON'T)

| Thickness of Strata | Formation | Total Depth |
|------------------------|------------|----------------|
| 3 | lime | 610 |
| 6 | coal/slate | 616 |
| 12 | lime | 628 |
| 9 | shale | 637 |
| 1 | lime | 638 |
| 2 | shale | 640 |
| 4 | lime | 644 |
| 6 | sand | 650 |
| 8 | sand | 658 |
| 5 | sand | 663 |
| 2 | sand | 665 |
| 39 | shale | 704 |
| 6 | sand | 710 |
| 2 | shale | 712 TD |

RECEIVED
KANSAS CORPORATION COMMISSION

DEC 21 2009

CONSERVATION DIVISION
WICHITA, KS