

9/13/09

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION
CONFIDENTIAL WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

ORIGINAL

Form ACO-1
September 1999
Form Must Be Typed
AMENDED

Operator: License # 33365
Name: Layne Energy Operating, LLC
Address: 1900 Shawnee Mission Parkway
City/State/Zip: Mission Woods, KS 66205
Purchaser: _____
Operator Contact Person: Timothy H. Wright
Phone: (913) 748-3960
Contractor: Name: Thornton Air Rotary
License: 33606

Wellsite Geologist: _____
Designate Type of Completion:
____ New Well ____ Re-Entry ____ Workover
____ Oil ____ SWD ____ SLOW ____ Temp. Abd.
 Gas ____ ENHR SIGW
____ Dry ____ Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: _____
Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
____ Deepening ____ Re-perf. ____ Conv. to Enhr./SWD
____ Plug Back ____ Plug Back Total Depth
____ Commingled Docket No. _____
____ Dual Completion Docket No. _____
____ Other (SWD or Enhr.?) Docket No. _____

<u>5/18/2007</u>	<u>5/21/2007</u>	<u>8/24/2007</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 125-31352-00-00
County: Montgomery
____ SW NE Sec. 19 Twp. 31 S. R. 17 East West
1978 feet from S / N (circle one) Line of Section
1978 feet from E W (circle one) Line of Section

Footages Calculated from Nearest Outside Section Corner:
(circle one) NE NW SW
Lease Name: Voelker Well #: 7-19
Field Name: Cherokee Basin Coal Area
Producing Formation: Cherokee Coals
Elevation: Ground: 842' Kelly Bushing: _____
Total Depth: 1102' Plug Back Total Depth: 1097'
Amount of Surface Pipe Set and Cemented at 21 Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from 1097
feet depth to Surface w/ 110 sx cmt.

Drilling Fluid Management Plan *AK 4-13-09*
(Data must be collected from the Reserve Pit)
Chloride content N/A ppm Fluid volume _____ bbls
Dewatering method used N/A - Air Drilled
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: [Signature]
Title: Agent Date: 12-6-07
Subscribed and sworn to before me this 6 day of December,
2007.
Notary Public: MacLaughlin Darline
Date Commission Expires: 1-4-2009

KCC Office Use ONLY
 Letter of Confidentiality Attached
If Denied, Yes Date: _____
 Wireline Log Received
 Geologist Report Received
UIC Distribution

RECEIVED
KANSAS CORPORATION COMMISSION

DEC 10 2007

CONSERVATION DIVISION
WICHITA, KS

MacLAUGHLIN DARLINE
Notary Public - State of Kansas
My Appt. Expires 1-4-2009

Operator Name: Layne Energy Operating, LLC Lease Name: Voelker Well #: 7-19
 Sec. 19 Twp. 31 S. R. 17 East West County: Montgomery

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Compensated Density Neutron Dual Induction	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample <table style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Name</th> <th style="text-align: left;">Top</th> <th style="text-align: left;">Datum</th> </tr> </thead> <tbody> <tr> <td>Pawnee Lime</td> <td>498 GL</td> <td>344</td> </tr> <tr> <td>Excello Shale</td> <td>622 GL</td> <td>220</td> </tr> <tr> <td>V Shale</td> <td>678 GL</td> <td>164</td> </tr> <tr> <td>Mineral Coal</td> <td>725 GL</td> <td>117</td> </tr> <tr> <td>Mississippian</td> <td>1024 GL</td> <td>-182</td> </tr> </tbody> </table>	Name	Top	Datum	Pawnee Lime	498 GL	344	Excello Shale	622 GL	220	V Shale	678 GL	164	Mineral Coal	725 GL	117	Mississippian	1024 GL	-182
Name	Top	Datum																	
Pawnee Lime	498 GL	344																	
Excello Shale	622 GL	220																	
V Shale	678 GL	164																	
Mineral Coal	725 GL	117																	
Mississippian	1024 GL	-182																	

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacjs Used	Type and Percent Additives
Surface	11"	8.625"	24	21'	Class A	4	Type 1 cement
Casing	6.75"	4.5"	10.5	1097'	Thick Set	110	#10 KOL seal @ sx

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
	See Attached Page		

TUBING RECORD	Size <u>2-3/8"</u>	Set At <u>1012'</u>	Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr. <u>10/17/2007</u>		Producing Method <input type="checkbox"/> Flowing <input checked="" type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)		
Estimated Production Per 24 Hours	Oil Bbbs. <u>0</u>	Gas Mcf <u>8</u>	Water Bbbs. <u>1</u>	Gas-Oil Ratio Gravity

Disposition of Gas <input type="checkbox"/> Vented <input checked="" type="checkbox"/> Sold <input type="checkbox"/> Used on Lease <i>(If vented, Submit ACO-18.)</i>	METHOD OF COMPLETION <input type="checkbox"/> Open Hole <input checked="" type="checkbox"/> Perf. <input type="checkbox"/> Dually Comp. <input checked="" type="checkbox"/> Commingled <input type="checkbox"/> Other (Specify) _____	Production Interval _____
--	---	---------------------------

RECEIVED
KANSAS CORPORATION COMMISS

DEC 10 2007

CONSERVATION DIVISION
WICHITA, KS

CONFIDENTIAL

Operator Name:	Layne Energy Operating, LLC.		
Lease Name:	Voelker 7-19		
	Sec. 19 Twp. 31S Rng. 17E, Montgomery County		
API:	15-125-31352-00-00		
Shots per Foot	Perforation Record	Acid, Fracture, Shot, Cement Squeeze Record	Depth
Initial Perforations			
4	Rowe 966' - 968' Drywood 848' - 850' Bluejacket 831.5' - 835' Weir 807' - 809'	10900 lbs 20/40 sand 755 bbls water 725 gals 15% HCl acid	807' - 968'
4	Scammon 741' - 743' Mineral 724' - 726' Fleming 691' - 693' Croweburg 679' - 681' Bevier 656' - 659'	14600 lbs 20/40 sand 928 bbls water 532 gals 15% HCl acid	656' - 743'

RECEIVED
KANSAS CORPORATION COMMISSION

DEC 10 2007

CONSERVATION DIVISION
WICHITA, KS