

CONFIDENTIAL

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

ORIGINAL

12/26/09
Form ACO-1
September 1999
Form Must Be Typed

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33739
Name: SEK Energy, LLC.
Address: P.O. Box 55
City/State/Zip: Benedict, Kansas 66714
Purchaser: _____
Operator Contact Person: Kerry King
Phone: (620) 698-2150
Contractor: Name: Thornton Air Rotary
License: 33606
Wellsite Geologist: Julie Shaffer

Designate Type of Completion:
 New Well Re-Entry Workover
 Oil SWD SLOW Temp. Abd.
 Gas ENHR SIGW
 Dry Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: _____
Well Name: _____

Original Comp. Date: _____ Original Total Depth: _____
 Deepening Re-perf. Conv. to Enhr./SWD
 Plug Back _____ Plug Back Total Depth _____
 Commingled _____ Docket No. _____
 Dual Completion _____ Docket No. _____
 Other (SWD or Enhr.?) _____ Docket No. _____

<u>9/28/07</u>	<u>10/2/07</u>	<u>NA</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 207-27248-00-50
County: Woodson
SE NW SE Sec. 25 Twp. 26 S. R. 14 East West
1680 feet from (S) / N (circle one) Line of Section
1680 feet from (E) / W (circle one) Line of Section


Footages Calculated from Nearest Outside Section Corner:
(circle one) NE (SE) NW SW
Lease Name: Wharry, Michael A. Well #: 1-25
Field Name: Cherokee Basin CBM
Producing Formation: Pennsylvanian Coals
Elevation: Ground: 1080' Kelly Bushing: _____
Total Depth: 1588' Plug Back Total Depth: 1586'
Amount of Surface Pipe Set and Cemented at 40 Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from 40
feet depth to 0 w/ 8 sx cmt.

Drilling Fluid Management Plan AMHMS-509
(Data must be collected from the Reserve Pit)
Chloride content _____ ppm Fluid volume _____ bbls
Dewatering method used _____
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: Julie Shaffer
Title: GEOLOGIST Date: 12-26-07
Subscribed and sworn to before me this 26th day of December,
2007.
Notary Public: George S. Slaughter
Date Commission Expires: 4-1-2010

 **GEORGE SLAUGHTER**
Notary Public - State of Kansas
My Appt. Expires _____

KCC Office Use ONLY

Letter of Confidentiality Received
 If Denied, Yes Date: _____
 Wireline Log Received
 Geologist Report Received
 UIC Distribution

RECEIVED
KANSAS CORPORATION COMMISSION
DEC 28 2007

CONSERVATION DIVISION
WICHITA, KS

Operator Name: SEK Energy, LLC. Lease Name: Wharry, Michael A. Well #: 1-25
 Sec. 25 Twp. 26 S. R. 14 East West County: Woodson

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input type="checkbox"/> No (Attach Additional Sheets) Samples Sent to Geological Survey <input type="checkbox"/> Yes <input type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No (Submit Copy) List All E. Logs Run: Density-Neutron, Dual Induction, Differential Temperature	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:60%;">Name</td> <td style="width:20%;">Top</td> <td style="width:20%;">Datum</td> </tr> <tr> <td>Lenapah Limestone</td> <td>964'</td> <td>+116'</td> </tr> <tr> <td>Altamont Limestone</td> <td>1000'</td> <td>+80'</td> </tr> <tr> <td>Pawnee Limestone</td> <td>1098'</td> <td>-18'</td> </tr> <tr> <td>Oswego Limestone</td> <td>1152'</td> <td>-72'</td> </tr> <tr> <td>Verdigris Limestone</td> <td>1266'</td> <td>-186'</td> </tr> <tr> <td>Mississippi</td> <td>1540'</td> <td>-460'</td> </tr> </table>	Name	Top	Datum	Lenapah Limestone	964'	+116'	Altamont Limestone	1000'	+80'	Pawnee Limestone	1098'	-18'	Oswego Limestone	1152'	-72'	Verdigris Limestone	1266'	-186'	Mississippi	1540'	-460'
Name	Top	Datum																				
Lenapah Limestone	964'	+116'																				
Altamont Limestone	1000'	+80'																				
Pawnee Limestone	1098'	-18'																				
Oswego Limestone	1152'	-72'																				
Verdigris Limestone	1266'	-186'																				
Mississippi	1540'	-460'																				

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	11"	8 5/8"		40'	Portland	8	
Production	6 3/4"	4 1/2"	10.5#	1586'	Thickset	180	See Attached

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
	Waiting on Pipeline		
		RECEIVED	
		KANSAS CORPORATION COMMISSION	
		DEC 28 2007	

TUBING RECORD	Size	Set At	Packer At	Liner Run <input type="checkbox"/> Yes <input type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr.				Producing Method <input type="checkbox"/> Flowing <input type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio Gravity

Disposition of Gas Vented Sold Used on Lease (If vented, Submit ACO-18.)

METHOD OF COMPLETION

Open Hole Perf. Dually Comp. Commingled _____

Other (Specify) _____

Production Interval

CONSOLIDATED OIL WELL SERVICES, LLC
 P.O. BOX 884, CHANUTE, KS 66720
 620-431-9210 OR 800-467-8676

ENTERED

TICKET NUMBER 12723
 LOCATION Eureka
 FOREMAN Rick Leonard

TREATMENT REPORT & FIELD TICKET
 CEMENT

DATE	CUSTOMER #	WELL NAME & NUMBER	SECTION	TOWNSHIP	RANGE	COUNTY
10-3-07	1805	Wherry Michael 1-25				Wheeler
CUSTOMER SEK Energy LLC			TRUCK #			
MAILING ADDRESS P.O. Box 55			DRIVER			
CITY Benedict		STATE KS	ZIP CODE 66714		TRUCK #	
					DRIVER	
			463		KYLE	
			502		HEATH	
			452/103		JIM	

JOB TYPE log string HOLE SIZE 6 3/4" HOLE DEPTH 1582' CASING SIZE & WEIGHT 4 1/2" 13.5"
 CASING DEPTH 1586' DRILL PIPE _____ TUBING _____ OTHER _____
 SLURRY WEIGHT 13.4° SLURRY VOL 52 Bbl WATER gal/sk 8.0° CEMENT LEFT in CASING 0'
 DISPLACEMENT 25 1/4 gal DISPLACEMENT PSI 200 PSI 1200 RATE _____

REMARKS: Safety meeting Ran wireline tag float shoe @ 1585' Rig up to 4 1/2"
casing. Break circulation w/ 30 Bbl fresh water. Pump 4 ses gel-flush w/ bulls
20 Bbl metasilicate pre-flush, 15 Bbl dye water. Mixed 180 ses thickset cement
w/ 1/4" floccle @ 13.4°/sec. Washout pump & lines, shut down, release label
down plug. Displace w/ 25 1/4 Bbl fresh water. Final pump pressure 200 PSI.
Bump plug to 1200 PSI. wait 2 minutes, release pressure, float held. Cement
returns to surface = 8 Bbl slurry to pit. Job complete Rig down.

"Thank You"

ACCOUNT CODE	QUANTITY or UNITS	DESCRIPTION of SERVICES or PRODUCT	UNIT PRICE	TOTAL
5401	1	PUMP CHARGE	840.00	840.00
5406	40	MILEAGE	3.30	132.00
1126A	180 ses	thickset cement	15.40	2772.00
1107	45°	1/4" floccle @ 13.4°/sec	1.90	85.50
1118A	200*	gel-flush	.15	30.00
1105	50*	bulls	.36	18.00
1102	80°	calc	.67	53.60
1111A	100°	metasilicate pre-flush	1.65	165.00
5407A	9.9	tax-mileage bulk trk	1.10	108.90
5501C	4 hrs	water transport	100.00	400.00
1123	5000 gals	city water	12.80	64.00
			Subtotal	4986.20
			6.32%	SALES TAX 200.05
				ESTIMATED TOTAL 5186.25

RECEIVED
 KANSAS CORPORATION COMMISSION
 DEC 28 2007
 CONSERVATION DIVISION
 WICHITA, KS

217030

AUTHORIZATION _____ TITLE _____ DATE _____
 5196.56