Form CP-4

STATE OF KANSAS
STATE CORPORATION COMMISSION
Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission

WELL PLUGGING RECORD

State Corporation Commission 211 No. Broadway Wichita, Kansas		Graham	Coun	ity. Sec. 1	wp10 Rge.	(E) (W)
NORTH		ie/cnwkswk"	or footage fr	om lines SE	NW NW	
	Lease Owner_	36.0 33 117				
	Lease Name _					_ Well No. 2
		Plainvill				
			as Oil, Gas	or Dry Hole)		-
	Date well com	-				19
	Application for plugging filed					
	Application for plugging approved 19 Plugging commerced 1-2-65					
	Plugging comm	nenceu			· · · · · · · · · · · · · · · · · · ·	19
	Plugging completed 1-4-65 Reason for abandonment of well or producing formation Depleted.					
	Reason for aba	ndonment of we	u or producii	ng tormation	рертетео.	
	If a producing	wall is abandan	ad data of 1	ast production_		10
<u> </u>	Was permissio	n obtained from	the Consor	ustion Division o	e ita aganta hafa	ore plugging was con
Locate well correctly on above Section Plat	menced?		me Consei	vacion Division o	n its agents bere	ore bringging was con
lame of Conservation Agent who supe			L. Nicho	ls		
roducing formation	I	Depth to top	Botto:	m	Total Depth of	Well 4130 Fe
how depth and thickness of all water,					Tom. Dopus of	4280 R
-		•				0
OIL, GAS OR WATER RECORD)\$					CASING RECORD
FORMATION	CONTENT	FROM	TO	SIZE	PUT IN	PULLED OUT
				8-5/8"	2131	None
				5-1/2"	4130'	None
		<u> </u>				
Chec to 3	tent or other plugs we t. cked hole to 3 475' and dump bailer. Cut	ere used, state the state of th	ed plug of cemer	to 3500', sont @ 3475'	h placed, from sanded with	feet
chec to 3 dump	ent or other plugs we et. eked hole to 3 475 and dump	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	h placed, from sanded with	feet
chec to 3 dump	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	feet
chec to 3 dump	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	h placed, from sanded with	feet
chec to 3 dump	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	feet
chec to 3 dump	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	feet
chec to 3 dump	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	TREDITATION COMMING
chec to 3 dump	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	PRPORTION COMMINGS
chec to 3 dump	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	ere used, state the state of $5\frac{32!}{5\frac{6}{6}!!}$ of $5\frac{1}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$ of $\frac{32!}{6}$	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	PRPORTION COMMINGS
cintroducing it into the hole. If cem feet for each plug se Chec to 3 dump brid read	ent or other plugs we be. eked hole to 3 475' and dump bailer. Cut ged 5½" casin	532', push ed 5 sacks off $5\frac{1}{6}$ " 1 g @ 1300' to base of	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	PRPORTION COMMINGS
introducing it into the hole. If cem feet for each plug se Chec to 3 dump brid read	eked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement	532', push ed 5 sacks off $5\frac{1}{6}$ " 1 g @ 1300' to base of	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	PRPORTION COMMINGS
chec feet for each plug se Chec to 3 dump brid read	eked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement	532', push ed 5 sacks off $5\frac{1}{6}$ " 1 g @ 1300' to base of	ed plug of cemer evel with	to 3500', so to 3475' the surface, $7\frac{1}{2}$ yards of	b placed, from_sanded_with	feet
chec feet for each plug se Chec to 3 dump brid read	check or other plugs we st. checked hole to 3 475' and dump chailer. Cut ged 5½" casin y-mix cement GING COMPLETE	ere used, state the state of 532!, push ed 5 sacks off 5½!! Leg 2300! to base of	ed plug of cemen evel with and ran cellar.	to 3500', so the angle of same and depth to 3500', so the angle of the	b placed, from_sanded_with	PRPORTION COMMINGS
cintroducing it into the hole. If cem feet for each plug se Chec to 3 dump brid read	eked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement	ere used, state the state of the sacks off $5\frac{1}{6}$. It is a sack of the sacks of	ed plug of cemer evel with and ran cellar.	to 3500', so the angle of same and depth to 3500', so the angle of the	b placed, from_sanded_with	PRPORTION COMMINGS
chec feet for each plug se Chec to 3 dump brid read PLUG-	check or other plugs we st. checked hole to 3 475' and dump chailer. Cut ged 5½'' casin y-mix cement GING COMPLETE	ere used, state the state of the sacks off $5\frac{1}{6}$. It is a sack of the sacks of	ed plug of cemer evel with and ran cellar.	to 3500', so the angle of same and depth to 3500', so the angle of the	b placed, from_sanded_with	PRPORTION COMMINGS
chec feet for each plug se Chec to 3 dump brid read PLUG-	eked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement	ere used, state the state of the sacks off $5\frac{1}{6}$. It is a sack of the sacks of	ed plug of cemer evel with	to 3500', so the angle of same and depth to 3500', so the angle of the	b placed, from_sanded_with	PRPORTION COMMINGS
chec feet for each plug se Chec to 3 dump brid read PLUG- PLUG- The contractor Kontractor Kontractor Contractor Cont	check or other plugs we st. check hole to 3 475' and dump chailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS	ere used, state the state of the sacks off $5\frac{1}{6}$. It is a sack of the sacks of	ed plug of cemer evel with	to 3500', so the angle of same and depth to 3500', so the angle of the	b placed, from_sanded_with	PRPORTION COMMINGS
Introducing it into the hole. If cem feet for each plug se Chec to 3 dump brid read PLUG Ame of Plugging Contractor Koldress C	chent or other plugs we st. cked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS	ere used, state the state of 52!, push ed 5 sacks off 5½!! Leg 1300! to base of the base of the sacks of the base of the sacks of the base of the sacks of the sa	ed plug of cemer evel with	to 3500', so the 3475' has urface, 7½ yards of	b placed, from_sanded_with	PRPORTION COMMINGS
chec feet for each plug se Chec to 3 dump brid read The contractor Karana Chec Chec to 3 dump brid read The contractor Karana Chec Chec Chec to 3 dump brid read The contractor Karana Check	check or other plugs we st. cked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS ANSAS OEL J. Knight	description is neces PULLING COI	e character of plug of cemes evel with and ran cellar.	to 3500', so the 3475' he surface, 7½ yards of this sheet)	b placed, from sanded with STATE CO CONSERVA WICHIES	TION ON-14-16 Kansas
PLUCA The of Plugging Contractor K Iddress C: CATE OF K Ket for each plug se Chec to 3 dump brid read Chec to 3 dump brid Chec to 4 dump brid Chec t	cent or other plugs we to the content of the conten	description is neces PULLING COM	e character of plug of cemes evel with and ran cellar. Sary, use BACK TPANY	to 3500', so the 3475' he surface, 7½ yards of this sheet)	b placed, from sanded with STATE CO CONSERVA WICHIES	TION ON-14-16 Kansas
chec feet for each plug se Chec to 3 dump brid read The contractor Karana Contractor Co	cent or other plugs we to the content of the conten	description is neces PULLING COM	e character of plug of cemes evel with and ran cellar. Sary, use BACK TPANY	to 3500', so the 3475' he surface, 7½ yards of this sheet)	b placed, from sanded with STATE CO CONSERVA WICHIES	TION ON-14-16 Kansas
PLUCA The of Plugging Contractor K Iddress C: CATE OF K Ket for each plug se Chec to 3 dump brid read Chec to 3 dump brid Chec to 4 dump brid Chec t	check hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS ANSAS COU oel J. Knight ays: That I have knot the same are true an	description is neces ONTY OF Gowledge of the idd correct. So h	e character of plug of cemes evel with and ran cellar. Sary, use BACK TPANY	to 3500', so the 3475' he surface, 7½ yards of this sheet)	b placed, from sanded with CONSERVA Wichits ss. ss. conservator) of herein container	MPONTION COMMICS MON ON -14 - (a) Kansas of the above-describe ed and the log of the
PLUCA TATE OF	check hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS ANSAS COU oel J. Knight ays: That I have knot the same are true an	description is neces PULLING COM	e character of plug of cemes evel with and ran cellar. Sary, use BACK TPANY	of same and depth to 3500', so the 3475' the surface, 7\frac{1}{2} yards of (of this sheet) owner) or (many ents, and matters)	Sanded with SAIR CONSERVA Wichilly Sherein contains Leanger To The Control of	MPONTION COMMICS MON ON -14 - (a) Kansas of the above-describe ed and the log of the
PLUCA TATE OF	check hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS ANSAS COU oel J. Knight ays: That I have knot the same are true an	description is neces ONTY OF Gowledge of the idd correct. So h	e character of plug of cemes evel with and ran cellar. Sary, use BACK TPANY	of same and depth to 3500!, so the 3475! the surface, 7½ yards of control of this sheet) owner) or (and ents, and matters)	STATE CONSERVA WICHIELD SS. SS. Scherein contains Kansas	MPONTION COMMICS MON ON -14 - (a) Kansas of the above-describe ed and the log of the
PLUG- The confect for each plug se check to 3 dump brid read read read read read read read rea	check or other plugs we st. cked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS ANSAS COU Oel J. Knight ays: That I have known the same are true an	description is neces PULLING COI NTY OF	e character of plug of cemes evel with and ran cellar. Sary, use BACK TPANY	of same and depth to 3500!, so the 3475! the surface, 7\frac{1}{2} yards of continuous of this sheet) owner) or (and a continuous of the sheet) Chase, (A	STATE CONSERVA Wichilly SS. SS. KANSAS Address)	MPONNION COMMING
chec feet for each plug se Chec to 3 dump brid read PLUC ame of Plugging Contractor K ddress C	check or other plugs we st. cked hole to 3 475' and dump bailer. Cut ged 5½" casin y-mix cement GING COMPLETE NIGHT CASING HASE, KANSAS ANSAS COU Oel J. Knight ays: That I have known the same are true an	description is neces Off of the ide correct. So he ides is a constant of the ides is a constant	e character of plug of cemes evel with and ran cellar. Sary, use BACK TPANY	of same and depth to 3500!, so the 3475! the surface, 7½ yards of control of this sheet) owner) or (and ents, and matters)	SALE CONSERVA STATE CONSERVA WICHIELD SERVE S	MPONNION COMMING