15-065-02596-00-00

STATE OF KANSAS STATE CORPORATION COMMISSION

WELL PLUGGING RECORD

	-7
	Give All Information Completely
:	Make Required Affidavit
	Mail or Deliver Report to:
	Conservation Division
	State Corporation Commission
	800 Bitting Building

21W

	OR		-	
 		~~~~		~~

Strike out upper line

Conservation Division State Corporation Commission			-			
00 Bitting Building	Gra	ham	Coun	ty. Sec. 14	Twp. 10 R	ge 21W % (
Vichita, Kansas	Location as "N	E¼NW¼SW¼'	or footage fro	om linesNW4	SE축 SW축	
NORTH LOS	Lease Owner	Anderson-P	richard O	il Corporat	tion	
	Lease Name	Lewis	Tower Ok	lahoma Cita	r. Oklahom	. Well No2 na
	Office Address	TOOO Apeo	TOWEL OF	Tariona of O	ov Hole	
	Character of W	ell (completed a	ls Oil, Gas or .	Dry Hole)	.y. 11010	19.1
	Appliestion for	nlugging filed	May L.	•••••••		19.1
11.	Application for	nlugging approx	ved May L	(verbal)		19. 1
86	Plugging comm	enced	Мау 4	. 1		19. ^L
	Plugging comp	leted	Мау 4	.3		19. ^L
	Reason for aba	ndonment of we	ell or producing	g formation	dry hole	
0				•••••		
						19
						fore plugging was co
Locate well correctly on above Section Plat	menced?	yes	JD., C+Avo	h		<u> </u>
ne of Conservation Agent who sup-	ervised plugging of th	is well	ാട്ട മരവു	<u>, , , , , , , , , , , , , , , , , , , </u>	T-1-1 D41 -4	. w.u 3816 r
lucing formation			Bottor	n	Total Depth of	WellJOTOF
v depth and thickness of all water,	oil and gas formation	ns.				
L, GAS OR WATER RECORDS	<b>S</b> .	•				CASING RECORD
Formation	Content	From	То	Size	Put In	Pulled Out
	,	0	2751	10-3/4"	2781	none
			1		1	
				-		
ducing it into the hole. If cemer feet for each plug lugged hole with 20 s	nt or other plugs were ; set. acks_cement_a:	used, state the	character of s	ame and depth p	olaced, from	fee
Describe in detail the manner in ducing it into the hole. If cemerfeet for each plug lugged hole with 20 s	nt or other plugs were ; set. acks_cement_a:	t bottom of	character of s  f surface  pp to cap	pipe (275' hole.	); hole f	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug lugged hole with 20 s d to 30 feet of top a	at or other plugs were set. acks cement a nd 15 sacks ce	t bottom of	character of s  f surface  pp to cap	pipe (275' hole.	); hole f	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug lugged hole with 20 s d to 30 feet of top a	at or other plugs were set. acks cement a nd 15 sacks ce	t bottom of ement on to	character of s  f surface  pp to cap	pipe (275' hole.	); hole f	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug lugged hole with 20 s d to 30 feet of top a	at or other plugs were set. acks cement a nd 15 sacks ce	t bottom of ement on to	character of s  f surface  pp to cap	pipe (275' hole.	); hole f	illed with
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s and to 30 feet of top a	at or other plugs were set. acks cement a nd 15 sacks ce	t bottom of ement on to	character of s  f surface  pp to cap	pipe (275' hole.	); hole f	illed with
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s and to 30 feet of top a	at or other plugs were set. acks cement a nd 15 sacks ce	e used, state the  t bottom of ement on to	character of s  f surface  pp to cap	pipe (275' hole.  MAY	); hole f	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a	at or other plugs were set. acks cement a nd 15 sacks ce	e used, state the  t bottom of ement on to	character of s  f surface  pp to cap	pipe (275' hole.  MAY	hole f	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plugged hole with 20 s id to 30 feet of top a constant of the hole.	at or other plugs were set. acks cement a nd 15 sacks cement a cem	description is necessed toAnde.	character of s  f surface pp to cap  sary, use BACK or son-Pric Apco Tow	me and depth pripe (275' hole.  MAY print this sheet) hard Oil Coer	hole f	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plugged hole with 20 s id to 30 feet of top a constant of the hole.	at or other plugs were set. acks cement a nd 15 sacks cement a cem	description is necessed toAnde.	character of s  f surface pp to cap  sary, use BACK or son-Pric Apco Tow	me and depth pripe (275' hole.  MAY print this sheet) hard Oil Coer	hole f	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a constant of the hole. If cemer feet for each plugged hole with 20 s id to 30 feet of top a constant of the hole. If the hole is the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id to 30 feet of top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20 s id top a constant of the hole with 20	at or other plugs were set. acks cement a nd 15 sacks cement a cem	description is necessed to Ande	character of s  f surface pp to cap  sary, use BACK or son-Price Apco Tow homa City	pipe (275' hole.  MAY to this sheet) hard Oil Coer, Oklahoma	Placed, from  ); hole f  1973  1949  rporation	illed with
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s and to 30 feet of top a contract of the hole. The contract of the hole with 20 s and to 30 feet of top a contract of the hole with 20 s and to 30 feet of top a contract of the hole with 20 s and to 30 feet of top a contract of the hole with 20 s and to 30 feet of top a contract of the hole. If cemer feet for each plugged hole with 20 s and to 30 feet of top a contract of the hole. If cemer feet for each plugged hole with 20 s and to 30 feet of top a contract of the hole. If cemer feet for each plugged hole with 20 s and to 30 feet of top a contract of the hole. If cemer feet for each plugged hole with 20 s and to 30 feet of top a contract of the hole.	at or other plugs were set. acks cement a nd 15 sacks cement a cem	description is necessed to Ande	character of s  f surface pp to cap  sary, use BACK or son-Price Apco Tow homa City	pipe (275' hole.  MAY to this sheet) hard Oil Coer, Oklahoma	Placed, from  ); hole f  1973  1949  rporation	illed with
Describe in detail the manner in ducing it into the hole. If cemer feet for each plug Plugged hole with 20 s id to 30 feet of top a correspondence regarding this was ress.  TE OF KANSAS hard Hindery, partner	at or other plugs were set. acks cement a nd 15 sacks cement a left of the	description is necessed to Ande 1000 Okla	character of s  f surface pp to cap  sary, use BACK or son-Price Apco Tow homa City  SEDCWICK	me and depth pripe (275' hole.  MAY roof this sheet) hard Oil Coer, Oklahoma	); hole f	illed with
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s and to 30 feet of top a control of the hole.  Correspondence regarding this was ress.  TE OF KANSAS mard Hindery, partner g first duly sworn on oath, says:	at or other plugs were set.  acks cement a nd 15 sacks cement a left of the	description is necessed to Ande 1000 Okla	sary, use BACK or son-Pric Apco Townhoma City SEDCWICK RILLING Computations of the statements, a	me and depth pripe (275' hole.  MAY roof this sheet) hard Oil Coer, Oklahoma	); hole f	illed with
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and to 30 feet of top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and top a constant of the hole with 20 s and	at or other plugs were set.  acks cement a nd 15 sacks cement a left of the	description is necessed to Ande 1000 Okla  OTY OF BARTLETTEN lege of the facts, ect. So help me	sary, use BACK or son-Pric. Apco Tow. homa City  SEDCWICK RILLING Computations as God.	me and depth pripe (275' hole.  MAY of this sheet) hard Oil Coer, Oklahoma	in poration  scontract  magnitude  for contained ar	or on above w
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s and to 30 feet of top a correspondence regarding this wilress.  ATE OF KANSAS hard Hindery, partner ng first duly sworn on oath, says:	at or other plugs were set.  acks cement a nd 15 sacks cement a left of the	description is necessed to Ande 1000 Okla  OTY OF BARTLETTEN lege of the facts, ect. So help me	sary, use BACK or son-Pric. Apco Tow. homa City  SEDCWICK RILLING Computations as God.	me and depth pripe (275' hole.  MAY of this sheet) hard Oil Coer, Oklahoma	in poration  scontract  magnitude  for contained ar	illed with
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s and to 30 feet of top a correspondence regarding this wilress.  ATE OF KANSAS hard Hindery, partner ng first duly sworn on oath, says:	at or other plugs were set.  acks cement a nd 15 sacks cement a left of the	description is necessed to Ande 1000 Okla  OTY OF BARTLETTEN lege of the facts, ect. So help me	sary, use BACK or son-Price Apco Townhoma City SEDGWICK RILLING Control of the statements, as God.	pipe (275' hole.  MAY to this sheet) hard Oil Coer  Oklahoma  Odrilling and matters herei	is hole f	or on above w
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s ud to 30 feet of top a correspondence regarding this wildress.  Correspondence regarding this wildress.  ATE OF KANSAS hard Hindery, partner ng first duly sworn on oath, says: cribed well as filed and that the sa	or other plugs were set.  acks cement a nd 15 sacks	description is necessed to Ande 1000 Okla  TY OF BARTLETTE 1ge of the facts, ect. So help me (Signature)	sary, use BACK or son-Price Apco Tow homa City SEDCWICK RILLING statements, as God. 705 Per	pipe (275' hole.  MAY for this sheet) hard Oil Coer, Oklahoma	sscontraction contained an address)	or on above what the log of the above the log of the log
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s ud to 30 feet of top a correspondence regarding this wilress.  ATE OF KANSAS hard Hindery, partner ng first duly sworn on oath, says:	or other plugs were set.  acks cement a nd 15 sacks	description is necessed to Ande 1000 Okla  TY OF BARTLETTE 1ge of the facts, ect. So help me (Signature)	sary, use BACK or SON-Price Apco Townhoma City SEDGWICK RILLING Control of the Co	pipe (275' hole.  MAY of this sheet) hard Oil Coer, Oklahoma on drilling and matters herei	is hole for its partition of the contained are contained a	or on above we detail the log of the above the 2, Kansas
Describe in detail the manner in oducing it into the hole. If cemer feet for each plug Plugged hole with 20 s ud to 30 feet of top a correspondence regarding this wilress.  Correspondence regarding this wilress.  ATE OF KANSAS hard Hindery, partner ng first duly sworn on oath, says: cribed well as filed and that the sa	at or other plugs were set.  acks cement a nd 15 sacks cement a nd 15 sa	description is necessed to Ande  TY OF	sary, use BACK or SON-Price Apco Townhoma City SEDGWICK RILLING Control of the Co	pipe (275' hole.  MAY for this sheet) hard Oil Coer, Oklahoma	is hole for its partition of the contained are contained a	or on above we detail the log of the above the 2, Kansas

#### LEWIS NO. 2 WELL

LOCATION:

C- NW4 SE4 SW4 Sec. 14-10S-21W

SPUDDED: April 20, 1949

Graham County, Kansas

COMPLETED: May 3, 1949

**OPERATOR:** 

Anderson-Prichard Oil Corp.

CONTRACTOR:

Birmingham-Bartlett Drilling Co.

SURFACE CASING: Ran 9 jts. 10-3/4" casing, 278 ft., cemented at 275 ft. with 175 sacks cement.

OIL STRING:

None. D & A

## LOG

### (Figures indicate bottom of formation)

0	to	45	Clay and shale	2720	Lime and shale
		275	Shale and shells	2830	Shale, shells and lime
		1000	Sand and shale	3235	Lime and shale
		1150	Shale and shells	3748	Lime
		1320	Sand	3768	Shale and Cong.
		1665	Shale and shells	3789	Lime
		1715	Anhydrite	3805	Conglomerate
		2135	Shale and shells	3816	Cong. & Arbuckle

Total Depth: 3816

The undersigned RICHARD HINDERY of the BIRMINGHAM-BARTLETT DRILLING CO. hereby certifies that the above is a true and correct log of the formations encountered in drilling the above noted well as shown on the daily drilling reports.

BIRMINGHAM-BARTLETT DRILLING CO.

Subscribed and sworn to before me the undersigned Notary Public, on this 5th day of May, 1949.

commission expires November 29, 1950.

