

9-2 15-065-01819-0000

4-031857

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15- - 1954

W2 NW SW /4 SEC. 36, 10 S, 21 W
1980 feet from S section line
4950 feet from E section line

Operator license# 6568

Lease Schneider well # A 4

Operator: Kaiser-Francis Oil Company

County Graham

120.05

Address: P.O. Box 21468
Tulsa, OK 74121-1468

Well total depth 3694 feet
Conductor Pipe: 0 inch @ 0 feet
Surface pipe 8 5/8 Inch @ 207 feet

Aband. oil well X, Gas well , Input well , SWD , D & A

Plugging contractor: Hembre Well Service License# 6907

Address: Ness City, Kansas 67560

Company to plug at: Hour: P.M. Day: 2 Month: September Year: 93

Plugging proposal received from: Gordon

Company: Kaiser-Francis Oil Company Phone:

Were: Order 300 sxs. 65/35 pozmix - 10% gel. - 500# hulls.
Allied Cement Company.

Plugging Proposal Received by: Carl Goodrow

Plugging operations attended by agent? All[X], Part[], None[]

Completed: Hour: 11:00A.M., Day: 2, Month: September, Year: 93

Actual plugging report: 8 5/8" set @ 207' w/125 sxs. 5 1/2" set @ 3664'
w/125 sxs. O.H. 3664' - 3694'. Perf. 3532' - 3596'. Squeezed @ 957'
w/200 sxs. Shots @ 1600' and 2120'. Pipe sanded in to 2500'. Pipe shot
off @ 2500'. Mix and pump through tubing from 2500' to 1350'. Lay down
to 1350'. Circulate cement to surface. Squeeze 5 1/2" with total 250 sx.
cement blend w/300# hulls mixed in to Max. P.S.I. 500#. Close in P.S.I.
500#. Squeeze 8 5/8" w/50 sx. cement blend to Max. P.S.I. 400#. Close
in 150#. Plug complete.

Remarks:

Condition of casing(in hole): GOOD X BAD Anhy. plug: YES X NO
Bottom plug(in place): YES , CALC , NO X Dakota plug: YES X, NO
Plugged through TUBING X, CASING . Elevation: GL

I did[X] / did not[] observe the plugging.

Carl Goodrow

(agent)

RECEIVED
STATE CORPORATION COMMISSION

SEP 22 1993

INVOICED
DATE 9-28-93
INV. NO. 38806

Form CP-20 CONSERVATION DIVISION
Wichita, Kansas