

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-195-21402-00-00
Spot: NENENE Sec/Twnshp/Rge: 9-12S-22W
4950 feet from S Section Line, 330 feet from E Section Line
Lease/Unit Name: BABB Well Number: 41-9
County: TREGO Total Vertical Depth: 4100 feet

Operator License No.: 9152
Op Name: MAREXCO, INC.
Address: 1225 W. MAIN STE. 107
NORMAN, OK 73069

Conductor Pipe: Size feet:
Surface Casing: Size 8.625 feet: 246 160 sxs cmt
Production: Size 4.5 feet: 4100 560 sxs cmt **8 133.25**
Liner: Size feet:

Well Type: OIL UIC Docket No: Date/Time to Plug: 12/04/2001 8:00 AM

Plug Co. License No.: 9152 Plug Co. Name: MAREXCO, INC.

Proposal Rcvd. from: STEPHEN MARDEN Company: MAREXCO, INC. Phone: (405) 321-3238

Proposed Plugging Method: According to KCC Rules and Regulations.
Ordered 200 sxs cement - 10 sxs gel - 400# hulls.

Plugging Proposal Received By: HERB DEINES WitnessType: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 12/04/2001 9:50 AM KCC Agent: ROGER MOSES

Actual Plugging Report:

8 5/8" S.P. at 246' w/160 sxs cement. 4 1/2" casing at 4100' w/560 sxs cement.
Tied to 4 1/2" casing and pumped 40 sxs cement with 400# hulls,
followed with 10 sxs gel and finished with 110 sxs cement.
Max. P.S.I. 800#. S.I.P. 500#.
Tied to 8 5/8" x 4 1/2" annulus and squeezed 5 sxs to Max. P.S.I. 500#.
Total of 155 sxs 60/40 pozmix - 10% gel - 10 sxs gel with 400# hulls.

Remarks: ALLIED CEMENTING COMPANY. WERTH TANK - WATER.

Plugged through: CSG

District: 04

Signed

Roger B. Moses
(TECHNICIAN)

RECEIVED
12-14-2001
DEC 14 2001
NCC WICHITA

INVOICED

DATE 12-19-01
INV. NO. 2002061070

Form CP-2/3


DEC 07 2001

MAREXCO
 3025 QUAIL ST. #41-9 BABB 9-12-22W
 LAKEWOOD, CO 80215 NE NE NE

CONTR WHITE & ELLIS DRIG. CTY TREGO

GEOL _____ FIELD SHAW CREEK SO.
EXT (1/8 SW)

ELV 2384 KB SPD 1/7/84 CARD ISSUED 4/19/84 IP P 48 BOPD, NW
MARM 4010-4027 OA



LOG	Tops	Depth/Datum
ANH	1820+ 564
HEEB	3630-1246
TOR	3652-1268
LANS	3665-1281
MARM	3996-1612
ARB	4082-1698
LTD	4097-1713
RTD	4100-1716

API 15-195-21,402
 8 5/8 " 246; E 4 1/2 " 4100
 DST (1) 3670-3698 (LKC) / 60-90-60-90, REC 240' MSW, SIP
 1272-1237#, FP 44-66 / 88-150#, HP 1932-1909#
 DST (2) 3748-3759 (LKC) / 60-60-165-60, REC 750' MSW, SIP
 849-838#, FP 22-207 / 242-392#, HP 1931-1909#
 DST (3) 4005-4050 (MARM) / 60-90-60-90, REC 130' OCM, W/
 SOME FO ON TOP, SIP 1180-1123#, FP 55-55 / 88-88#, HP
 2102-2079#
 MICT - CO, PF (MARM) 4010-16 & 4023-27, W/1 SPF, AC 500G
 (15% MCA), SWB DWN, RE-AC 2000G (7.5% HCL), FRAC
 40,000G 2% GEL KCL WTR & 22,000# SD, SWB DWN, GSC,
 POP, P 48 BOPD, NW, 2/10/84