

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-195-21679-00-00
Spot: CNWNESW Sec/Twnshp/Rge: 9-12S-22W
2310 feet from S Section Line, 3630 feet from E Section Line
Lease/Unit Name: BABB Well Number: 23-9
County: TREGO Total Vertical Depth: 4145 feet

Operator License No.: 9152
Op Name: MAREXCO, INC.
Address: 1225 W. MAIN STE. 107
NORMAN, OK 73069

Conductor Pipe: Size feet: 8 1/4
Surface Casing: Size 8.625 feet: 248 175 SX CMT
Production: Size 4.5 feet: 4144 575 SX CMT
Liner: Size feet:

Well Type: OIL UIC Docket No: Date/Time to Plug: 12/04/2001 10:00 AM

Plug Co. License No.: 9152 Plug Co. Name: MAREXCO, INC.

Proposal Rcvd. from: STEPHEN MARDEN Company: MAREXCO, INC. Phone: (405) 321-3238

Proposed Plugging Method: According to KCC Rules and Regulations.
Ordered 200 sxs cement - 10 sxs gel - 400# hulls.

Plugging Proposal Received By: HERB DEINES

WitnessType: Plugging Operations 100% Witnessed (Complete)

Date/Time Plugging Completed: 12/04/2001 10:45 AM

KCC Agent: ROGER MOSES

Actual Plugging Report:

8 5/8" S.P. at 248' w/175 sxs cement. 4 1/2" casing at 4144' w/575 sxs cement.
Tied to 4 1/2" casing and pumped 40 sxs cement and 400# hulls,
followed with 10 sxs gel and pumped 120 sxs into 4 1/2".
Max. P.S.I. 600#. S.I.P. 300#.
Tied to 8 5/8" x 4 1/2" annulus and pressured to 500#. Took no cement.
Total of 160 sxs 60/40 pozmix - 10% gel - 10sxs gel - 400# hulls.

Remarks: ALLIED CEMENTING COMPANY. WERTH-WATER.

Plugged through: CSG

District: 04

Signed

Roger B. Moses

(TECHNICIAN)

RECEIVED
12-14-2001
DEC 14 2001

KCC WICHITA

INVOICED


DATE 12-19-01

INV. NO. 2002061070

Form CP-2/3

DEC 07 2001

MAREXCO
 3025 QUAIL STREET #23-9 BABB 9-12-22W
 LAKEWOOD, CO 80215 NW NE SW
 CONTR BEVIN DRILLING CTY TREGO
 GEOL STEVE MARDEN FIELD RINKER SE EXT
 (1/8 S)
 ELV 2377 K.B. SPD 3/11/85 CARD ISSUED 5/30/85 IP P 17.5 BO & 50 BWPD
2372 GL MARM 4000-4027



LOG	Tops	Depth/Datum
ANH	1810 + 567
TOP	3405-1026
HEEB	3623-1246
TOR	3643-1266
LANS	3660-1283
BKC	3907-1530
MARM	3992-1615
ARB	4093-1716
RTD	4145-1768

API 15-195-21,679
 8 5/8 " 248 / 175SX, 4 1/2 " 4144
 DST (1) 3678-3710 (LANS) / 35-63-15-99, REC 40' M, SIP 831-841#, FP 51-51 / 65-65#, HP 1989-1952#
 DST (2) 3995-4030 (MARM) / 70-60-20-90, REC 40' SOCM, SIP 764-782#, FP 45-45 / 65-65#, HP 2236-2146#
 MICT - CO, PE (MARM) 1 / 4000-27, AC 1000G (7.5%) & 500G (HCL), SWB DWN; FRAC 4000G (GELLED PAD) & 13,300# SD & 2500G (GELLED-FLSH) & 1900G (KCL), SWB DWN, SO, POP, P 17.5 BO & 50 BWPD, 4/28/85