

CONFIDENTIAL

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

ORIGINAL

Form ACO-1
September 1999
Form Must Be Typed

2/25/10

AMENDED

WELL COMPLETION FORM
WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33365
Name: Layne Energy Operating, LLC
Address: 1900 Shawnee Mission Parkway
City/State/Zip: Mission Woods, KS 66205
Purchaser: _____
Operator Contact Person: Timothy H. Wright
Phone: (913) 748-3960
Contractor: Name: Thornton Air Rotary
License: 33606
Wellsite Geologist: _____

CONFIDENTIAL
FEB 25 2008
KCC

Designate Type of Completion:
____ New Well ____ Re-Entry ____ Workover
____ Oil ____ SWD ____ SLOW ____ Temp. Abd.
 Gas ____ ENHR ____ SIGW
____ Dry ____ Other (Core, WSW, Expl., Cathodic, etc)

If Workover/Re-entry: Old Well Info as follows:
Operator: _____

Well Name: _____
Original Comp. Date: _____ Original Total Depth: _____
____ Deepening ____ Re-perf. ____ Conv. to Enhr./SWD
____ Plug Back ____ Plug Back Total Depth
____ Commingled Docket No. _____
____ Dual Completion Docket No. _____
____ Other (SWD or Enhr.?) Docket No. _____

<u>9/4/2007</u>	<u>9/6/2007</u>	<u>11/9/2007</u>
Spud Date or Recompletion Date	Date Reached TD	Completion Date or Recompletion Date

API No. 15 - 125-31427-00-00
County: Montgomery
____ NW ____ SW ____ NW Sec. 11 Twp. 32 S. R. 13 East West
1556 feet from S / (circle one) Line of Section
351 feet from E / (circle one) Line of Section
Footages Calculated from Nearest Outside Section Corner:
(circle one) NE SE (NW) SW
Lease Name: Scovel Well #: 5-11
Field Name: Cherokee Basin Coal Area
Producing Formation: Cherokee Coals
Elevation: Ground: 846' Kelly Bushing: _____
Total Depth: 1535' Plug Back Total Depth: 1529'
Amount of Surface Pipe Set and Cemented at 121 Feet
Multiple Stage Cementing Collar Used? Yes No
If yes, show depth set _____ Feet
If Alternate II completion, cement circulated from 1529
feet depth to Surface w/ 160 sx cmt.

Drilling Fluid Management Plan AH INS 6-2-09
(Data must be collected from the Reserve Pit)
Chloride content N/A ppm Fluid volume _____ bbls
Dewatering method used N/A - Air Drilled
Location of fluid disposal if hauled offsite: _____
Operator Name: _____
Lease Name: _____ License No.: _____
Quarter _____ Sec. _____ Twp. _____ S. R. _____ East West
County: _____ Docket No.: _____

INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, Kansas 67202, within 120 days of the spud date, recompletion, workover or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information of side two of this form will be held confidential for a period of 12 months if requested in writing and submitted with the form (see rule 82-3-107 for confidentiality in excess of 12 months). One copy of all wireline logs and geologist well report shall be attached with this form. ALL CEMENTING TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form with all temporarily abandoned wells.

All requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Signature: [Signature]
Title: Agent Date: 2/27/2008
Subscribed and sworn to before me this 27 day of February,
2008
Notary Public: MacLaughlin Darling
Date Commission Expires: 1-4-2009

MacLAUGHLIN DARLING
Notary Public - State of Kansas
My Appt. Expires 1-4-2009

KCC Office Use ONLY
 Letter of Confidentiality Attached
 If Denied, Yes No Date _____
KANSAS CORPORATION COMMISSION
Wireline Log Received
Geologist Report Received **FEB 28 2008**
CONSERVATION DIVISION
WICHITA, KS

CONFIDENTIAL

5-11 FEB 25 2008

KCC

Operator Name: Layne Energy Operating, LLC Lease Name: Scovel Well #: 5-11
 Sec. 11 Twp. 32 S. R. 13 East West County: Montgomery

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: Compensated Density Neutron Dual Induction	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input type="checkbox"/> Sample <table style="width:100%; border-collapse: collapse;"> <tr> <td style="width:60%;">Name</td> <td style="width:20%;">Top</td> <td style="width:20%;">Datum</td> </tr> <tr> <td>Pawnee Lime</td> <td>999 GL</td> <td>-153</td> </tr> <tr> <td>Excello Shale</td> <td>1134 GL</td> <td>-288</td> </tr> <tr> <td>V Shale</td> <td>1186 GL</td> <td>-340</td> </tr> <tr> <td>Mineral Coal</td> <td>1231 GL</td> <td>-385</td> </tr> <tr> <td>Mississippian</td> <td>1483 GL</td> <td>-637</td> </tr> </table>	Name	Top	Datum	Pawnee Lime	999 GL	-153	Excello Shale	1134 GL	-288	V Shale	1186 GL	-340	Mineral Coal	1231 GL	-385	Mississippian	1483 GL	-637
Name	Top	Datum																	
Pawnee Lime	999 GL	-153																	
Excello Shale	1134 GL	-288																	
V Shale	1186 GL	-340																	
Mineral Coal	1231 GL	-385																	
Mississippian	1483 GL	-637																	

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacjs Used	Type and Percent Additives
Surface	11"	8.625"	24	121'	Class A	65	Type 1 cement
Casing	6.75"	4.5"	10.5	1529'	Thick Set	160	#10 KOL seal @ sx

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
<input type="checkbox"/> Perforate <input type="checkbox"/> Protect Casing <input type="checkbox"/> Plug Back TD <input type="checkbox"/> Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
	See Attached Page		

TUBING RECORD		Size <u>2-3/8"</u> Set At <u>1331'</u> Packer At	Liner Run <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Date of First, Resumerd Production, SWD or Enhr. <u>12/19/2007</u>		Producing Method <input type="checkbox"/> Flowing <input checked="" type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)	
Estimated Production Per 24 Hours	Oil Bbls. <u>0</u>	Gas Mcf <u>95</u>	Water Bbls. <u>0</u> Gas-Oil Ratio Gravity

RECEIVED
KANSAS CORPORATION COMMISSION

Disposition of Gas <input type="checkbox"/> Vented <input checked="" type="checkbox"/> Sold <input type="checkbox"/> Used on Lease <i>(If vented, Submit ACO-18.)</i>	METHOD OF COMPLETION <input type="checkbox"/> Open Hole <input checked="" type="checkbox"/> Perf. <input type="checkbox"/> Dually Comp. <input checked="" type="checkbox"/> Commingled <input type="checkbox"/> Other (Specify) _____	Production Interval
--	---	---------------------

FEB 28 2008

**CONSERVATION DIVISION
WICHITA, KS**

CONFIDENTIAL
FEB 25 2008
KCC

Operator Name:	Layne Energy Operating, LLC.		
Lease Name:	Scovel 5-11		
	Sec. 11 Twp. 32S Rng. 13E, Montgomery County		
API:	15-125-31427-00-00		
Shots per Foot	Perforation Record	Acid, Fracture, Shot, Cement Squeeze Record	Depth
Initial Perforations			
4	Mineral 1230.5' - 1232'	3601 lbs 20/40 sand 282 bbls water 300 gals 15% HCl acid	1230.5' - 1232'
4	V-Shale 1186.5' - 1189' Bevier 1166' - 1167.5'	7603 lbs 20/40 sand 601 bbls water 300 gals 15% HCl acid	1166' - 1189'
4	Mulky 1134' - 1137.5' Summit 1112' - 1114.5'	1280 lbs 20/40 sand 673 bbls water 400 gals 15% HCl acid	1112' - 1137.5'

RECEIVED
KANSAS CORPORATION COMMISSION
FEB 28 2008
CONSERVATION DIVISION
WICHITA, KS