4-050164

,'	
TO: STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING 200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	API number: 15-065-22,715-00-00 NW SW SE
	Lease G. Hobbs well # 1
Address: P.O. Box 32 Morland, Kansas 67650	Well total depth 4038 feet Conductor Pipe: inch e feet Surface pipe 8 5/8 inch e 223 feet
Aband. oil well, Gas well, Input well, SWD, D & A _X	
Plugging contractor: <u>Helberg Oil Company</u> License# <u>5669</u>	
Address:	
Company to plug at: Hour: PM Day:	25 Month: June Year: 1993
Plugging proposal received from: <u>Jerry Helberg</u>	
Company: Helberg Oil Company phone: 913-627-5665	
Were: Spot plugs through drill pipe w/ heavy mud between all plugs.	
1st plug @ 2150 feet with 25 sacks	Rat hole: 15 sacks
2nd plug @ 1260 feet " 100 "	
3rd plug @ <u>275</u> feet " 40 "	
4th plug @ 40 feet " 10	with 8 5/8" wiper plug
Plugging Proposal Received by: <u>Marvin L. Miller</u>	
Plugging operations attended by agent? All[], Part[], None[X]	
Completed: Hour: 12:45 PM, Day: 25, Month: June, Year: 1993	
Actual plugging report: <u>Hole reported plugged as above.</u> Order 190 sx 60/40 pozmix w/ 6% gel and 1/4# celloflake or flowcel per sk	
Remarks:Elevation: <u>2483</u> , Anhydrite: <u>2132-2168</u> feet, Anhydrite plug: <u>2150</u> Bottom plug (in place): Yes X , Calc , No Arbuckle: None	
Did NOT penetrate Arbuckle, cemented by Allied Cementing Company 8-2-100 Note	
I did [] did not [X] observe the plugging. Marin R. Milly - 2 1993	
AUS 0 4 1993	Marvin L. Miller P.I.R.T.II