| TO: STATE CORPORATION COMMISSIO | API Well Number: <u>15-107-24130-00-00</u> | |
|---|---|---|
| CONSERVATION DIVISION - PLUGGIN | Spot: <u>NWSESESW</u> Sec/T 383 feet from S Section Line, | wnshp/Rge: <u>35-21S-22E</u> <u>3076</u> feet from <u>E</u> Section Line |
| 130 SOUTH MARKET, SUITE 2078 | Lease Name: LANHAM | Well #: 14-35S |
| WICHITA, KANSAS 6720 | County: LINN | Total Vertical Depth: 800 feet |
| Operator License No.: 5150 | | |
| Op Name: COLT ENERGY INC | | |
| Address: PO BOX 388 IOLA, KS 66749 | | |
| Well Type: OIL UIC Docket N | o: Date/Time | to Plug: 02/01/2010 2:30 PM |
| · · · · · · · · · · · · · · · · · · · | CONSOLIDATED OIL WELL SERVI | CES, INC |
| Proposal Rcvd. from: SHIRLEY STOTLER | Company: COLT ENERGY, INC. | Phone: |
| Proposed Plugging Method: CEMENT PLUGS AT TD, 450 FEET, AND | FROM 250 FEET TO SURFACE WIT | H GEL SPACERS. |
| Plugging Proposal Received By: JOHN ALMOND WitnessType: COMPLETE (100%) | | |
| Date/Time Plugging Completed 02/01/2010 12:00 At | M KCC Agent: <u>LEVI SHOR</u> | <u>T</u> |
| Actual Plugging Report: | | Perfs: |
| PUMP CEMENT THROUGH 1-INCH PIPE INSIDE 7- | | |
| PLUG AT 800 FEET, 50 FOOT CEMENT PLUG AT 4 FEET TO SURFACE WITH CEMENT. GEL SPACERS | | |
| CEMENT PLUGS. USE TOTAL OF 65 SACKS OF CE | EMENT. | |
| | | |
| | ſi | |
| | | |
| | D | TE 3/01/10 |
| | | W. NO. 2010060913 |
| | RECEIVED | DECEMEN. |
| M | AR 1 2010 LS | RECEIVED KANSAS CORPORATION COMMISSION |
| ксс | Chanute Dist. #3 | MAR 0 8 2010 |
| | | CONSERVATION DIVISION WICHITA, KS |
| Remarks: | | |
| Plugged through: <u>TBG</u> | • | |
| District: 03 Sig | ned Rillia | |

(TECHNICIAN)