8-12

E-14,576	
FO: API number: 15-065-20,201-000	
STATE CORPORATION COMMISSION (TWIN) 100'NW	
CONSERVATION DIVISION - PLUGGING NW SW NE /4 SEC. 15 , 10 S, 25 W	
200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202 3730 feet from S section line feet from E section line	
WICHITA, KANSAS 67202 2310 feet from E section line	
Operator license# <u>3553</u> Lease <u>Elrick</u> well # <u>3-4 Unit</u>	<u> </u>
Operator: Citation Oil & Gas Corporation County Graham	
Address: 8223 Willow Place Well total depth 3987 feet Conductor Pipe: 0 inch 0 0 feet	
Suite 250 Conductor Pipe: 0 inch 0 0 feet	
Suite 250Conductor Pipe:0 inch @ 0 feetHouston, Texas 77070Surface pipe 8 5/8 Inch @ 192 feet	
Aband. oil well, Gas well, Input well <u>X</u> , SWD, D & A	
Plugging contractor: <u>Halliburton Services</u> License# -	
License#	
Address: <u>Hays, Kansas 67601</u>	
Company to plug at: Hour: P.M. Day: 12 Month: August Year: 94	
Plugging proposal received from: <u>Don</u>	
Company: Citation Oil & Gas Corporation Phone:	
Vere: Order 425 sxs. 60/40 pozmix - 8% gel - 100 sxs. common - 800# hulls Halliburton Services.	
Work string of 2 3/8" tubing.	
Plugging Proposal Received by: <u>Carl Goodrow</u>	
Plugging operations attended by agent? All[], Part[X], None[]	
'ompleted. Hour.1.15D M. Day. 12 Month. Buguet	
ompleted: Hour: 1:15P.M., Day: 12 , Month: August , Year: 94	
ctual plugging report: 8 5/8" set @ 192' w/150 sxs. 5 1/2" set @ 3987'	
<u>/150 sxs. PBTD 3976'. Prod. perfs.</u> 3738' - 3956'. Critical area	
control shots @ 2150' and 1240' w/3 holes each. Run tubing to 3932'.	
potted 100 sxs. common cement with 400# nulls. Pulled to 2119'.	
ith 75 sxs. Pulled tubing. Hooked-up 5 1/2" 165 sxs. cement blent conference	
/100# hulls. Used total 440 sxs. cement with 700# hulls.	
potted 100 sxs. common cement with 400# hulls. Pulled to 2119'. potted 100 sxs. cement with 200# hulls. Pulled to 1210' - circulated ith 75 sxs. Pulled tubing. Hooked-up 5 1/2" 165 sxs. cement blend confice to the first confice to the fir	10n
- 4 190 ₄	- 70
ondition of casing(in hole):GOOD X BAD Anhy.plug:YES X NO WATTON	
ottom plug(in place):YES,CALC 7 ,NO Dakota plug:YES X .NO"4 & A SUCCESSION DAKOTA PLUG:YES X .NO"4 & A SUCCESSION DAKOTA PLUG:YES X .NO DAKOTA PLUG:YE	
lugged through TUBING , CASING . Elevation: GL	
·	
did X y did not] observe the plugging.	
9-36-94 (agent)	