

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-065-20424-00-01
Spot: E2W2SE Sec/Twnshp/Rge: 22-10S-25W
1320 feet from S Section Line, 1650 feet from E Section Line
Lease/Unit Name: KNOLL Well Number: 3
County: GRAHAM Total Vertical Depth: 1892 feet

Operator License No.: 31086
Op Name: RICHLAN DRILLING
Address: 598 - 2ND AVE.
BEAVER, KS 67525

Conductor Pipe: Size feet:
Surface Casing: Size 8.625 feet: 204 150 SX CMT
Production: Size 4.5 feet: 1892
Liner: Size feet:

Well Type: SWD UIC Docket No: D17035.0 Date/Time to Plug: 06/18/2002 12:00 PM
Plug Co. License No.: 6901 Plug Co. Name: D S & W WELL SERVICING, INC.
Proposal Rcvd. from: RICK SCHREIBER Company: RICHLAN DRILLING Phone: (620) 587-3605

Proposed According to KCC Rules & Regulations.
Plugging Rig over the hole.
Method: Ordered 150 sxs cement.

Plugging Proposal Received By: HERB DEINES Witness Type: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 06/18/2002 1:30 PM KCC Agent: ROGER MOSES

Actual Plugging Report:

8 5/8" S.P. at 204' w/150 sxs cement.
4 1/2" casing at 1892' with cement circulated - unknown amount.
2 3/8" tubing cemented in hole from 1670' to surface.
Tied to tubing and squeezed 45 sxs cement to Max.P.S.I. 1000#. S.I.P. 0#.
Tied to 2 3/8" x 4 1/2" and pressure to Max. P.S.I. 700#. S.I.P. 0#.
Tied to 4 1/2" x 8 1/2" and squeezed 50 sxs cement to Max. P.S.I. 300#. S.I.P. 100#.
Total of 94 sxs 60/40 pozmix with 10% gel.

RECEIVED
8-9-2002
AUG 09 2002
KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY.


Plugged through: TBG

District: 04

Signed Roger Moses by Herb Deines
(TECHNICIAN)

INVOICE
DATE 8-9-02
WV # 2003060210 Form CP-2/3

AMERICAN DRILLING CO., LT #3 ¹⁰⁰ KNOLL 22-10-25W
 WICHITA, KANSAS C E/2 W/2 SE
 CONTR CO. TOOLS CTY GRAHAM
 GEOL FIELD AMBROSE
 E 2506 KB. CM 4/12/71 ^{CARD} ISSUED 5/13/71 IP D&A/LANS
 4/22/71



API 15-065-20, 424

SMP . TOPS	DEPTH	DATUM
ANHY	2142	+ 364
TOP	3553	-1047
QH	3711	-1205
HFFB	3769	-1263
TOR	3789	-1283
LANS	3811	-1305
RID	4020	-1514

8 5/8" 204/1505X

DST(1) 3845-60(LANS)/40", 2400' WTR, BHP
 1360-1320#/20", FP 300-1130#
 DST(2) 3875-90(LANS)/2', 120' GIP, 1950'
 MDY SGCSW, RAINBOW 50, BHP 1410-
 1340#/20", FP 144-1010#
 DST(3) 3924-55(LANS)/40", 15'M, BHP
 110-110#/15", FP 110-110#
 DST(4) 3996-4020(LANS)/40", 195'M, NO
 PRESS

NO LOG

INDEPENDENT OIL & GAS SERVICE
 WICHITA, KANSAS

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-065-20424-00-01
Spot: E2W2SE Sec/Twnshp/Rge: 22-10S-25W
1320 feet from S Section Line, 1650 feet from E Section Line
Lease/Unit Name: KNOLL Well Number: 3
County: GRAHAM Total Vertical Depth: 4020 feet

Operator License No.: 31086
Op Name: RICHLAN DRILLING
Address: 598 - 2ND AVE.
BEAVER, KS 67525

Conductor Pipe: Size feet: 8/30.65
Surface Casing: Size 8.625 feet: 204 150 SX CMT
Production: Size 4.5 feet: 1892
Liner: Size feet:

Well Type: SWD UIC Docket No: D17035.0 Date/Time to Plug: 06/18/2002 12:00 PM
Plug Co. License No.: 6901 Plug Co. Name: D S & W WELL SERVICING, INC.
Proposal Rcvd. from: RICK SCHREIBER Company: RICHLAN DRILLING Phone: (620) 587-3605

Proposed Plugging Method: According to KCC Rules & Regulations.
Rig over the hole.
Ordered 150 sxs cement.

Plugging Proposal Received By: HERB DEINES Witness Type: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 06/18/2002 1:30 PM KCC Agent: ROGER MOSES

Actual Plugging Report:

8 5/8" S.P. at 204' w/150 sxs cement.
4 1/2" casing at 1892' with cement circulated - unknown amount.
2 3/8" tubing cemented in hole from 1670' to surface.
Tied to tubing and squeezed 45 sxs cement to Max.P.S.I. 1000#. S.I.P. 0#.
Tied to 2 3/8" x 4 1/2" and pressure to Max. P.S.I. 700#. S.I.P. 0#.
Tied to 4 1/2" x 8 1/2" and squeezed 50 sxs cement to Max. P.S.I. 300#. S.I.P. 100#.
Total of 94 sxs 60/40 pozmix with 10% gel.

RECEIVED
7-15-2002
JUL 15 2002
KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: TBG

District: 04

Signed Raymond Moses
(TECHNICIAN)


INVOICED

DATE 7-19-02
2003060076

JUL 08 2002

AMERICAN DRILLING CO., LT #300 KNOLL 22-10-25W
 WICHITA, KANSAS C E/2 W/2 SE
 CONTR CO. TOOLS CTY GRAHAM

GEOL FIELD AMBROSE
 E 2506 KB CM 4/12/71 ^{CARD} ISSUED 5/13/71 IP D&A/LANS
 4/22/71



API 15-065-20,424

SMP	TOPS	DEPTH	DATUM
ANHY		2142	+ 364
TOP		3553	-1047
QH		3711	-1205
HEFB		3769	-1263
TQR		3789	-1283
LANS		3811	-1305
RID		4020	-1514

8 5/8" 204/150SX
 DST(1) 3845-60(LANS)/40", 2400'WTR, BHP
 1360-1320#/20", FP 300-1130#
 DST(2) 3875-90(LANS)/2', 120'GIP, 1950'
 MDY SGCSW, RAINBOW SO, BHP 1410-
 1340#/20", FP 144-1010#
 DST(3) 3924-55(LANS)/40", 15'M, BHP
 110-110#/15", FP 110-110#
 DST(4) 3996-4020(LANS)/40", 195'M, NO
 PRESS

NO LOG

INDEPENDENT OIL & GAS SERVICE
 WICHITA, KANSAS