ORIGINAL

*****

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

Form ACO-1
- October 2008
Form Must Be Typed

WICHITA, KS

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License # 32309	API No. 15 - 081-21724-0000 02
Name: Presco Western, LLC	Spot Description:
Address 1: 5665 Flatiron Parkway	SW_SE_NE_SE_Sec. 30 Twp. 30 S. R. 33 East West
Address 2:	1614 Feet from North / South Line of Section
City: Boulder State: CO Zip: 80301 +	599 Feet from 📝 East / 🗌 West Line of Section
Contact Person: Susan Sears	Footages Calculated from Nearest Outside Section Corner:
Phone: (303) 444-8881	□NE □NW ☑SE □SW
CONTRACTOR: License #	County: Haskell
Name:	Lease Name: SWLVLU Well #: 9
Wellsite Geologist:	Field Name: Lemon Victory
Purchaser:	Producing Formation: Lansing
Designate Type of Completion:	Elevation: Ground: 2949' Kelly Bushing: 2961'
New Well Re-Entry Workover	Total Depth: 4400' Plug Back Total Depth: 4139'
✓ Oil SWD SIOW	Amount of Surface Pipe Set and Cemented at: 1748' Feet
Gas ENHR SIGW	Multiple Stage Cementing Collar Used?
CM (Coal Bed Methane) Temp. Abd.	If yes, show depth set: 3266' Feet
Dry Other(Core, WSW, Expl., Cathodic, etc.)	If Alternate II completion, cement circulated from:
If Workover/Re-entry: Old Well Info as follows:	feet depth to:w/sx cmt/sv
Operator: Presco Western	feet depth to: w/ wo - Do - #13/10 Drilling Fluid Management Plan
Well Name: SWIVIU 9	(Data must be collected from the Reserve Pit)
Original Comp. Date: 9 (18 67 Original Total Depth: 4400	Chloride content: ppm Fluid volume: bbls
Deepening Re-perf Conv. to Enhr Conv. to SWD	Dewatering method used:
Plug Back:Plug Back Total Depth	Location of fluid disposal if hauled offsite:
Commingled Docket No.:	
Dual Completion	Operator Name:
Other (SWD or Enhr.?) Docket No.:	Lease Name: License No.:
11/4/2009 11-4-09	Quarter Sec TwpS. R East West
Spud Date or Date Reached TD Completion Date or Recompletion Date Recompletion Date	County: Docket No.:
INSTRUCTIONS: An original and two copies of this form shall be filed with the Kansas 67202, within 120 days of the spud date, recompletion, workover or cort of side two of this form will be held confidential for a period of 12 months if requitiality in excess of 12 months). One copy of all wireline logs and geologist well BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 form	nversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information ested in writing and submitted with the form (see rule 82-3-107 for confiden-report shall be attached with this form. ALL CEMENTING TICKETS MUST
All requirements of the statutes, rules and regulations promulgated to regulate the	e oil and gas industry have been fully complied with and the statements herein
are complete and correct to the best of my knowledge.	
Signature: HWAN HEAVY	KCC Office Use ONLY
Title: KS/CO Engineering Manager Date: 1/28/2010	Letter of Confidentiality Received
Subscribed and sworn to be fore methis 20 day of	/ If Denied. Yes □ Date:
	DECEIVED
20 10 Blackburg Blackburg	Wireline Log Received RECCTV COMMISSION Geologist Report RESENSAS CORPORATION COMMISSION
Notary Public:	UIC Distribution FEB 0 1 2010
Date Commission Expires 0/29/20/5	CONSERVATION DIVISION

Side Two

Operator Name: Presco Western, LLC Leas					ease Name: SWLVLU		Well #: 9				
Sec. 30 Twp. 3			st 🗸 West	Coun	y: Hask	ell	· · · · · · · · · · · · · · · · · · ·		 		
INSTRUCTIONS: So time tool open and cl recovery, and flow ra surveyed. Attach final	osed, flowing and s tes if gas to surface	hut-in pres test, along	sures, whether	shut-in pre	ssure rea	ched static level	, hydrostatic	pressures, bottom	hole tempe	erature, fluid	
Drill Stem Tests Taken Yes (Attach Additional Sheets)			Yes No			Log Formation (Top), De		oth and Datum	s	Sample	
Samples Sent to Geological Survey		Yes No	Name			Тор			atum		
Cores Taken Electric Log Run (Submit Copy)			Yes No Yes No								
List All E. Logs Run:											
		Rep		RECORD	Ne	w Used	ion, etc.				
Purpose of String	Size Hole Drilled		ize Casing et (In O.D.)		ight / Ft.	Setting Depth	Type o Cemer		Type and Percent Additives		
Surface	11"	7"	" 17			1748'	65/35	700	3% CC,	1/4 Floseal	
DV Tool						3266'	Lite	350	1/4 Floseal		
Production	6 1/4"	4 1/2"		10.5		4400'	ASC/Lite	50/50	<u> </u>	10% salt	
		1	ADDITIONA	L CEMENT	ING / SQL	EEZE RECORD	-	KANSAS	REC	EIVED TION COMMISSI	
Purpose: —— Perforate	Depth Top Bottom	Type of Cement		#Sacks Used		Type and Percent Additives					
Protect Casing Plug Back TD Plug Off Zone						CONSERVATION DIVISI					
ridg on zone					WICHITA, K					A, KS	
Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Acid, Specify Footage of Each Interval Perforated						racture, Shot, Cement Squeeze Record (Amount and Kind of Material Used) Depth				
4	4106'-4114' (l	ansing	B1)			1000 gals 15% NEFE, 30 bbls 4% KCl flush					
4 4122'-4132' (Lansing B2)						1000 gals 15% NEFE, 30 bbls 4% KCl flush					
	CIBP @ 4139	•	·				:				
4	4142'-4160' (Lansing C)					2000 gals 15% NEFE, 18 bbls 4% KCl flush					
							·				
TUBING RECORD: 2:	Size: 3/8"	Set At 4136'		Packer A	At:	Liner Run:	Yes [No			
Date of First, Resumed 11/5/2009	Production, SWD or E	nhr.	Producing Met		Flowing	Pumpin	ng 🔲 G	as Lift Othe	er <i>(Explain)</i>		
Estimated Production Per 24 Hours	Oil 13	Bbls.	Gas 0	Mcf	Wate	r Bt 246	ols.	Gas-Oil Ratio		Gravity	
DISPOSITION OF GAS: METHOD Vented Sold Used on Lease Open Hole Perf. (If vented, Submit ACO-18.) Other (Specify)						COMPLETION: PRODUCTION INTERVAL: Dually Comp. Commingled 4106'-4114', 4122'-4132'			L:		