

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 063-21, 016-00-00  
200' EAST  
SE-NW-NW, SEC. 19, T. 12 S, R. 30 W  
4290 feet from S section line  
4090 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5146 Lease Name Thielen Well # 1

Operator: Rains & Williamson Oil Co. County Gove 149.18

Name & Address 435 Page Court, 220 West Douglas, Wichita, Kansas, 67202 Well Total Depth 4290 feet

Juanita, Green. Conductor Pipe: Size 0 feet

Surface Casing: Size 8 5/8 feet 301

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A X

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Rains & Williamson Oil Co. License Number \_\_\_\_\_

Address 435 Page Court, 220 West Douglas, Wichita, Kansas, 67202

Company to plug at: Hour: 12:00 PM Day: 31st Month: March Year: 86

Plugging proposal received from Mike Godfrey

(company name) Rains and Williamson Oil (phone) 316-265-9686

were: 8 5/8" 301 EI 50' emt w/ 200 5x 60 1/4 Foamix Gel - Ca-cl, B.J. Titan.

Proposal - Order 205 5x 60 1/4 Foamix Gel - Ca-cl, 1 5x 60 1/4 Plug

spot with Drill Stem, Reconditioned Hole (viscosity) Heavy Mud Between All Plugs

No Circulation Problems, Elev. 2883, July 2366', (Miss. well)

Plugging Proposal Received by Marion Schmidt (TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None X

Operations Completed: Hour: 12:00 PM Day: 31st Month: March Year: 19 86

ACTUAL PLUGGING REPORT Ordered 205 5x 60 1/4 Foamix Gel - Ca-cl - 1 Plug + 8 5/8" Plug

spot with Drill Stem, Reconditioned Hole, Heavy Mud Between All Plugs

1st Plug @ 2380 EI w/ 30 5x emt, 2nd Plug @ 2480 EI w/ 100 5x emt

3rd Plug @ 250 EI w/ 20 5x emt, 4th Plug 50' Solid Bridge Plug @ 40' w/ 0 1/10 emt

15' In Cat Hole Circulate, Cemented By B.J. Titan

Remarks: \_\_\_\_\_

(if additional description is necessary, use BACK of this form.)

INVOICED

DATE 3-31-86

INV. NO. 13315

Signed Marion Schmidt (TECHNICIAN)

NOTICE OF INTENTION TO DRILL CORRECTION

(see rules on reverse side)

2-25-86

Starting Date 02 28 86 month day year

API Number 15-063-21,016-00-00

\*200' East of SE NW NW Sec. 19 Twp. 12 S, Rg. 30 X West 4290 Ft. from South Line of Section \* 4090 Ft. from East Line of Section

OPERATOR: License # 5146 Name Rains & Williamson Oil Co., Inc. Address 435 Page Court, 220 West Douglas City/State/Zip Wichita, Kansas 67202 Contact Person Juanita Green Phone (316) 265-9686

(Note: Locate well on Section Plat on reverse side) Nearest lease or unit boundary line 990 feet County Gove

CONTRACTOR: License # 5146 Name Same as Above City/State

Lease Name THIELEN Well # 1 Ground surface elevation feet MSL

Well Drilled For: Well Class: Type Equipment: X Oil SWD Infield X Mud Rotary X Gas Inj Pool Ext Air Rotary OWWO Expl X Wildcat Cable

Domestic well within 330 feet: yes no Municipal well within one mile: yes no Depth to bottom of fresh water 130 Depth to bottom of usable water 1325

If OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

Surface pipe by Alternate: 1 2 Surface pipe planned to be set 260 Conductor pipe required -0- Projected Total Depth 4550 feet Formation Mississippian

I certify that well will comply with K.S.A. 55-101, et seq., plus eventual plugging hole to KCC specifications. Date 2-24-86 Signature of Operator or Agent Wilson Rains Title PRESIDENT

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required feet per Alt. 1 2 This Authorization Expires 5-14-86 Approved By 2-14-86

Handwritten notes: mike G, 3-20-86, 8 9/8, 160 f, 4290 FSL, Houtling, 3-20-86

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 2825 feet depth with 20 sx's of ... 2nd plug @ 1425 feet depth with 10 sx's of ... 3rd plug @ 400 feet depth with 40 sx's of ... 4th plug @ 40 feet depth with 10 sx's of ... 5th plug @ 10 feet depth with 10 sx's of ... (2) Rathole with 10 sx's (b) Mousehole with sx's

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office after well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only: API #15- Surface casing of feet set with sx's at hours, 19 Alternate 1 or 2 surface pipe was used. Alternate 2 cementing was completed @ ft. depth with sx's on 19 Hole plugged, 19, agent

RECEIVED STATE CORPORATION COMMISSION 04-07-1986 APR 7 1986 Form C-1 12/85

CONSERVATION DIVISION Wichita, Kansas