

15-195-01055-00-00

Office Phone 379
Res. Phone 350

WICK'S PETROLEUM CO.

W. E. Wickizer, Mgr.

WAKEENEY, KANSAS

11-22-53

Bender #2 Location: NW NE NW 21-12-23 Trego County, Kansas

201 8 5/8" surface pipe, cemented with 125 sax

100'	to	750'	Shale
750'	-	1050'	Shale
1050'	-	1270'	Shale and sand
1270'	-	1410'	Shale, shells and red bed
1410'	-	1525'	Sand
1525'	-	1915'	Red bed
1915'	-	1965'	Anhydrite
1965'	-	2490'	Shale & shells
2490'	-	3135'	Shale & Lime
3135'	-	3255'	Lime & Shale
3255'	-	3330'	Shale
3330'	-	3390'	Shale & Lime
3390'	-	3625'	Lime & Shale
3625'	-	3765'	Lime & Shale
3765'	-	3805'	Lime
3805'	-	3830'	Lime
3830'	-	4000'	Lime

T.D.

01-28-1954

PLUGGING
 FILE SEC 21 T 12 R 23W
 BOOK PAGE 3 LINE 20


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- WICK PETROLEUM
Farm- Bender No. 2

SEC. 21 T. 12 R. 23W
NW NE NW

Total Depth. 4000'
Comm. 12-2-53 Comp. 12-18-53
Shot or Treated.
Contractor.
Issued. 5-15-54

County Trego
KANSAS



CASING:
8 5/8" 201' cem w/125 sx

Elevation. 2427'

Production. Dry

Figures Indicate Bottom of Formations.

shale	1050
shale & sand	1270
shale, shells & red bed	1410
sand	1525
red bed	1915
anhydrite	1965
shale & shells	2490
shale & lime	3255
shale	3330
shale & lime	3765
lime	4000
Total Depth	

Tops: Scout	
Lansing	3769
Sand	3810