•	
To: 6-100494	API number: <u>15-195-22,144-00</u> -00
STATE CORPORATION COMMISSION	
CONSERVATION DIVISION - PLUGGING	NW NW NW/4 SEC 05, 12 8, 25 W
200 COLORADO DERBY BUILDING WICHITA, KANSAS 67202	<pre>330 feet from N section line 330 feet from W section line</pre>
WICHIIA, RANSAS 07202	reet from w section line
Operator license# 31016	Lease: TOTO Well # 8-4-5
Operator: <u>Diversified Operating Corpo</u>	r County: TREGO  Well total depth: 4660 feet Conductor pipe: inch @ feet Surface pipe: 8 5/8 inch @ 248 feet
Address: 1675 Larimer Street	_ Well total depth:4660 feet 15'
Suite 850	_ Conductor pipe: inch 0 feet Surface pipe: 8 5/8 inch 0 feet
Denver, CO 80202-1523	
Abandoned Oil well: Gas Well:	Input Well: SWD Well: D & A:_X
Plugging contractor: EMPHASIS OIL OPE	RATIONS License: 0824:
Address: RUSSELL, KANSAS	
Company to plug at: Hour: ??	Day: Month: Year:
Plugging proposal received from: TOM Company: EMPHASIS OIL OPERATIONS	
Were: Spot all plugs through drill w	ith heavy mud between all plugs.
1st plug @ 4575 feet with 25 sacks	Rat hole: 15 sacks
2nd plug @ 2100 feet with 25 sacks	Mouse hole: 10 sacks
3rd plug @ 1150 feet with 100 sacks	Wiper plug @ 40 feet
4th plug @ 290 feet with 40 sacks	
5th plug @ 40 feet with 10 sacks	
Plugging proposal received by: DAVID	WANN
Plugging operations attended by agent	
Completed: hour: 1:30 PM, Day: 17	
Actual plugging report: Hole reported	i plugged as above
Order 225 sx 60/40 posmix w/ 6% gel	and 2 sx celloflake or flowcel.
	CONTROL OF THE PROPERTY OF THE
	Con Crado Como
	1999945 CN
	Har bear
Remarks: Elevation: <u>2528</u> G Anhydr Dakota plugged: <u>T</u>	rite depth: <u>2092</u> feet, Anhy. plug: <u>T</u> Bottom hole plug in place (A/E/N): <u>A</u>
	· · · · · · · · · · · · · · · · · ·

Remarks: Elevation...

Dakota plugged: <u>T</u>

Plugged through drill pipe: <u>T</u>

Arbuckle: <u>4589</u> Cemented by: <u>ALLIED CMT</u>

INdid [ ] [ ] [ ] did not [ <u>X</u> ] observe the plugging.

(TECHNICIAN)

.

10

DATE \_\_\_\_\_\_