

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

Form ACO-1 October 2008 Form Must Be Typed

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License # 32309	API No. 15 - 081-21799-00000
Name: Presco Western, LLC	Spot Description:
Address 1: 5665 Flatiron Parkway	SW_NW_SE_NE_Sec. 24 Twp. 30 S. R. 34 East West
Address 2:	
City: Boulder State: CO zip: 80301 +	1117 Feet from 📝 East / 🗌 West Line of Section
Contact Person: Susan Sears	Footages Calculated from Nearest Outside Section Corner:
Phone: (303) 444-8881	□ NE □ NW ☑ SE □ SW
CONTRACTOR: License #	County: Haskell
Name:	Lease Name: SWLVLU Well #: 48
Wellsite Geologist:	Field Name: Lemon Victory
Purchaser:	Producing Formation: Lansing
Designate Type of Completion:	Elevation: Ground: 2956' Kelly Bushing: 2968'
New Well Re-Entry Workover	Total Depth: 4400' Plug Back Total Depth: 4327'
Oil SWD SIOW	Amount of Surface Pipe Set and Cemented at: 1809' Feet
Gas ENHR SIGW	Multiple Stage Cementing Collar Used? Yes No
CM (Coal Bed Methane) Temp. Abd.	If yes, show depth set:Feet
Dry Other	
(Core, WSW, Expl., Cathodic, etc.)	If Alternate II completion, cement circulated from: sx cmt.
If Workover/Re-entry: Old Well Info as follows:	ieet deptir to sx critt.
Operator: Yesco Western, LLC	Drilling Fluid Management Plan OWWO - Alt I NCR
Well Name: 5 WL V 48	(Data must be collected from the Reserve Pit) 5-14-10
Original Comp. Date: 4-13-08 Original Total Depth: 4460	Chloride content: ppm Fluid volume: bbls
Deepening Re-perf Conv. to Enhr Conv. to SWD	Dewatering method used:
Plug Back: Plug Back Total Depth	Location of fluid disposal if hauled offsite:
Commingled Docket No.:	Operator Name:
Dual Completion Docket No.:	Lease Name: License No.:
Other (SWD or Enhr.?) Docket No.:	
8/26/2008	Quarter Sec. Twp. S. R. East West
Spud Date or Date Reached TD Completion Date or Recompletion Date	County: Docket No.:
Kansas 67202, within 120 days of the spud date, recompletion, workover or confiside two of this form will be held confidential for a period of 12 months if required tiality in excess of 12 months). One copy of all wireline logs and geologist we BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 for	
All requirements of the statutes, rules and regulations promulgated to regulate tare complete and correct to the best of my knowledge. Signature:	the oil and gas industry have been fully complied with and the statements herein
	KCC Office Use ONLY
Title: KS/CO Engineering Manager Date: 1/28/2010	Letter of Confidentiality Received
Subscribed and sworn to before me this day of	If Denied, Yes Date:
20/0	/ Wireline Log Received RECEIVED
Sudia Malbuin	Geologist Report Received CORPORATION COMMISSIO
Notary Public: autustu Gucco uni	UIC Distribution FEB U 1 2010
Date Commission Expires: 0/29/20/3	

CONSERVATION DIVISION WICHITA, KS

Side Two

Operator Name: Pres	sco Western, LLC		Lease Na	me: SWLVLU		Well #: 48			
Sec. <u>24</u> Twp. <u>30</u>		☐ East 🗸 West	County: _	County: Haskell					
ime tool open and clo	sed, flowing and shu es if gas to surface te	d base of formations p t-in pressures, whether st, along with final cha eport.	r shut-in pressur	re reached station	level, hydrostatic	pressures, bottom	hole tem	perature, fluid	
Drill Stem Tests Taken Yes No (Attach Additional Sheets) Samples Sent to Geological Survey Yes No			Log For	mation (Top), Dep	epth and Datum Sample		Sample		
		☐ Yes ☐ No		Name		Тор		Datum	
Cores Taken Electric Log Run (Submit Copy)		Yes No							
ist All E. Logs Run:									
			G RECORD [New Use					
Purpose of String	Size Hole Drilled	Report all strings se Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Settin	д Туре о		Type and Percent Additives		
Surface	12 1/4"	8 5/8"	23.0	1809'	65/35/Cla		6%gel,1/4floseal,3%CC		
Production 7 7/8"		4 1/2"	11.6	4400'	Varicem	170	Gilsonite/poly flake		
					Expandad	cem 225	5%sa	t, 5%CalSeal	
		ADDITION	AL CEMENTING	/ SQUEEZE REC	ORD		•		
Purpose: —— Perforate —— Protect Casing	Depth Top Bottom	Type of Cement	#Sacks Use	ed	Type and Percent Additives				
Plug Back TD Plug Off Zone									
Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated				Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used) Depth				
4	4123'-4130' (Lan	sing B1), 4144'-41	51' (Lansing	B2) 1500 g	als 15% NEF	E			
						F	RECE	VED	
								ION COMMISS	
						F	B 0 .	2010	
						CONS	SERVATION WICHIT	N DIVISION	
UBING RECORD: 2 3/	Size: '8"	Set At: 4044'	Packer At: 4044'	Liner Run:] No	Wichin	,,,,,,	
ate of First, Resumed P 11/30/2008 (Began	roduction, SWD or Enhr Injection)	. Producing Me	_	lowing	umping G	as Lift Othe	er <i>(Explain</i>)	
Stimated Production Per 24 Hours	Oil B	bls. Gas	Mcf	Water	Bbls.	Gas-Oil Ratio		Gravity	
DISPOSITIO	N OF GAS:		METHOD OF CO	MPLETION:		PRODUCTIO	ON INTER	VAL:	
Vented Sold Used on Lease Open Hole V F			▼ Perf. □ □	Dually Comp. Commingled 412			123'-4130', 4144'-4151'		