Correction #1

## KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

ORIGINAL Form ACO-1
September 1999
Form Must Be Typed

## **WELL COMPLETION FORM**

## **WELL HISTORY - DESCRIPTION OF WELL & LEASE**

Operator: License # 32461	API No. 15 - 003-24512-00-00
ranwater, inc.	County: Anderson
Name:6421 Avondale, Ste. 212	
City/State/Zip: Oklahoma City, OK 73116	SE - NW St - NW Sec. 22 Twp. 20 S. R. 20 East West
Purchaser: CMT	feet from S / N (circle one) Line of Section
Purchaser: Christian I Martin	4797 feet from (E) W (circle one) Line of Section
Operator Contact Person: Christian L. Martin	Footages Calculated from Nearest Outside Section Corner:
Phone: (405) 810-0900	(circle one) NE SE NW SW
Contractor: Name: Evans Energy Development License: 8509	Lease Name: Garnett Shoestring Field Name: Garnett Shoestring
Wellsite Geologist:	Producing Formation: Bartlesville
Designate Type of Completion:	967  Elevation: Ground: Melly Bushing: n/a
New Well Re-Entry Workover	790' n/a
Oil SWD SIOW Temp. Abd.	Amount of Surface Pipe Set and Cemented at 25.3 Feet
Gas ENHR SIGW	
	Multiple Stage Cementing Collar Used?
Dry Other (Core, WSW, Expl., Cathodic, etc)	If yes, show depth setFeet
If Workover/Re-entry: Old Well Info as follows:	If Alternate II completion, cement circulated from 0
Operator:	feet depth to 25.3 w/ 7 sx cmt.
Well Name:Original Total Depth:	Drilling Fluid Management Plan AH II NCR 5-19-10
Deepening Re-perf Conv. to Enhr./SWD	(Data must be collected from the Reserve Pit)
Plug Back Plug Back Total Depth	Chloride content ppm Fluid volume bbls
-	Dewatering method used
Commingled Docket No.	Location of fluid disposal if hauled offsite:
Dual Completion Docket No	Operator Name:
Other (SWD or Enhr.?) Docket No	
5/2/08 5/5/08 6/20/08	Lease Name: License No.:
Spud Date or Date Reached TD Completion Date or Recompletion Date	Quarter Sec Twp S. R East West County: Docket No.:
Information of side two of this form will be held confidential for a period of 1 107 for confidentiality in excess of 12 months). One copy of all wireline logs TICKETS MUST BE ATTACHED. Submit CP-4 form with all plugged wells.	er or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply.  2 months if requested in writing and submitted with the form (see rule 82-3- and geologist well report shall be attached with this form. ALL CEMENTING
ignature: Stace & mail	KCC Office Use ONLY
itle: Ugart Date: 8-15-08	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	Letter of Confidentiality Received
ubscribed and sworn to before me this 15 day of Wyst	If Denied, Yes Date:
001 19 MM	Wireline Log Received  RECEIVED
otary Public: (#0500 Exp. 8	Geologist Report Received  UIC Distribution  MAR 0 1 2010
ate Commission Expires: 08/09/2007 () No of the Commission Expires	KCC WICHITA

Operator Name: Ial	iwater, inc.		Lease Nai	me:———	// / / / / / / / / / / / / / / / / / /	Well #:		
Sec. 22 Twp. 2	80 S. R. 20	East West	County: A	nderson				
tested, time tool ope temperature, fluid re	n and closed, flowin covery, and flow rate	and base of formations pe g and shut-in pressures, v s if gas to surface test, a final geological well site r	whether shut-i long with final	n pressure rea	ched static level, hydro	ostatic pressur	es, bottom hole	
Drill Stem Tests Taken			Log Formation (Top), Depth		and Datum	Sample		
Samples Sent to Ge	ological Survey	Yes No		Name		Тор	Datum	
Cores Taken Electric Log Run (Submit Copy)		☐ Yes ☑ No ☑ Yes ☐ No		Bartlesville Oriller's Log	Attached			
List All E. Logs Run:								
Gamma Ray I	Neutron							
		CASING Report all strings set-c	-	New Us				
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Settin Dept		# Sacks Used	Type and Percent Additives	
Surface	9 7/8"	7"		25.3'	Portland	7-		
Completion	5 5/8"	2 7/8"		778.9'	Portland	121	50/50 POZ	
·			·				-	
		ADDITIONAL	CEMENTING /	/ SQUEEZE RE	CORD			
Purpose:  Perforate Protect Casing Plug Back TD Plug Off Zone	Depth Top Bottom	Type of Cement	#Sacks Use	ed	Type and	Percent Additive	s	
Shots Per Foot		ON RECORD - Bridge Plug Footage of Each Interval Per	Ac	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used) Depth				
2	652' - 657' (11 perfs)			Acid s	Acid spot 15% HCL 100 gal.			
2	689' - 699' (21 perfs)			75 sx s	75 sx sand - 202 bbls H2O			
2	726' - 732"(13	perfs)						
TUBING RECORD 2	Size 7/8"	Set At 778.9'	Packer At	Liner Ru	n Yes V N	0		
Date of First, Resumer 6/20/08	rd Production, SWD or I	Enhr. Producing Met		Flowing 🗹	Pumping Gas L	.ift 🗌 Ot	ner (Explain)	
Estimated Production Per 24 Hours	10	Bbls. Gas	Mcf n	Water ONE		Gas-Oil Ratio	Gravity	
Disposition of Gas	METHOD OF (	COMPLETION		Production	on Interval			
Vented Sold	Used on Lease ubmit ACO-18.)	Open Hole Other (Speci	Perf.	Dually Com	p. Commingled			