KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

CONFIDENTIAL

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

Operator: License # 33365	API No. 15 - 125-30973-00-01
Name: Layne Energy Operating, LLC	County: Montgomery
Address: 1900 Shawnee Mission Parkway	SW_SE_Sec. 35 Twp. 32 S. R. 16
City/State/Zip: Mission Woods, KS 66205	787 feet from S/ N (circle one) Line of Section
Purchaser:	1975 feet from (E) W (circle one) Line of Section
Operator Contact Person: Timothy H. Wright	Footages Calculated from Nearest Outside Section Corner:
Phone: (_913) _748-3960	(circle one) NE SE NW SW
Contractor: Name: McPherson Drilling	Lease Name: Keck Well #: 15-35
License: 5675	Field Name: Brewster
Wellsite Geologist:	Producing Formation: Cherokee Coals
Designate Type of Completion:	Elevation: Ground: 789' Kelly Bushing:
New Well Re-Entry Workover	Total Depth: 1106' Plug Back Total Depth: 1097'
Oil SWD SIOW Temp. Abd.	Amount of Surface Pipe Set and Cemented at 21 Feet
✓ Gas ENHR SIGW	Multiple Stage Cementing Collar Used?
Dry Other (Core, WSW, Expl., Cathodic, etc.)	If yes, show depth setFeet
If Workover/Re-entry: Old Well Info as follows FIDENTIAL	If Alternate II completion, cement circulated from 1097
Operator:	feet depth to Surface w/ 115 sx cmt.
Well Marrie:	10016
Original Comp. Date: 5/15/2006 Original Total Septim 1106'	Drilling Fluid Management Plan (Data must be collected from the Reserve Pit) WWW US Control
Deepening Re-perf Conv. to Enhr./SWD	Chloride content_N/A ppm Fluid volume bbls
Plug Back Plug Back Total Depth	Dewatering method used N/A - Air Drilled
Commingled Docket No.	· ·
Dual Completion Docket No	Location of fluid disposal if hauled offsite:
Other (SWD or Enhr.?) Docket No	Operator Name:
1/18/2008 1/21/2008	Lease Name: License No.:
Spud Date or Date Reached TD Completion Date or	Quarter SecTwpS. R East West
Recompletion Date Recompletion Date	County: Docket No.:
	1
Kansas 67202, within 120 days of the spud date, recompletion, workove Information of side two of this form will be held confidential for a period of 1	the Kansas Corporation Commission, 130 S. Market - Room 2078, Wichita, er or conversion of a well. Rule 82-3-130, 82-3-106 and 82-3-107 apply. 2 months if requested in writing and submitted with the form (see rule 82-3-and geologist well report shall be attached with this form. ALL CEMENTING . Submit CP-111 form with all temporarily abandoned wells.
All requirements of the statutes, rules and regulations promulgated to regulation are complete and correct to the best of my knowledge.	te the oil and gas industry have been fully complied with and the statements
Signature.	KCC Office Use ONLY
Title: Agent Date: 5-2-08	Letter of Confidentiality Attached
Subscribed and sworn to before me this	If Denied, Yes Date: RECEIVED KANSAS CORPORATION COMMISSION Wireline Log Received
Martural C. A. A.	Geologist Report Received MAV 0.C 2009
Notary Fublic.	Notary Public - State of Kansas Distribution YAPPT. Expires 1-4-2009 Notary Public - State of Kansas Conservation Division WICHITA, KS

Operator Name: La	yne Energy Opera	Operating, LLC Lease Name			se Name:	Keck	- Well #: <u>15-35</u>				
Sec35	³² S. R. 16	. V Eas	st West		inty: Mont			·			
tested, time tool ope temperature, fluid re	Show important tops a en and closed, flowing covery, and flow rate gs surveyed. Attach	g and shu s if gas to	t-in pressures, surface test, a	whether long wit	shut-in pr	essure reached	I static level, hydro	static pressur	es, botto	m hole	
Drill Stem Tests Taken Yo (Attach Additional Sheets)			∕es ✓ No		[ZI	.og Format	tion (Top), Depth a	nd Datum		Sample	
,		∕es ☑ No		Nam	ne		Тор	ı	Datum		
			res ☑No		Paw	nee Lime		431 GL	3	358	
Electric Log Run		V	=		Exc	ello Shale		585 GL	2	204	
(Submit Copy)					V SI	nale		634 GL	1	155	
List All E. Logs Run:						eral Coal		678 GL		111	
Compensated D	ensity Neutron							1003 GL		214	
Dual Induction					MIS	sissippian		1003 GL	-	Z 14	
		Pana	CASING ort all strings set-c		-		etion oto				
Purpose of String	Size Hole	Si	ze Casing	٧	Veight	Setting	Type of	# Sacjs		and Percent	
Surface	Drilled	8.625"	et (In O.D.)	24	s. / Ft.	Depth 21'	Class A	Used 4	Additives		
			<u></u>				 	 	Type	1 cement	
Casing	6.75"	4.5"		10.5		1097'	Thick Set	115			
Purpose:	Depth					QUEEZE RECORD					
Perforate	Top Bottom	Туре	Type of Cement		ks Used	Type and Percent Additives					
Protect Casing Plug Back TD			CONCIDE		<u> </u>	,					
Plug Off Zone			UNITUL	1 7 0 0							
_	PERFORATION	ON RECOR	RD - Bridge Plug	c Sat/Tu	ne	Acid Fra	ncture Shot Coment	Saucozo Bosor	4		
Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated				Je	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used) Depth					
	See Attached Pa			100							
		C(ONFIDENTI								
MAY 0 5 2008											
KCC											
				•							
TUBING RECORD	Size	Set At		Packe	r At	Liner Run					
	3/8" d Production, SWD or E	841'	Producing Moth				Yes 🗸 No				
1/31/2008	a Production, SWD or E	nor.	Producing Meth	00	Flowing	g 🗸 Pumpi	ing Gas Lift	Othe	r (Explain)		
Estimated Production Per 24 Hours		Bbls.		Mcf	Wate	er E	Bbls. Ga	as-Oil Ratio		Gravity	
	0 METHOD OF C	OMPLET:	60		0	Dod		Þ	ECEIVE	- D	
Disposition of Gas	METHOD OF C	OWPLETIC		<u> </u>		Production Inter				COMMISSION	
Vented ✓ Sold (If vented, Su	Used on Lease		Open Hole Other (Specif	√ P∈ (v)	ert. [C	ually Comp.	Commingled ————————————————————————————————	MAY	1062	008	

Operator Name:	Layne Energy Operating, LLC.							
Lease Name:	Keck 15-35							
	Sec. 35 Twp. 32S Rng. 16E, Montgomery County							
API:	15-125-30973-00-01							
Shots per Foot	Perforation Record	Acid, Fracture, Shot, Cement Squeeze Record	Depth					
Initial Perforations (5/2006)								
4 Riverton 991		3200 lbs 20/40 sand	991' - 994'					
	Riverton 991' - 994'	275 bbls water						
		250 gals 15% HCl acid						
	Recompletion Pe	erforations (1/2008)						
4	Weir 790.5' - 794.5'	4209 lbs 20/40 sand						
		442 bbls water	790.5' - 794.5					
		500 gals 15% HCl acid						
4	Mineral 678' - 679.5' Croweburg/V-Shale 635.5' - 637.5'	4578 lbs 20/40 sand						
		620 bbls water	635.5' - 679.5'					
		500 gals 15% HCl acid						
4 1	Mulky 587' - 590' Summit 556' - 558'	6676 lbs 20/40 sand						
		599 bbls water	556' - 590'					
		600 gals 15% HCl acid						

CONFIDENTIAL



RECEIVED KANSAS CORPORATION COMMISSION

MAY 0 6 2008