6-100452

TO:	API number: 15-193-20,590-000
STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING	<u>SE NE NW</u> /4 SEC. 01 , 10 S, 32 W
200 COLORADO DERBY BUILDING	990 feet from N section line
WICHITA, KANSAS 67202	2310 feet from W section line
Operator license# <u>6484</u>	Lease <u>Robbin</u> well # <u>1</u>
Operator: Anderson Energy, Inc.	County Thomas
Address: 200 East First Street	Well total depth 4730 feet
Suite 414	Conductor Pipe: inch @ feet Surface pipe 8 5/8 Inch @ feet
wichita, Kansas 67202	Surface pipe 8 5/8 Inch @ 333 feet
Aband. oil well, Gas well, Inp	out well, SWD, D & A _X_
Plugging contractor: White & Ellis Dri	.11ing License#_5420
Address:	
Company to plug at: Hour: ?? Day:	Month: Year:
Plugging proposal received from: <u>Judy (secretary)</u>	
Company: White & Ellis Drilling, Inc.	phone:
Were: Spot plugs through drill pipe w/	heavy mud between all plugs.
1st plug @ 2650 feet with 25 sacks	Rat hole: 15 sacks
2nd plug @ 1780 feet " 100 "	Mousehole:sackscelveD
3rd plug @ 380 feet " 40 "	STATE CORPORATION COMMISSION
	3-5-92 MAR - 5 1992
4th plug @ 40 feet " wiper plug	a 10 Sx.
5th plug @ feet	CONSERVATION DIVISION Wichita, Kansas
Plugging Proposal Received by: <u>David</u>	K. Wann
Plugging operations attended by agent?	All[], Part[], None[X]
Completed: Hour: 8:30 pm, Day: 28, Mo	onth: February , Year: 1992
Actual plugging report: Hole reporte	d plugged as above.
Order 190 sx 60/40 pozmix w/ 6% gel an	d 2 sx celloflake or flowcel.
Remarks: Elevation: 3082 GL, Anhydr	ite depth: 2646 - 2676 feet
Anhy. plug: YES Dakota plug: YES	Bottom hole plug in place: YES
Plugged through drill pipe: YES Did NOT penetrate Arbuckle, cemented by	v Allied ^
I did not [X] observe the p	lugging. David K. Wann P.I.R.T. II
DATE 3-11-7-1	(agent)
3410 x	HD (agenc) Form CP-2/3