1	000000 : 4-26	API NUMBER	15-033-20,	884-0000	
STATE: CORPORATION COMMISSION CONSERVATION DIVISION PLUGGING SECTION					s = 20 = 4
		SE SW NW, SE			
TAR COLORA	DO DERBY BUILDING Ansas 67202		150 t • •	t from N Š	Section 11n
	S PLUGGING REPORT				Saction 11A
	31232	Lease Name_	Bluff Cree	k well	16-1
Operator:	Cody Energy Inc.	County Co	omanche		
	7555 E. Hampden Ave. Ste. 600	Well Total	Depth	675	0 219.217,
	Denver, CO 80231	Conductor P	lpe: Size		feet
		Surface Cas	ing: Size	8 5/8	725
15 and 22 4	Oli Well Gas Well	Input Well	Swo	Y-11	D&A X
	l as hereinafter indicated				
Other Wel	Contractor H-40 Drilling, Inc.		Lici	ense Numbe	30692
Plugging	251 N. Ubton Sto 10' Wichita KS	67202			
. Address	251 N. Water, Ste. 10, Wichita, KS	0.F Mas +	h • /	Ye	ar:19 94
	o plug at: Hour: 5:30 p.m. Day:		•• •		
Plugglng	proposal received from Jim Joh	IIISOII			216-263-20/3
(company	name) H-40 Drilling, Inc.			(phone)	310-203-2043
40F8:	to fill hole with heavy mud and spot	cement through d	rill pipe	·	,
lst plug a	at Arbuckle with 40 sx cement, 2nd r	olug at 750' with	1 50 sx cem	ent,	
3rd plug	at 400' with 30 sx cement, 4th plug	at 40' with 10 s	ex cement,		
	to circulate rathole with 15 sx cemer				
	to circulate mousehole with 10 sx cem				
oth prog		posal Recalved	by	Steve Middl	Leton
				(TECHN	1GTAN)
Plugging	Operations attended by Agent1:	A1 1	Part	Но	u e X
	ns Completed: Hour: 1:45 a.m. Day:				
ACTUAL P	LUGGING REPORT 1st plug at 6363' w	ith 40 sx cement,	,		
	at 530' with 50 sx cement,		·	·	
	at 267' with 30 sx cement,			. R	Ene.
	at 40' with 10 sx cement,		· · · · · · · · · · · · · · · · · · ·	STATE CORPO	ECEIVED DRATION COMMISSION
	to circulate rathole with 15 sx ceme	nt.		MAY	U 2 1994
				CONSERVAT	·
	to circulate mousehole with 10 sx ce			Wichita,	Kansas A
	: Used 60/40 Pozmix 6% gel by Allied	is necessary,	use BACK		r=.)
	I (End) observe this plugging.				•
20 M	7 M & 100%	\$ I gn •		TECHNICIAN	
may may 40	1382 4-24		,		FORM C
مريما والماما	4-24				Ray.