

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-167-30063-00-00
Spot: NENENE Sec/Twnshp/Rge: 28-11S-15W
4950 feet from S Section Line, 330 feet from E Section Line
Lease/Unit Name: STRECKER Well Number: 1
County: RUSSELL Total Vertical Depth: 3339 feet

Operator License No.: 7628
Op Name: LORENZEN OIL COMPANY, INC.
Address: 705 - 1/2 AVENUE G.
FORT MADISON, IA 52627

Production Casing Size: 5.5 feet: 3332 w/150 sxs cmt
Surface Casing Size: 8.625 feet: 230 w/165 sxs cmt

#10852

Well Type: OIL UIC Docket No: _____ Date/Time to Plug: 05/22/2003 10:00 AM
Plug Co. License No.: 99996 Plug Co. Name: ALLIED CEMENT COMPANY
Proposal Rcvd. from: ALLEN BANGART Company: LORENZEN OIL COMPANY, INC. Phone: (319) 372-6665

Proposed
Plugging
Method:

Plugging Proposal Received By: HERB DEINES WitnessType: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 05/22/2003 12:00 PM KCC Agent: CASE MORRIS

Actual Plugging Report:

Pulled 875' of rods. Last rod ate off.
Tubing stuck in the hole. Stretch indicated approximately 1800'.
Pumped dye down tubing that morning to determine approximate depth (800') of holes. Took 18 bbls to circulate dye back up.
Tied onto tubing and circulated with 120 sxs 60/40 pozmix - 10% gel cement.
Pumped 80 sxs more cement with 200# hulls. On vacuum.
Pumped 10 sxs cement down backside.
Max. P.S.I. 300#. S.I.P. 200#.
Tied back onto tubing and pumped 30 sxs cement.
Max. P.S.I. 500#. S.I.P. 200#.

RECEIVED
JUN 04 2003
KCC WICHITA

Remarks: ALLIED CEMENTING COMPANY.

Plugged through: CSG

District: 04


Signed Case Morris
(TECHNICIAN)

BD

INVOICED
6.5.03
2003061620

MAY 30 2003

8-11 Map No. _____
 OPER. NADEL & GUSSMAN
Tulsa, Oklahoma
 WELL #1 STRECKER
 CONTR. Murfin Drilling
 WC 1 mi S_E of Fairport Field
 I.P. P 40 BOPD/NW (Gr 29 deg) Arb 3332-39 (OH)



S-T-R 28-11S-15W
 SPOT NE NE NE
 CO RUSSELL, Ks.
 ELEV 1865 KB

DST #1 (Lan) 2961-3020, Op 60, R 730' SW, ISIP 463/30",
 FP 62-365, FSIP 392/30"
 DST #2 (Lan) 3045-70, Op 60, R 20' M, ISIP 227/30"
 FP 31-47, FSIP 98/30
 DST #3 (Arb) 3317-3330', Op 45 min, R 20' SOM, ISIP
 903/30", FP 11-19', FSIP 895/30"
 DST #4 (Arb) 3330-39, Op 60", 120' GIP, R 1370' C.O.
 (Gr 35.0), ISIP 746/30", FP 215-510, FSIP 675/30" &
 incr. - RTD 3339', 5" 3332/150 sx
 CO 3339 T.D., § 5' BOPH Nat, NW/4 hrs, P 61 BO/NW/
 16 hrs (Gr 35°) State Pot: P 40 BOPD/NW (Gr 29.0°) Arb 3332-39 (OH)

Log (KB)
 Top 2703 - 838
 Hb 2955 - 1090
 Tor 2974 - 1109
 Lan 3005 - 1140
 BKC 3238 - 1373
 Arb 3321 - 1456
 LTD 3338 - 1473
 Sp1 (KB)
 Top 2703
 Hb 2954
 Tor 2975
 Lan 3005
 BKC 3238
 Arb 3323
 RTD 3339

COMPLETED