4-060920

15-167-05161 -00-00. TO: API Number: 15- - 1-1-64 STATE CORPORATION COMMISSION CONSERVATION DIVISION - PLUGGING **SE NW SE** /4 SEC. **35** , **11** S, **15** W 130 SOUTH MARKET, SUITE 2078 1650 feet from S section line WICHITA, KANSAS 67202 _____ feet from E section line 1650 Lease <u>Eulert</u> Well # 9 Operator license#_4058 County: Russell Operator: American Warrior, Inc. Well total depth 3313 107.67 Address: **P.O. Box 399** Garden City, Kansas 67846 Conductor Pipe: 0 inch @ 0 feet Surface pipe 8 5/8 Inch @ 917 feet Aband. oil well_x, Gas well___, Input well__, SWD__, D & A__ Plugging contractor: Co Tools _____License#____-Address:___ Company to plug at: Hour: 10:00 A.M. Day: 28 Month: June Year: 1996 Plugging proposal received from: Vernon Pfughoef Company: American Warrior, Inc. Phone: 316-275-2963 Were: Order 375 sxs 60/40 posmix - 10% gel and hulls. Plugging Proposal Received by: Herb Deines Completed: Hour: 11:50 A.M. , Day: 28 , Month: June _____, Year: **1996** Actual plugging report: 8 5/8" to 917'. 5 1/2" to 3304' with 100 sxs. BP at 3260'. Perfs at 2920' - 3227'. Tied onto production casing and pumped 35 sxs cement with 500# hulls, 12 sxs gel and 225 sxs cement. Tied onto annulus and pumped 100 sxs cement. Max. P.S.I. 500#. Remarks: Allied Cementing. Condition of casing(in hole): GOOD_X BAD_ Anhy.plug: YES X Bottom plug(in place): YES___, CALC_X_, NO___ Dakota plug: YES_X__, NO__ Plugged through TUBING_____, CASING X . Elevation: 1854 d not[x] observe the plugging.

Form CP-2/3