

11-16

6 070726

API NUMBER 15-051-22674-0000

STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION SW NE SE, SEC. 27, T 11 S, R 16 W/EK
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

TECHNICIAN'S PLUGGING REPORT

Operator License # 6790
Operator: CB/JB Oil Operations
Name & Address: Box 531, Russell, Ks. 67665
William R. Clair

feet from S section line
feet from E section line
Lease Name Bowlby Well # C #1
County Ellis 110.44
Well Total Depth 3398 feet
Conductor Pipe: Size 0 feet
Surface Casing: Size 8 5/8 feet 205

Abandoned Oil Well Gas Well Input Well SWD Well

Other well as hereinafter indicated

Plugging Contractor Allied Cemnting Co. License Number
Address Box 31 Russell, Ks. 67665

RECEIVED
STATE CORPORATION COMMISSION
DEC 20 1988
CONSERVATION DIVISION
Wichita, Kansas

Company to plug at: Hour: 10:00AM Day: 16 Month: Nov Year:

Plugging proposal received from Bill Clair

(company name) CB/JB Oil Operations (phone)

were: 8 5/8" 205' S.P. cwc w/150 sks cement. 4 1/2" casing set at 3398' w/200 sks cement.

Perfs at 3328' - 3038' casing poor. (No squeeze, no D.V. tool) Elv. 1781' - Anhy 945'

Proposal 325 sks 65/35 Poz 6% Gel 3% Cal Cl and 5 sk Hulls. Perferate 4 1/2" casing at 500' and 955'. Spot cement with tubing load both 4 1/2" casing and 4 1/2" and 8 5/8" annulus with cement. Shut in under pressure. Ostrum Well Service.

Plugging Proposal Received by Marion J. Schmidt (TECHNICIAN)

Plugging Operations attended by Agent?: All Part None

Operations Completed: Hour: 5:30PM Day: 16 Month: Nov Year: 19 88

ACTUAL PLUGGING REPORT Ordered 325 sks 65/35 Poz 6% Gel 3% Cal Cl and

5 sks Hulls. Pumped in with pump truck through tubing. Bad casing at 412' - 615' -755' Perferated 4 1/2" casing at 954' in anhydrite. 1. Ran 2 3/8" tubing to 1440' spotted 200 sks cement w/2 sks Hulls mixed in. 2. 2 3/8" tubing at 210' cwc w/10 sks cement circulated 1 Hulls mixed in. 3. Squeezed 4 1/2" casing w/15 sks cement. Max pressure 200 psig. Shut in at 100 psig. Pumped 100 sks in annulus. Max pressure 500 psig.

Remarks: Shut in at 300 psig. Cemented by Allied Cementing. Russell, Ks. (If additional description is necessary, use BACK of this form.)

INVOICED
Observe this plugging.

DATE 1-5-89

INV. NO. 23476

Signed Marion J. Schmidt (TECHNICIAN)

JAN 06 1989

FEB 10 1989

FORM CP-2/3 Rev. 01-84