

To:  
STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, Kansas 67202

API NUMBER 15-205- 19832-00-00  
SE NW NE Sec/Twp/Rge Sec 16 T29S R17E  
4504 (GPS) feet from south section line  
1865 (GPS) feet from east section line

## TECHNICIAN'S PLUGGING REPORT

Operator License # 101  
Operator: State Of Kansas Fee Fund  
Name & Stich North Project  
Address \_\_\_\_\_  
AB oil well XXXXXX Gas Well \_\_\_\_\_

Lease/Well# Stich North-Wiles gps# MCD 08  
County Wilson  
Well Total Depth 850 (est) feet  
Production Pipe: NA Size Feet NA  
Surface Casing: 10 Size Feet NA  
SWD Well/ Input Well \_\_\_\_\_ D & A \_\_\_\_\_

Other well as hereinafter indicated: \_\_\_\_\_

Plugging Contractor: K-W Oil Well Service, Inc Lic. # 3097Address: 19450 Ford Road, Chanute, Kansas 66720Company to plug at: \_\_\_\_\_ Hour: \_\_\_\_\_ Day: 9 Month: 6 2009Plugging proposal received from: Sam KepleyCompany Name: K-W Oil Well Service, Inc Phone: 620-433-7730Were: Wash well to TD and fill from btm to top with portland cement.Plugging Proposal Received by: Alan M. Dunning

TECHNICIAN

Plugging attended by Agent: All \_\_\_\_\_ Part XXXXXX None \_\_\_\_\_Operations Completed: Hour: \_\_\_\_\_ Day: 9 Month: 6 2009

Actual Plugging Report: 3' of 12" surface pipe was set to bring well to surface. A 1" cement string was washed to 375' inside the surface pipe. The well was pumped full of cement from btm to top thru this cement string. A total of 78 sacks of portland cement were used to plug well. The well was cut off below plow depth and the location restored.

RECEIVED

AUG 21 2009

Remarks: Control # 20090028-023

(If additional description is necessary, use BACK of this form.)

KCC WICHITA

I partially observed this plugging

Signed:

Alan M. Dunning  
TECHNICIAN