15-051-03574-0000

## DISTRICT CONSERVATION AGENT'S REPORT

Or.

State Corporation Commission Conservation Division 211 North Breadway Wichita, Kansas

Т		
FILE	NO.	Parket and the second s

LOCATION NE NW NE

•	SEC. 31 TWP.11 RGE. 20
Dry Hole X Abandoned Oil Well	Abandoned Gas Well
I have this date completed supervision	of plugging of:
	KRX Caskey ANB KCC
<del></del>	Address Hutchinson, Kans
Field	County Ellis
Total Depth 3968 Feet.	
Plugging Contractor Wentworth I	org & Halliburton Cementing Co
Flugging Contractor's License No	
Address (Describe briefly the	manner in which the well was plugged)
8 5/8" at 278' circulated Wi	th cement.
Circulated hole with heavy m	nud, displaced 25 sax cement through
drill pipe at 3968' - set ce	menting plug at 270' - displaced 25
sax cement through drill pip	oe at 270' - mud to 60', set comenting
plug and filled from 60' to	O' with cement.
Cementing By Halliburton Co.	
	Esson Tette
	District Conservation Agent

TECEIVED
SHALL CORPORATION COMMISSION

JUN 6 - 1955 CANATION DIVISION Michita, Kansas PLUGGING

Date

COOK PAGE 123 UNE 38