

WELL PLUGGING RECORD

OR

FORMATION PLUGGING RECORD

Strike out upper line when reporting plugging off formations.

STATE OF KANSAS STATE CORPORATION COMMISSION

Give All Information Completely Make Required Affidavit Mail or Deliver Report to: Conservation Division State Corporation Commission 800 Bittling Building Wichita, Kansas

County. Sec. Twp. Rge. (E) (W)

Location as NE 1/4 NW 1/4 SW 1/4 or footage from lines

Lease Owner Falcon Seaboard Drg. Co. & Central Prod. Co.

Lease Name Eaton Well No. 71

Office Address 107 Philhower Bldg., Tulsa, Okla.

Character of Well (Completed as Oil, Gas or Dry Hole) Dry Hole

Date, well completed July 5th, 1931

Application for plugging filed Same 193

Application for plugging approved Same 193

Plugging Commenced Same 193

Plugging Completed July 5th, at 8:00 AM 193

Reason for abandonment of well or producing formation Dry Hole

If a producing well is abandoned, date of last production 193

Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes, by Mr. C.T. Alexander, Great Bend, Kans.

Name of Conservation Agent who supervised plugging of this well Mr. C.T. Alexander, Great Bend, Kans.

Producing formation Depth to top Bottom Total Depth of Well Feet 3145

Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Table with 7 columns: Formation, Content, From, To, Size, Put In, Pulled Out. Includes handwritten note: 'The above pipe was run in 11 in. hole and cemented with 90 sacks Reg. cement and 100 lbs. calcium chloride...' and '8 5/8 250.00 None'.

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from feet to feet for each plug set.

We had an extra good pit of mud, We dropped motion and circulated same before starting out of the hole breaking down drill pipe, On the way out we circulated at the following points, 2645, 1945, 1445, 945, 445, Put in a good solid bridge from 245 to 221, consisting of wooden bridge plug on bottom, 10 crushed rocks, some old paper bags, and a burlap bag filled with hay and pushed same to 221 feet where it was solid with the drill pipe, then spotted 15 sacks Reg. cement and 25 lbs Calcium chloride with Ballburton through the drill pipe. Pushed top bridge plug plug to 32 feet, pushed some paper bags on same and pumped 5 sacks Reg cement on same, Will weld cap on surface pipe before covering same, left open at present for plugger's inspection.

PLUGGING FILE 3-13-146 BOOK PAGE 145 LINE 35

RECEIVED JUL 11 1941 STATE CORP. COMM. CONSERV. DIV.

07-11-1941

(If additional description is necessary, use BACK of this sheet)

Correspondence regarding this well should be addressed to

Address Cecil A. Prather, Box # 65, Great Bend, Kansas

STATE OF KANSAS, COUNTY OF KANBOS, ss.

(employee of owner) or (owner or operator) of the above-described well, being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) Cecil A. Prather

Box # 65, Great Bend, Kansas (Address)

SUBSCRIBED AND SWORN to before me this 8 day of July, 1941

My commission expires Jan 25, 1945

Notary Public.

**PLUGGING INSTRUCTIONS**

**How Well Shall Be Plugged**

Pluggers Name . . . . .

Address . . . . .

Date . . . . . 7-5-41

Location . . . . . C.F.G. SW. SW.

Sec. 3 . Twp. 13 . Rge. 14W

Name of Operator *Earl Butler* . . . . . Address *Beaver Dam, Bartlett, Wisconsin*

Lessee . . . *Caton* . . . . . Well No. *1* . . . . . County . *Russell* . . . . .

Describe briefly the manner in which well is to be plugged.

The operator shall have the option as to the method of placing cement in hole, by: (a) dump bailer, (b) pumped through tubing, (c) (pump and plug).

Total depth *3145* ft. P.B. to *756* ft.

The hole shall be filled with mud from . . . ft. to . . . ft.

and bridge and cement to . . . ft. and mud to . . . ft.

and bridge and cement to . . . ft. and mud to . . . ft.

and bridge and cement to . . . ft. and mud to . . . ft.

and a permanent bridge placed at *756* ft. and cement to *756* ft.

and mud to *756* ft. and cement to *8* ft. and mud to top of

surface.

**A ROTARY DRILLED HOLE THAT HAS ONLY THE SURFACE PIPE LEFT IN**


The hole shall be filled with not less than 14 pound mud, and circulated every 500 ft. from bottom up to the bottom of surface pipe, or fresh water. The hole shall be bridged with a wooden plug, rock and burlap. Cement shall be placed in hole through the drill pipe.

Pipe in hole. . . in. . . . ft. . . in. . . . ft. . . in. . . . ft.

. . . in. . . . ft. . . in. . . . ft. . . in. . . . ft.

. . . in. . . . ft.

3 13 14W  
145 NE 35



Operator sign . . . . .

*E. J. Alexander*



CERTIFIED WELL LOG

Central Pet. Co & Falcon Seaboard Drg. Co. EATON #1, Center East 1/4 - S W 1/4, of the S W 1/4, Sec. 3, Twp. 13, Range 14 west of the Sixth P.M. Russell County, Kansas, Drilling Commenced June 19, 1941, Drilling Completed July 5, 1941, Elevation 1626, Production D&A, Plugging Completed July 6, 1941.

Post Rock and Mud from 0	40
Shale with shells from	40 104
Sand	104 115
Shale and Lime breaks	115 210
Sand	210 220
Shale	220 249
Hard Shale	249 258
Sandy Shale	258 290
Hard Shale	290 340
Dakota Sand-Iron	340 380
Red and Blue Shale	38 410
Sand and Shale	410 668
Lime (anhydrate)	668 701
Shale	701 710
Sand, Shale	710 787
Sand	787 801
Sandy Shale	801 832
Limy Shale	832 860
Red and Blue Shale	860 1100
Salt - shale	1100 1165
Salt	1165 1324
Shales - Shells	1324 1372
Lime	1372 1392
Broken Lime	1392 1460
Lime	1460 1530
Shale - Shells	1530 1565
Lime	1565 1595
Shale	1595 1666
Shale and Lime	1666 1790
Lime	1790 1795
Broken Lime	1795 1875
Shale - Lime Shells	18 5 1910
Lime - Shale	1910 1950
Lime	1950 2025
Lime - Shale	2025 2085
Shale - Shells	2085 2180
Lime	2180 2190
Shale	2190 2210
Shale - Lime	2210 2330
Shale - Shells	2330 2477
Lime	2477 2500
Lime - Soft	2500 2515
Lime	2515 2539
Lime - Shale	2539 2579
Lime	2579 2739
Lime - Shale	2739 2789
Lime	2789 3058
Lime - Shale	3058 3107
Lime - Chert	3107 3145
Total Depth	3145

Set and Cemented 250.00ft. of ~~5/8~~ 5/8 28lb. lw. surface pipe with 90 sacks ~~xxxx~~ regular cement and 100lb. Calcium Chloride



PLUGGING  
 FILE 3 13 14W  
 BOOK PAGE 145 LINE 35

STATE OF KANSAS S S  
 COUNTY OF RUSSELL,

Cecil A. Prether, of Lawful age, Being duly sworn, upon his oath desposes and says,  
 That I was drilling Supt. on the above well and the log and ~~xxxxxx~~ information is a true and correct record of the above well.  
 FURTHER AFFIANT SAYETH NOT.

Cecil A. Prether  
 Affiant

SUBSCRIBED AND SWORN TO Before me, A Notary Public. This 8th, day of July, 1941.

My Commission Expires,

James K. Seelen  
 Notary Public

July 25, 1945

