15-051-01172-00-01
X 5-16

6 070766

To:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 19,708

C N/2 NE SW SEC. 4, T 11 S, R 17 W/E

_____ feet from S section line

_____ feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5293

Operator: Name& Address: Helmerich and Payne Inc.
Box 558
Garden City, Ks. 67846

Lease Name Roy Carmichael Well # #3 Inj.

County Ellis 127.95

Well Total Depth 3937 feet

Conductor Pipe: Size 15" feet 60"

Surface Casing: Size 10 3/4 feet 1180'

Abandoned Oil Well _____ Gas Well _____ Input Well x SWD Well _____ D&A _____

Other well as hereinafter indicated _____

RECEIVED
STATE CORPORATION COMMISSION
JUN 6 1989
6-6-1989
CONSERVATION DIVISION
Wichita, Kansas

Plugging Contractor Halliburton Cement Co. License Number _____

Address East Hwy 40, Hays, Ks. 67601

Company to plug at: Hour: AM Day: 16 Month: May Year: 19 89

Plugging proposal received from Lee Fellhoelter

(company name) Helmerich and Payne Inc. (phone) _____

were: 15" conductor at 60' w/90 sks cement: 10 3/4" S.P. 1180' cwc w/350 sks cement. 5½" casing set at 3690' w/150 sks cement. Open hole 3690' to 3937'. Casing good to 2955' Poor casiang below. Proposal 100 sks Class A Common and 500 sks 65/35 Poz 6% Gel. Pump in with pump truck. Spot with tubing. Load both 5½" casing and 5½" casing and 10 3/4" s.p. with cement. Shut in under pressure.

Plugging Proposal Received by Marion J. Schmidt (TECHNICIAN)

Plugging Operations attended by Agent?: All x Part _____ None _____

Operations Completed: Hour: 10:30AM Day: 16 Month: May Year: 19 89

ACTUAL PLUGGING REPORT Ordered 100 sks Class A Cement 2% Gel and 500 sks 65/35 Poz 6% gel and 5 sks Hulls. Spotted cement with tubing. 1. 2 7/8" tubing at 3376'. Spotted 100 sks Class A common cement. 2. 2 7/8" tubing at 2264'. Spotted 90 sks cement. Cement cir 65/35 poz 6% gel. 3. Squeezed 5½" casing w/15 sks cement. Max psig 400. Shut in at 400 psig. 4. Pumped 297 sks in annulus max pressure 500 psig. Shut in 300 psig.

INVOICED
DATE 6-8-89
INV. NO. 25011

Remarks: Cemented by Halliburton Cement 500 sks total cement.
(If additional description is necessary, use BACK of this form.)

I (did /~~did not~~) observe this plugging.

Signed Marion J. Schmidt (TECHNICIAN)

Note: spotted 100 sks class A on May 15, 1989
Tagged cement plug on May 16, 1989

Marvin Miller

FORM CP-2/3
Rev.01-84