

WELL PLUGGING RECORD

OR 15-051-05665-00-00
FORMATION PLUGGING RECORD

Strike out upper line
when reporting plugging
off formations.

Give All Information Completely
Make Required Affidavit
Mail or Deliver Report to:
Conservation Division
State Corporation Commission
800 Bitting Building
Wichita, Kansas

Ellis County, Sec. 6 Twp. 11 Rge. 17 (E) (W)

NORTH

Locate well correctly on above
Section Plat

Location as "NE $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$ " or footage from lines C/W $\frac{1}{2}$ NW $\frac{1}{2}$ NW $\frac{1}{2}$
Lease Owner The Dickey Oil Company
Lease Name N. Henderson Well No. C-1
Office Address Ellis-Sing. Bldg., Wichita, Kansas
Character of Well (completed as Oil, Gas or Dry Hole) Arbuckle lime
Date, well completed February 1, 1941 19.
Application for plugging filed February 1, 1941 19.
Application for plugging approved February 1, 1941 19.
Plugging Commenced February 1, 1941 19.
Plugging Completed February 1, 1941 19.
Reason for abandonment of well or producing formation dry

If a producing well is abandoned, date of last production 19.
Was permission obtained from the Conservation Division or its agents before plugging was commenced? Yes - by C. T. Alexander

Name of Conservation Agent who supervised plugging of this well C. T. Alexander
Producing formation Arbuckle Depth to top Bottom 3558 $\frac{1}{2}$ Total Depth of Well 3558 $\frac{1}{2}$ Feet
Show depth and thickness of all water, oil and gas formations.

OIL, GAS OR WATER RECORDS

CASING RECORD

Formation	Content	From	To	Size	Put In	Pulled Out
				10-3/4"	1271'	None

Describe in detail the manner in which the well was plugged, indicating where the mud fluid was placed and the method or methods used in introducing it into the hole. If cement or other plugs were used, state the character of same and depth placed, from 1231' feet to 1271' feet for each plug set.

Pumped heavy mud through drill pipe from bottom of hole to 1271'; set wood plug at bottom of 10-3/4" pipe at 1271'; run 20 sacks of ask grove cement through drill pipe; plugged top of 10-3/4" pipe with 10 $\frac{1}{2}$ " bull plug

PLUGGING
FILE SEC 6 T 11 R 17 W
BOOK PAGE 128

2-19-1941
FEB 19 1941
STATE CORP. COMM.
60 N. W. 2ND ST.

(If additional description is necessary, use BACK of this sheet)
Correspondence regarding this well should be addressed to The Dickey Oil Company
Address Ellis-Singleton Building, Wichita, Kansas

STATE OF Kansas, COUNTY OF Sedgwick, ss.
Wayne Bradley (employee of owner) or owner or operator of the above-described well,
being first duly sworn on oath, says: That I have knowledge of the facts, statements, and matters herein contained and the log of the above-described well as filed and that the same are true and correct. So help me God.

(Signature) Wayne Bradley

Ellis-Singleton Bldg., Wichita, Kansas (Address)

SUBSCRIBED AND SWORN to before me this 17th day of February, 1941.

My commission expires: Aug 2, 1941.

Paul W. Keeling
Notary Public.



15-051-05665-00-00

THE DICKEY OIL COMPANY
Henderson-C #1

COMMENCED: 1-13-41
COMPLETED: 2- 1-41

LOCATION: C-W $\frac{1}{2}$ NW $\frac{1}{4}$ NW $\frac{1}{4}$ 6-11-17
Ellis County, Kansas
ELEVATION: 1984

Pipe Record
1250' 10"

Shale	40
shale and shells	750
water sand	875
red bed	1257
anhydrite	1295
shale and shells	1530
salt	1710
shale and shells	2050
shale and lime	2130
broken lime	2150
lime	2158
broken lime	2242
lime	2300
shale and shells	2327
broken lime	2415
shale and shells	2930
top Topeka lime	2950
lime	3111
shale and lime	3155
lime	3197
lime and shale	3236
top K. C. lime	3236
lime	3410
conglomerate	3435
lime	3481
chert	3486
lime	3490
conglomerate	3537
green shale	3552
top Arbuckle	3356 $\frac{1}{2}$
sand	3357
dolomite	3558 $\frac{1}{2}$
T.D. corrected to Derrick Floor	3556

INDEXING	
FILE	6 11 176
BOOK	128
PAGE	1

