KANSAS CORPORATION COMMISSION
ONE POINT STABLIZED OPEN FLOW OR DELIVERABILITY TEST

FORM G-2
(Rev.8/98)

TYPE TEST:
☒ Open Flow
☒ Deliverability

TEST DATE: 2/9/02

API No. 15-023-20379-0000

Company	Lease	Well Number
Priority Oil & Gas LLC	Holzworth	2-17

County	Location	Section	TWP	RNG(E/W)	Acres Attributed
Cheyenne	SE SW SW	17	4s	40w	

Field	Reservoir	Gas Gathering Connection
Dent Field	Niobrara	Kinder-Morgan

Completion Date	Plug Back Total Depth	Packer Set at
4/19/01	1330	

Casing Size	Weight	Internal Diameter	Set at	Perforations	To
4.500	10.500	4.052	1372	1230	1265

Tubing Size	Weight	Internal Diameter	Set at	Perforations	To
NONE					

Type Completion (Describe)	Type Fluid Production	Pump Unit or Traveling Plunger?
Frac		No

Producing Thru (Annulus/Tubing)	% Carbon Dioxide	% Nitrogen	Gas Gravity- Gg
casing	.575	3.481	.586

Vertical Depth (H)	Pressure Taps	Meter Run Size
1247	Flange	2

RECEIVED
FEB 25 2002
KCC WICHITA

Pressure Buildup: Shut in	2/6/02@12:00	TAKEN	2/8/02@10:15
Well on Line: Started	2/8/02@10:15	TAKEN	2/9/02@12:50

OBSERVED SURFACE DATA

Static/ Dynamic Property	Orifice Size in.	Meter Pressure psig	Pressure Diff. In. H_2O	Flowing Temp. t.	WellHead Temp. t.	Casing WellHead Press. (P_w) (P_t) (P_c) psig	Casing WellHead Press. psia	Tubing WellHead Press. (P_w) (P_t) (P_c) psig	Tubing WellHead Press. psia	Duration (Hours)	Liquid Prod. Barrels
Shut-in						135	147			72.0	
Flow	.500	95.5	19.00	26		112	124			24.0	

FLOW STREAM ATTRIBUTES

COEFFICIENT (F_b) Mcfd	(METER) PRESSURE psia	EXTENSION $\sqrt{P_m \times H_w}$	GRAVITY FACTOR Fg	FLOWING TEMP FACTOR Ft	DEVIATION FACTOR Fpv	RATE OF FLOW R Mcfd	GOR	G_m
1.219	108.0	45.30	1.3063	1.0344	1.0097	75		.586

(OPEN FLOW)(DELIVERABILITY) CALCULATIONS

$(Pc)^2$ = 21.8 $(Pw)^2$ = 15.5 Pd = 64.7 % (Pc - 14.4) + 14.4 = $(Pa)^2$ = 0.207 $(Pd)^2$ = 9.12

$(P_c)^2 - (P_a)^2$ or $(P_c)^2 - (P_d)^2$	$(P_c)^2 - (P_w)^2$	$\frac{(P_c)^2 - (P_a)^2 \text{ or } (P_c)^2 - (P_d)^2}{(P_c)^2 - (P_w)^2}$	LOG [ ]	Backpressure Curve Slope "n" ---- or ---- Assigned Standard Slope	n x LOG [ ]	Antilog	Open Flow Deliverability = R x Antilog Mcfd
21.60	6.25	3.453	.5382	.974	.5241	3.343	251
12.64	6.25	2.020	.3054	.974	.2974	1.983	149

OPEN FLOW 251 Mcfd @ 14.65 psia DELIVERABILITY 149 Mcfd @ 14.65 psia

The undersigned authority, on behaf of the Company, states that he is duly authorized to make the above report and that he has knowledge of the facts stated herein and that said report is true and correct. Executed this the 12 day of Feb, 20 02

Witness (if any)

For Company

For Commission

Checked by

Form G-2
Rev.8/98

I declare under penelty or perjury under the laws of the state of kansas that I am authorized to request exempt status under rule K.A.R. 82-3-304 on behalf of the operator Priority Oil & Gas LLC and that the foregoing information and statements contained on this application form are true and correct to the best of my knowledge and belief based upon gas production records and records of equipment installation and/or of type completion or upon use of the gas well herein named.

I hereby request a permanent exemption from open flow testing for the Holzworth gas well on the grounds that said well:

(check one)

- ☐ is a coalbed methane producer
- ☐ is cycled on plunger lift due to water
- ☐ is a source of natural gas for injection into an oil reservoir undergoing ER
- ☐ is on vacum at the present time; KCC approval Docket No. _____
- ☒ is incapable of producing at a daily rate in exess of 150 mcf/D

Date: 2-19-07

Signature: _____

Title: Admin. Asst.

Instructions:

All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.

PRECISION MEASUREMENT, INC.
P.O.Box 3659
745 North Circle Drive
Casper, WY. 82602

2/11/2002 6:41 PM
Phone: 307-237-9327
800-624-7260
Fax: 307-577-4139
E Mail: pmi@trib.com

GAS ANALYSIS REPORT

Analysis For: PRIORITY OIL & GAS
Field Name:
Well Name: 2-17 HOLZWARTH
Station Number:
Purpose:
Sample Deg. F: 28
Volume/Day:
Formation:
Line PSIG: 135
Line PSIA:

Run No: 5481-2
Date Run: 2/11/02
Date Sampled: 2/5/02
Producer:
County:
State:
Sampled By: K. ANDREWS
Atmos Deg. F:
LOCATION : SEC. 17-4S-40W

GAS COMPONENTS		MOL%	GPM
Carbon Dioxide	C02:	0.575	
Nitrogen	N2:	3.481	
Hydrogen Sulfide	H2s:	0.0000	
Methane	C1:	94.090	
Ethane	C2:	1.316	0.351
Propane	C3:	0.399	0.110
Iso-Butane	IC4:	0.068	0.022
Nor-Butane	NC4:	0.071	0.022
Iso-Pentane	IC5:	0.000	0.000
Nor-Pentane	NC5:	0.000	0.000
Hexane Plus	C6+:	0.000	0.000
Totals		100.000	0.505

Pressure Base: 14.730
Real BTU Dry: 992.405
Real BTU Wet: 975.137
Calc. Ideal Gravity: 0.586
Calc. Real Gravity: 0.587
Field Gravity:
Standard Pressure: 14.696
BTU Dry: 990.128
BTU Wet: 972.900
Z Factor: 0.998
Avg Mol Weight: 16.975
Avg CuFt/Gal: 59.842
Ethane+ GPM 0.505
Propane+ GPM: 0.154
Butane+ GPM: 0.045
Pentane+ GPM: 0.000

Analysis By: S.G. WALLACE
Approved By:

Remarks: