

87  
R

3-9

6 061801

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-051-02160-0000  
E/2 SW SE, SEC. 13, T 11 S, R 17 W&E

660 feet from S section line  
1650 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5214

Lease Name Pearl Cress Well # 4

Operator: Lario Oil and Gas Co.

County Ellis 110.31

Name & Address 301 S Market St.

Well Total Depth ~~3394~~ 3378 AWB feet KCC

Wichita, Ks. 67202

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 1/4 feet 1078

Abandoned Oil Well  Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ O&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Kelso Casing Pulling Inc. License Number 6050

Address Box 347 Chase, Ks. 67524

Company to plug at: Hour: 9:00AM Day: 9th Month: Mar Year: 19 89

Plugging proposal received from Vern Duntz

(company name) Kelso Casing Pulling Inc. (phone) 319-938-2457

were: Order 250 sks 60/40 Poz 8% Gel 3% Cal Cl 5 sk Hulls.

RECEIVED  
STATE CORPORATION COMMISSION

03-21-89  
MAR 21 1989

Plugging Proposal Received by Gilbert G. Scheck  
(TECHNICIAN)

Plugging Operations attended by Agent Wichita, Kansas Part None

Operations Completed: Hour: 10:00AM Day: 9 Month: March Year: 19 89

ACTUAL PLUGGING REPORT 8 1/4" set at 1078' w/350 sks. 5 1/2" set at 3376' w/125 sks.

Top perf at 3376'. Plugged bottom w/sand and 5 sks cement to 3325'.

Shot pipe one time and recovered 2400'. Pdumped in 8 1/4" 25 sks cement followed w/

5 sks Hulls in 225 sks cement w/400 psi.

Remarks: By Halliburton

(If additional description is necessary, use BACK of this form.)

I (client) do hereby observe this plugging.

Signed Gilbert G. Scheck  
Gilbert (TECHNICIAN)

DATE 3-23-89

INV. NO. 24201