

4-30-84 Contacted  
5-9-84

1100012

COBRA OIL & GAS  
E. J. TINE  
(316) 267-1333  
Rine Drilling

API NUMBER 15-025-20,764-00-00

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION NW NW NW, Sec. 26, T 34 S, R24 W/E  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

330 feet from N/E section line

TECHNICIAN'S PLUGGING REPORT

330 feet from W/E section line

Operator License # 6415

Lease Name Shutts Well # 26-1

Operator: Petro-Lewis Corp.  
Name & 5400 North Independence  
Address Oklahoma City, OK 73112

County Clark

Well Total Depth 7425 feet

405-948-3000

J.L. LANE  
(316) 792-3212  
Matt Eagleston

Conductor Pipe: Size 24.31 feet

Surface Casing: Size 8 5/8 feet 763

Abandoned Oil Well \_\_\_\_\_ Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Rine Drilling Co. License Number 5654

Address Ste. 600, 300 West Douglas, Wichita, KS 67202

Company to plug at: Hour: 10:30 am Day: 2 Month: February Year: 19 84

VERBAL PLUGGING ORDERS GIVEN TO Joe Parks

(company name) Rine Drilling (phone) 316-267-1333

were: to fill hole with heavy mud and spot cement through drill pipe

1st plug at 7292' with 50 sx cement

2nd plug at 800' with 50 sx cement

3rd plug at 480' with 40 sx cement  
wolid bridge

4th plug hulls - plug at 40' -- cement to surface with 15 sx cement.

6th plug to circulate rathole with 15 sx cement, 7th plug to circulate mouse hole with 10 sx cement, Plug water well with 5 sx cement

*Clyde Wiley*  
(TECHNICIAN)

Plugging Operations attended by Agent?: All  Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 8:30 pm Day: 2 Month: February Year: 19 84

ACTUAL PLUGGING REPORT 1st plug at 7292' with 50 sx cement, 2nd plug at 800' with 50

sx cement, 3rd plug at 480' with 40 sx cement, 4th & 5th plugs - solid bridge - hulls -

plug at 40' -- cement to surface with 15 sx cement. 6th plug to circulate rathole with

15 sx cement, 7th plug to circulate mousehole with 10 sx cement. Plug water well

with 5 sx cement.

Remarks: Use 60/40 Pozmix with 2% gel by Halliburton

Clyde Wiley gave plugging orders and Paul Luthi observed the entire operation.

I hereby certify that the above plugging instructions were given as herein stated and that I (did / ~~did not~~) observe this plugging.

INVOICE

DATE 2-13-84  
EXT. NO. 0184  
2-2

RECEIVED  
STATE CORPORATION COMMISSION  
FEB 06 1984  
CONSERVATION DIVISION  
Wichita, Kansas

Signed *Clyde Wiley*  
(TECHNICIAN)

FORM CP-2/3  
Rev. 9-82