

KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

| Type Test | : | | | | | (| See Instru | uction | s on Re | verse Side | 9) | | | | | | |
|--------------------------------------------|--------------|-----------------------------------------------------------------|---------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------------------|-----------------------------------------------------|------------------------------------------------------------------------------------------------|------------------------------------------------------|--------------------------------------------------------------------------------|-----------------------------|--------------------------------------|------------------------------------------------------------------|------------------------------|-------------------------------------------------------------|--|
| ✓ Op | en Flov | ٧ | | | | Test Date | , | | | | API | No. 15 | | | | | |
| De | liverabi | ity | | | | 12/17/0 | | | | | | 3-20600-00 | 000 | | | | |
| Company Priority | | Ga | as LLC | | | | | | _{Lease} Gustav | / Hilt | | | | 3-14 | Well Nu | ımber | |
| County Location Cheyenne SW SE SW | | | | Section 14 | * * * * * * * * * * * * * * * * * * * * | | | TWP 3 S | | RNG (E/W) 42 | | Acres Attributed | | | | | |
| Field C herry | Creel | k | | | | Reservoir Beech | er Islan | d/Nic | obrara | | | hering Conne y Oil & Gas | | ı | RE(| EIVE | |
| Completion Date 10/21/04 | | | | | Plug Back Total Depth 1586.65 | | | | Packer Set at | | | FEB 1 4 2005 | | | | | |
| Casing Size Weight 4.5 in 10.5 | | | | Internal Diameter 4.052 | | | Set at 1628.10 | | Perforations 1467 | | | 15 CC WICHI | | | | | |
| Tubing Size Weight none | | | Internal [| Internal Diameter Set at | | | ıt | Perforations | | | То | | | | | | |
| ype Com o2 Fra | • | (De | escribe) | | a unu | Type Flui none | d Product | ion | | | Pump Ui | nit or Traveling | Plunger? | Yes | / (No) | | |
| roducing casing | Thru | (Anr | nulus / Tubir | ig) | | % C | % Carbon Dioxide | | | | % Nitrog 3.77 | | Gas Gravity - G _。 .584 | | | | |
| /ertical D | epth(H) |) | | | | | Pr | essure | e Taps | | ··- | | (| Meter F | | rover) Size | |
| Pressure | Buildup | | Snut in | | | 0 at | | _ (AI | M) (PM) | Taken | | 20 | at | | | (AM) (PM) | |
| Well on Li | ine: | | Started 12 | /17. | /042 | 0 at | 1:42 | _ (A | M) (PM) | Taken | | 20 | at | | (| (AM) (PM) | |
| | | | Circle one: | | | 1 | OBSER\ | VED S | SURFACE | | | | Duration (| of Shut- | in_24 | Hours | |
| Static / Dynamic Property | amic Size | | Meter Prover Pressure psig (Pm) | | Pressure Differential in Inches H ₂ 0 | Flowing Temperature t | Temperature Temperature | | Casing Wellhead Pressure (P _w) or (P _t) or (P _c) psig psia | | Tubing Wellhead Pressure $(P_w) \text{ or } (P_t) \text{ or } (P_c)$ psig psia | | Duration (Hours) | | Liquid Produced (Barrels) | | |
| Shut-In | | | | | | | | | | | | | | | | | |
| Flow | .500 |) | | | *************************************** | | | | 207 | 221.4 | | | | | <u> </u> | | |
| | | | | · r · · | | 1 | FLOW S | TREA | M ATTRI | BUTES | | | | | | | |
| Plate Coefficeient $(F_b)(F_p)$ Mcfd | | Circle one: Meter or Prover Pressure psia | | | Press Extension P _m x h | Gravity Factor F _g | | Flowing Temperature Factor F ₁₁ | | Fa | Deviation Meter Factor F _{pv} (N | | (Cubic Fe | | et/ | Flowing Fluid Gravity G _m | |
| | | | | | | | | | · · · · · · · · · · · · · · · · · · · | | | | | | | | |
| P _c) ² = | | : | (P _w)² = | = | : | (OPEN FLO | | IVER | | CALCUL - 14.4) + | | : | | (P _a) ² (P _d) ² | != 0.2 != | 07 | |
| $(P_c)^2 - (P_a)^2$ or $(P_c)^2 - (P_d)^2$ | | (P _c) ² - (P _w) ² | | Cho | ose formula 1 or 2: 1. P _c ² - P _a ² 2. P _c ² - P _d ted by: P _c ² - P _w ² LOG of formula 1. or 2. and divide by: | | Back | | Backpres Slop Ass | ssure Curve he = "n" or signed ard Slope | n x | n x LOG | | Antilog | | Open Flow Deliverability Equals R x Antilog (Mcfd) | |
| | | - | | | | | · | | | | | | | | | | |
| Open Flow | | Mcfd @ 14.6 | | | | _l 65 psia | l5 psia | | | Deliverability | | Mc | | ofd @ 14.65 psia | | | |
| The u | ndersig | gned | authority, c | n b | ehalf of the | Company, s | tates that | he is | duly au | thorized to | make th | e above repor | | | | ledge of | |
| | | | | | report is true | | | | | | | January | | | | 20 <u>05</u> . | |
| | V | | Witness | (if any | ′) | | | | , | /Le | u'n | - Ar | ompany | ewi | <u> </u> | | |
| | | | | | | | (·m(·k····)····· | | | | | | mpany | | | | |
| | | | For Comr | nissio | n | | | | - | | | Check | red by | | | | |

| | der penalty of perjury under the laws of the state of Kansas der Rule K.A.R. 82-3-304 on behalf of the operator Priority Oil | |
|-------------------|------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| | going pressure information and statements contained on thi | |
| | st of my knowledge and belief based upon available productio | |
| | allation and/or upon type of completion or upon use being made | |
| • • | est a one-year exemption from open flow testing for the Gus | |
| | rounds that said well: | |
| , <u>J</u> | | RECEIVED |
| (Check | (one) | FEB 1 4 2005 |
| | is a coalbed methane producer | |
| | is cycled on plunger lift due to water | KCC WICHIT |
| | is a source of natural gas for injection into an oil reservoir u | undergoing ER |
| | is on vacuum at the present time; KCC approval Docket No. | • |
| • | is not capable of producing at a daily rate in excess of 250 | mcf/D |
| staff as necessar | ee to supply to the best of my ability any and all supporting do y to corroborate this claim for exemption from testing. | ocuments deemed by Commission |
| Date: 1/28/05 | | |
| | Signature: | J. |

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.