KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST (See Instructions on Reverse Side)

Type Test	i :					(See Instruc	rions on Hev	rerse Side,	,					
Oр	en Flo	w			Test Date	. .			API	No. 15				
De	liverat	oilty			rest Date	,				181	-2007Q-	000	>	
Company							Lease					Vell Number	-	
Lobo	Pr	odi	uction,	Inc.			Glasco	0	<u>3-31</u>					
County			Location		Section		TWP		RNG (E/	•	. /	Acres Attribut	ed	
Sher	man	<u> </u>	SW_S	W SW	31		<u>7s</u>		<u> 38W</u>					
Field		_			Reservoir					nering Connect	ion			
	dla			N	iobrar				Packer S	N				
Completio			•			k Total Depth) 20 "	1		Packers	el al				
11-		/3	Weight				Set a	<u> </u>	Perfo	rations	То			
Casing Size		weign	Internal Diameter			918'		Open Hole						
Tubing Size Weigh			Internal D	Set at		Perforations		То						
Type Com Sing					Type Flui	d Production	1		Pump Un	it or Traveling F	Plunger? Yes /	No		
			ulus / Tubing)		% Carbor	Dioxide			% Nitroge	en -		avity - G _g		
Casi		•	•								.5	81		
Vertical D		1)				Pressi	ure Taps				(Meter F	lun) XPXOX9X)	% ize	
Pressure	Buildu	ıp: {	Shut in7	/619	99 at	8:00	XXXX (PM)	Taken	7/7	199	9 at 8:00		(PM)	
Well on Li	ine:	5	Started	19	9 <u> </u>		(AM) (PM)	Taken		19 _	at	(AM) ((PM)	
						OBSERVE	D SURFACI	E DATA			Ouration of Shut-	n	Hours	
Static / Orific		Circle one:		Pressure	Flowing Well Head		Casing Mallhood Brooking		Tubing Wellhood Bressure		Duration Liquid Pr		luced	
Dynamic S		e	Meter of Prover Pressur	Differential e in (h)		1	Wellhead Pressure (P _m) or (P ₁) or (P _c)		Wellhead Pressure (P _w) or (P _t) or (P _c) psig psia		(Hours)		(Barrels)	
		nches psig		Inches H ₂ 0	t	t	psig	psia						
Shut-In						,	22					•		
Flow														
						FLOW STR	EAM ATTR	BUTES						
Plate Coefficient (F _b) (F _p) Mcfd		Circle one: Meter.or Prover Pressure psia		Press Extension √P _m x H _w	Grav Fact	tor	Flowing Temperature Factor F ₁₁		iation ictor : pv	Metered Flow R (Mcfd)	GOR (Cubic Fe Barrel)	et/ Fi	owing luid avity G _m	
								<u> </u>			<u></u>]	
(D.)2 -			(P _w) ² =		•	OW) (DELIV		CALCUL - 14.4) +		:	(P _a) ² (P _d) ²	? = 0.207 ? =		
(P _c) ² =		=:-		Choose formula 1 or 2			1	ssure Curve	1					
(P _c)² - (F)²	(P	c)2 - (P_)2	1. P _c ² -P _s ²	LOG of formula		Slop	e = "n"	nxl	_og	Antilon	Open Flo Deliverabi		
$(P_c)^2 \cdot (P_a)^2$ or $(P_c)^2 \cdot (P_d)^2$		1		2. P _c ² ·P _d ² livided by: P _c ² ·P _w ²	1. or 2. and divide	P _c ² · P _w ²	Assigned Standard Slope		-		Anulog	Antilog Equals R x Antilog Mcfd		
							<u> </u>							
Open Flow Mcfd @ 14.6			5 psia Deliverability			ity	ST. MCRITE PARENCHINISSION							
						ton that ha !-			ke the sh					
				s true and corre			23	day o		// (hatte cask now	ィኅ9 <u>의</u> Division	9 .	
			Witness (il	any)			_	-f	our	For Co	mpanjenita, Ka	nsas -	.,.	
			For Comm	ission			-			Check	ed by			

exempt sta	are under penalty or perjury under the laws of the state of Kansas that I am authorized to request atus under Rule K.A.R. 82-3-304 on behalf of the operator Lobo Production, Inc. The foregoing information and statements contained on this application form are true and correct to
	f my knowledge and belief based upon gas production records and records of equipment installa-
	r of type completion or upon use of the gas well herein named.
	by request a permanent exemption from open flow testing for the <u>Glasco 3-31</u>
	n the grounds that said well:
Date:	is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No. is incapable of producing at a daily rate in excess of 150 mcf/D
	Signature:

Instructions:

All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data."

Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.