

5-5 4-041678

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 S. MARKET, ROOM #2078  
WICHITA, KANSAS 67202

API number: 15-051-22151-0001  
SE SE NW /4 SEC. 18, 11 S, 17 W  
2970 feet from S section line  
2970 feet from E section line

Operator license# 3613

Lease Carmichael <sup>A</sup> well # 11

Operator: Hallwood Petroleum

County Ellis 113.62

Address: Box 404  
Plainville, Kansas 67664

Well total depth 3496 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 8 5/8 Inch @ 193 feet  
w/225 sxs.

Aband. oil well ~~X~~, Gas well     , Input well     , SWD     , D & A ~~X~~     

Plugging contractor: Halliburton Cementing License#     

Address: Hays, Kansas 67601

Company to plug at: Hour: 9:00A.M. Day: 5 Month: May Year: 95

Plugging proposal received from: Aven Weaverling

Company: Hallwood Petroleum Phone:     

Were: 5 1/2" casing set at 3495' w/130 sxs. cement. Perf. at 3014' - 3196'. Anhy. at 1145' w/275 sxs. W.L.M. at 3300'. CIBP at 3413' w/ one sxs. cement. CIBP at 3350'. May 5, 1995 - hole swabbed and checked for new production - non-commercial. Ordered 300 sxs. 60/40 pozmix - 10% gel with 1/4# F.C. plus 500# hulls.

Plugging Proposal Received by: Dennis L. Hamel  
Plugging operations attended by agent? All[  ], Part[  ], None[  ]

Completed: Hour: 12:00P.M., Day: 5, Month: May, Year: 95

Actual plugging report: Hooked-up cementors to 5 1/2" casing - pumped in 300 sxs. cement with 500# hulls. Max. P.S.I. 900#. S.I.P. 200#. Cement at surface in 5 1/2" x 8 5/8" annulus.

Remarks:       
Condition of casing(in hole): GOOD  BAD  Anhy. plug: YES  NO   
Bottom plug(in place): YES , CALC , NO  Dakota plug: YES , NO   
Plugged through TUBING , CASING . Elevation: 1887 GL

I did  did not  observe the plugging.

Dennis L. Hamel  
(agent)

INVOICED  
DATE 5-24-95  
INV. NO. 42892

RCVD  
05-24-95