KANSAS CORPORATION COMMISSION ONE POINT STABILIZED OPEN FLOW OR DELIVERABILITY TEST

у _ОЕВ		Test Date 10-218	: 228 2010			API	No. 15				
	······································	10-2 1 8	: 29 2010			API	IVO. 15				
_OEB	***************************************		122,2010)		15-	095-2137	7-00-	00		
	Company HERMAN L. LOEB			Lease VORAN				#1	Well Number		
y Location GMAN C N/2 NW/4		Section		TWP 29S		RNG (E/W) 7W			Acres Attribute		
c.		Reservoir MISS. CHERT			Gas Gathering Connection LUMEN ENERGY						
•		Plug Bac 4157				Packer Set at NONE					
Weight 10.50		Internal Diameter 3.927		Set at 4208		Perforations 4128		To 4152	2		
Weight 4.70		Internal Diameter 1.995		Set at 4160		Perforations OPEN		То			
ype Completion (Describe)		Type Fluid Production GAS,WATER			Pump Unit or Traveling Plunger? Yes / No PUMPING						
Annulus / Tubi	ing)	% C	arbon Diox	ide		% Nitrog	en	Gas (Gravity -	G _g	
			Pres	ssure Taps			· · · · · · · · · · · · · · · · · · ·	(Mete	r Run) (F	rover) Size	
Shut in)-21-10	0 at		· (AM) (PM)	Taken_1	0-22-10	20	at		(AM) (PM)	
										(AM) (PM)	
			OBSERVE	D SURFAC	E DATA			Duration of Shu	ıt-in	Hou	
Meter Prover Pres	Differential in	Flowing Temperature t	Well Head Temperature t	Wellhead Pressure (P_w) or (P_t) or (P_c)		Tubing Wellhead Pressure (P _w) or (P ₁) or (P _c) psig psla		Duration (Hours)		Liquid Produced (Barrels)	
				153				24			
	·		FLOW STR	REAM ATTR	IBUTES						
Plate Circle one: Press efficient Meter or Extension (Fp) Prover Pressure psia Pm x h		Gravity Factor F _g		Flowing Temperature Factor F ₁₁	Deviation Factor F _{pv}		Metered Flow R (Mcfd)	(Cubic F	GOR Flowing Cubic Feet/ Fluid Barrel) Gravity G _m		
	1	(OPEN FLO)W) (DELIV	ERABILITY) CALCUL	ATIONS		/P	\2 - O 3	07	
(P _w) ²		P _d = _		% (F	° _c - 14.4) +	14.4 =	<u> </u>				
$(P_c)^2 - (P_w)^2 \qquad 1. P_c^2 - P_a^2$ $2. P_c^2 - P_d^2$		LOG of formula 1. or 2. and divide by: P 2 - P 2		Backpressure Curve Slope = "n"or Assigned Standard Slope		n x log		Antilog	Open Flow Deliverability Equals R x Antilog (Mcfd)		
	Mcfd @ 14.6	65 psia		Deliverab	ility			Mcfd @ 14.65 ps	sia_		
				_						ledge of 20 10	
Witness	(if any)				٤	Tesh	() For C	Wheev ompany	\ RE	CEIVE	
	Annulus / Tubi Shut in Circle one: Meter or Prover Pressure psia (P_w)² (P_c)²- (P_w)² ed authority, of ein, and that significant in a significant in and that significant in a signi	The second of the ded authority, on behalf of the second	MISS. Plug Bac 4157 Weight Internal E 3.927 Weight 4.70 1.995 (Describe) Type Flui GAS,V Annulus / Tubing) % C Shut in 10-21-10 20 at Started 20 at Started 20 at Started 5 Circle one: Meter Prover Pressure psig (Pm) Inches H₂0 Circle one: Meter or Prover Pressure psia Flowing Temperature to Pressure psia Flowing Temp	MISS. CHERT Plug Back Total Der 4157 Weight 10.50 3.927 Weight 4.70 Internal Diameter 1.995 (Describe) Type Fluid Production GAS,WATER Annulus / Tubing) Pres Shut in 10-21-10 20 at Started 20 at Started Prover Pressure psig (Pm) The standard prover Pressure psig (Pm) Shut in 10-21-10 Clircle one: Meter Prover Pressure psig (Pm) Press Flowing Temperature 1 Flowing Temperature 1 Flow STF Clircle one: Meter or Prover Pressure psia Gravity Factor Facto	MISS. CHERT Plug Back Total Depth 4157 Weight Internal Diameter Set 10.50 3.927 420 Weight Internal Diameter Set 4.70 1.995 416 (Describe) Type Fluid Production GAS,WATER Annulus / Tubing) % Carbon Dioxide Pressure Taps Shut in 10-21-10 20 at (AM) (PM) Started 20 at (AM) (PM) Started Prover Pressure Prover Pressure Psig (Pm) Inches H ₂ 0 Temperature Prover Pressure Psia Psia Psia Psia Psia Psia Psia Psia	MISS. CHERT Plug Back Total Depth 4157 Weight Internal Diameter Set at 10.50 3.927 4208 Weight Internal Diameter Set at 4.70 1.995 4160 Type Fluid Production GAS, WATER Annulus / Tubing) % Carbon Dioxide Pressure Taps Shut in 10-21-10 20 at (AM) (PM) Taken 10-20 a	MISS. CHERT Plug Back Total Depth 4157 NONE Weight Internal Diameter Set at Performance of the Pump Uniter Set at Performance of the Pump Unit	MISS. CHERT	MISS. CHERT Plug Back Total Depth 4157 Plug Back Total Depth 4157 Weight 10.50 3.927 4208 4128 4158 4157 Weight Internal Diameter Set at Perforations To 4208 4128 4158 Plug Back Total Depth 4208 4128 4158 Missing Weight Internal Diameter Set at Perforations To OPEN Pump Unit or Traveling Plunger? Yee Pump Unit	MISS. CHERT Plug Back Total Depth 4157 Weight 10.50 3.927 4208 4128 4152 Weight 10.50 1.995 Weight 10.995 Pressure Taylor Weight 10.905 Weight 10.9	

	clare under penalty of perjury under the laws of the state of Kansas that I am authorized to request status under Rule K.A.R. 82-3-304 on behalf of the operator HERMAN L. LOEB
correct to of equipr	the foregoing pressure information and statements contained on this application form are true and to the best of my knowledge and belief based upon available production summaries and lease records ment installation and/or upon type of completion or upon use being made of the gas well herein named. The reby request a one-year exemption from open flow testing for the VORAN #1
	is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No. ✓ is not capable of producing at a daily rate in excess of 250 mcf/D ther agree to supply to the best of my ability any and all supporting documents deemed by Commission necessary to corroborate this claim for exemption from testing.
	Signature: Seshe H. Allan Title: REP. HERMAN L. LOEB

Instructions:

If a gas well meets one of the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to claim exempt status for the gas well.

At some point during the current calendar year, wellhead shut-in pressure shall have been measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under **OBSERVED SURFACE DATA**. Shut-in pressure shall thereafter be reported yearly in the same manner for so long as the gas well continues to meet the eligibility criterion or until the claim of eligibility for exemption **IS** denied.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than December 31 of the year for which it's intended to acquire exempt status for the subject well. The form must be signed and dated on the front side as though it was a verified report of annual test results.