

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15-051 - 23310-00-00

SE, Sec. 8, T 13 S, R 17 W10

330 feet from ~~W~~S section line

2310 feet from ~~E~~E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # C261

Lease Name L. Stueb Well # 2

Operator: Ernst + Steink Oil Operations  
Name & Address Box 859, Russell, Ks 67665

County Ellis

Well Total Depth 3649 feet \$118.59

Conductor Pipe: Size \_\_\_\_\_ feet

Surface Casing: Size 8 5/8" feet 265

Abandoned Oil Well X Gas Well \_\_\_\_\_ Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ D&A \_\_\_\_\_

Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Five Star Well Service Inc. License Number 7088

Address E. Hugo, 40, Hugo, Ks, 67601

Company to plug at: Hour: 2:00 PM Day: ~~5/11/83~~ Month: 5 Year: 19 83

VERBAL PLUGGING ORDERS GIVEN TO Rich Steinkley

(company name) Ernst + Steink Oil Operations (phone) 913-483-2585

were: Order 165 lbs. SP. pro mix - 4% gel. - 3% vol. U., 5 sh. balls, 20 sh. bel., 8 5/8" plug.

Signed G. G. L. L. L.  
(TECHNICIAN)

Plugging Operations attended by Agent?: All X Part \_\_\_\_\_ None \_\_\_\_\_

Operations Completed: Hour: 5:30 PM Day: 11 Month: 5 Year: 19 83

ACTUAL PLUGGING REPORT 8 5/8" - 265' SP. case w/ 165 sh. 5 1/2" set at 3649' w/ 200 sh.

Top perf. at 3589'. Plugged bottom w/ 5 sh. cement, sand & 5 sh. cement.  
Shot pipe 1 time & recovered 2100'. Pumped in 8 5/8" SP., 4 sh. balls, 15 sh.  
gel., 65 sh. cement, 5 sh. gel., 1 sh. balls, released plug & followed  
w/ 100 sh. cement w/ 800 pounds pressure.

Remarks: \_\_\_\_\_

RECEIVED  
STATE CORPORATION COMMISSION  
05-20-1983  
MAY 20 1983

CONSERVATION DIVISION  
Wichita, Kansas

I hereby certify that the above plugging instructions were given as herein stated  
and that I (did / did not) observe this plugging.

Signed G. G. L. L. L. ✓  
(TECHNICIAN)

INVOICED

DATE 5-23-83  
INV. NO. 4403-6