Kansas Corporation Commission One Point Stabilized Open Flow or Deliverability Test

Type Test	:				(See Instru	ctions on l	Pevers	se Side)						
Open Flow X Shut-in Deliverability Pressure					Test Date: 12-17-05					API No. 15 -103-21,091					
Company		 ⊢ R/	esources	. Inc.			Lease Gruer						₩e #3	ll Number	
County Location N/2,S/2,NE				Section 12	000.0			rwp RNG (E/W) 10S 22E			Acres Attributed 40				
Field Fairmount					Reservoir McLouth				Gas Gathering Connection COG Transmission Corporation						
				Plug Back 1192'	Plug Back Total Depth 1192'				Packer S	et at					
Casing Size Weight 10.5#				Internal D		Set at 1192'			Perforations 1092			7ο 92' - 1100'			
Tubing Size Weight 2 3/8" 4.7#			Internal D		Set at 1080'			Perforations			То				
Type Completion (Describe) Gas				Type Fluid Water	ก				Pump Unit or Trespond Stands ? Pump			Yes /xNo			
Producing Thru (Annulus / Tubing) Annulus				% Carbon Nil				% Nitroge Nil	en	Gas Gravily - G _o					
Vertical D	epth(F	1)				Pres	sure Taps			,		(Me	eter Rur 2") (Proyer) Size	
Pressure	Buildu	p: :	Shut in12:	-1620	05at	9:00	(AM) (R2	Ma) Tal	ken	12-17	200)5_ al9	:00	(AM) (#2KB)\$	
Well on L	ine:	9	Started	19	at		_ (AM) (PI	M) Tal	ken		19	at		(AM) (PM)	
						OBSERV	ED SURF	ACE D	ATA		_	Duration of	Shut-in	Hours	
Static / Orlfice Dynamic Size Property inches		e	Circle one: Mater of Prover Pressu	1 1	Flowing Temperature t	Well Head Temperatur t	e Wellhe	Casing Wellhead Pressure $(P_w) \text{ or } (P_1) \text{ or } (P_c)$		Tubing Wellhead Pressure (P _w) or (P ₁) or (P _c)		Duration (Hours)		Liquid Produced (Barrels)	
Shul-In -			psig 	Inches H ₂ 0			psig 20		psia	psig	psia	24			
Flow		-												·	
						FLOW ST	REAM AT	TRIBL	UTES	···					
Plate Coeffiecient (F _b) (F _p) Mold		Pro	Circle one: Mater or over Pressure psia	Press Extension	Gravity Factor F		Flowing Temperature Factor		Deviation Factor F _p ,		Metered Flor R (McId)	GOR (Cubic Feet Barrel)		Flowing Fluid Gravity G _m	
	_									ATIONS	, -				
(P _e) ² =		:	(P_)² =	·:	(OPEN FL		_% _%			14.4 =	:		$(P_a)^2 = \frac{(P_a)^2}{(P_a)^2}$	0.207	
(P ₄) ² - (P ₄) ² or (P ₂) ² - (P ₄) ²		(P _g) ² · (P _w) ²		1. P ₂ ² - P ₂ ² 2. P ₂ ² - P ₂ ²	1. P ² -P ² LOG of formula 2. P ² -P ² 1. or 2.			Backpressure Curve Slope = "n" Assigned Slandard Slope		1		Antilog		Open Flow Deliverability Equals R x Antilog Mctd	
-		_		divided by: P2 - P	2 by:	P.1 - P.1	3	langaro	1 Slupe						
		-									<u> </u>				
Open Flo	w	1		Mcfd @ 14.	65 psia		Delive	rability	, <u></u>	<u> </u>	-	Mcld @ 14.6	5 psia		
The stated the	unders	igne	d authority, or at said report	is true and com	ECEIN	ou this the	is duly au		ed to ma		December		knowle	dge of the facts	
			Witness	(il anv)	N 0 3 20 2 WICH			_		Presi		Company	•		
				1101	<u>کې۷۷۱کټ</u>	711/4		_		T T C D T					

exempt and tha the bes	eclare under penalty or perjury under the laws of the state of Kansas that I am authorized to request it status under Rule K.A.R. 82-3-304 on behalf of the operator <u>Monument Resources</u> , <u>Inc</u> . at the foregoing information and statements contained on this application form are true and correct to st of my knowledge and belief based upon gas production records and records of equipment installa-
	d/or of type completion or upon use of the gas well herein named.
l he	ereby request a permanent exemption from open flow testing for theGruendel #3
gas wel	If on the grounds that said well:
Date:	is a coalbed methane producer is cycled on plunger lift due to water is a source of natural gas for injection into an oil reservoir undergoing ER is on vacuum at the present time; KCC approval Docket No. x is incapable of producing at a daily rate in excess of 150 mcf/D December 30, 2005
	Signature:

Instructions:

All active gas wells must have at least an original G-2 form on file with the conservation division. If a gas well meets the eligibility criteria set out in KCC regulation K.A.R. 82-3-304, the operator may complete the statement provided above in order to obtain a testing exemption.

At some point during the succeeding calendar year, wellhead shut-in pressure shall be measured after a minimum of 24 hours shut-in/buildup time and shall be reported on the front side of this form under "observed surface data." Shut-in pressure shall thereafter be reported yearly in the same manner.

The G-2 form conveying the newest shut-in pressure reading shall be filed with the Wichita office no later than thirty (30) days after the taking of the pressure reading. The form must be signed and dated on the front side as though it was a verified report of test results.