

DISTRICT CONSERVATION AGENT'S REPORT

*R*

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

15-051-04241-00-00

FILE NO. \_\_\_\_\_

LOCATION NE NE SW

SEC. 31 TWP. 13 RGE. 19 *W*

Dry Hole x Abandoned Oil Well \_\_\_\_\_ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. 3 Lease ~~Reidel~~ *Riedel*

Operator The Texas Co Address Wichita, Kans

Field \_\_\_\_\_ County Ellis

Total Depth 4052 Feet.

(Describe briefly the manner in which the well was plugged)

8 5/8" at 645' circulated with cement.

Circulated hole with heavy rotary mud, pushed cementing  
plug to 300', displaced 20 sax cement through drill pipe,  
mud to 40', set cementing plug, 1/2 sack hulls and 10  
sax cement to bottom cellar.

Cementing by Halliburton Co

RECEIVED  
STATE CORPORATION COMMISSION  
05-05-52  
MAY - 5 1952

CONSERVATION DIVISION  
Wichita, Kansas

*J. D. Perry*  
District Conservation Agent

Date 5-2-52

PLUGGING  
FILE NO. 31 T 13 R 19 W  
BOOK 13 PAGE 13 LINE 42

*F*