

4-29

4-041898

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

API Number: 15-051-03437-0000  
SE-NW-NE  
/4 SEC. 25, 11 S, 17 W  
990 feet from N section line  
1650 feet from E section line

Operator license# 5447

Lease: Colahan "B" Well # 5

Operator: OXY USA, Inc.

County: Ellis 109.92

Address: P.O. Box 300  
Tulsa, OK 74102-0300

Well total depth 3382 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 10 3/4 Inch @ 1070 feet  
w/ 300 sxs.cmt.

Aband. oil well , Gas well , Input well , SWD , D & A

Plugging contractor: Allied Cementing License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: 9:00A.M. Day: 29 Month: April Year 1997

Plugging proposal received from: Gary Wagner

Company: OXY USA, Inc. Phone: \_\_\_\_\_

Were: 5 1/2" casing set at 3368' w/100 sxs cement. Anhy. at 1000'. Perf at 1000'  
Ordered 425 sxs 60/40 pozmix - 10% gel with 1/4# F.C. plus 600# hulls - 10 sxs gel

RECEIVED  
KANSAS  
CDRP  
COMM  
SO  
1997  
MAY  
23  
A  
1:51

05-23-97

Plugging Proposal Received by: Dennis Hamel  
Plugging operations attended by agent? All[  ], Part[  ], None[  ]

Completed: Hour: 2:00 P.M., Day: 29, Month: April, Year: 1997

Actual plugging report: 5 1/2" casing. Squeezed down casing with 25 sxs cement plus 300# hulls, followed with 10 sxs gel spacer, followed with 225 sxs cement with 300# hulls.  
Max. P.S.I. 1000#. S.I.P. 500#.  
8 5/8" S.P. Squeezed 30 sxs cement to Max. P.S.I. 600#. S.I.P. 400#.

Remarks: Checked cement on May 1, 1997 - OK. Filled to surface with 75 sxs cement.  
Condition of casing(in hole): GOOD  BAD  Anhy.plug: YES  NO   
Bottom plug(in place): YES , CALC , NO  Dakota plug: YES , NO   
Plugged through TUBING , CASING . Elevation: \_\_\_\_\_ G.L.

I did[  ] / did not[  ] observe the plugging.

Dennis J. Hamel  
(agent)

Form CP-2/3

**INVOICED**

DATE MAY 28 1997

INV. NO. 48186

4-29