

4-28

4-041894

API Number: <sup>15</sup> 051-19389-0000

TO:  
STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
130 SOUTH MARKET, SUITE 2078  
WICHITA, KANSAS 67202

NWNE SE /4 SEC. 26, 11 S, 17 W  
2310 feet from S section line  
990 feet from E section line

Operator license# 5447

Lease: McCord "A" Well # 9

Operator: OXY USA, Inc.

County: Ellis 116.64

Address: P.O. Box 300  
Tulsa, OK 74102-0300

Well total depth 3589 feet  
Conductor Pipe: 0 inch @ 0 feet  
Surface pipe 10 3/4 Inch @ 1105 feet  
w/ 335 sxs.cmt.

Aband. oil well , Gas well , Input well , SWD , D & A

Plugging contractor: Allied Cementing License# -

Address: Russell, Kansas 67665

Company to plug at: Hour: 8:00A.M. Day: 28 Month: April Year 1997

Plugging proposal received from: Gary Wagner

Company: OXY USA, Inc. Phone: \_\_\_\_\_

Were: 5 1/2" casing set at 3589' w/100 sxs cement. Perf at 3540' - 3551'. Squeeze at 1158' - 1173' w/200 sxs cwc. Squeeze at 2443' - 2504' w/60 sxs.  
Ordered 300 sxs 60/40 pozmix - 10% gel with 1/4# F.C. plus 600# hulls - 10 sxs gel.

Plugging Proposal Received by: Dennis Hamel

Plugging operations attended by agent? All[  ], Part[  ], None[  ]

Completed: Hour: 12:30 P.M., Day: 28, Month: April, Year: 1997

Actual plugging report: 5 1/2" casing. Squeezed 25 sxs cement with 200# hulls, followed with 10 sxs gel, followed with 235 sxs cement. Max. P.S.I. 800#. S.I.P. 500#. 8 5/8" S.P. Pressured-up to 500#.

RECEIVED  
KANSAS  
OHP  
COMM  
1997 MAY 22 A 12:58

05-22-97

Remarks: Checked cement on May 1, 1997 - OK.

Condition of casing(in hole): GOOD  BAD   
Bottom plug(in place): YES , CALC , NO   
Plugged through TUBING , CASING

Anhy.plug: YES  NO   
Dakota plug: YES , NO   
Elevation: \_\_\_\_\_ G.L.

I did[  ] / did not[  ] observe the plugging.

Dennis L Hamel  
(agent)

Form CP-2/3

**INVOICED**

DATE 5-22-97

INV. NO. 48163  
4-28

ND