

4-041463

4-11

02-867-0000

TO: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API number: 15-057 - 9-1943

W2 NW NW /4 SEC. 06 , 13 S, 20 W
4620 feet from S section line
4950 feet from E section line

Operator license# 5364 Lease Bittel well # B-2

Operator: Beren Corporation County Ellis

Address: Box 723 Well total depth 3840 feet
Hays, Kansas 67601 Conductor Pipe: 0 inch @ 0 feet
Surface pipe 7 Inch @ 118 feet

124.80

Aband. oil well X, Gas well , Input well , SWD , D & A

Plugging contractor: Allied Cementing License#

Address: Hays, Kansas 67601

Company to plug at: Hour: 11:00A.M Day: 11 Month: April Year: 93

Plugging proposal received from: George Jorgensen

Company: Beren Corporation Phone: 913-628-6101

Were: 7" casing set @ 3821' w/N.A.sx. cement. Perf. @ 3490' -
3821'. Anhy. - Perf. @ 1540'. Dakota Top @ 400'.
Order 400 sxs. 60/40 pozmix - 10% gel. with 1/4# F.C. plus 500# hulls
plus 12 sx. gel.

Plugging Proposal Received by: Dennis L. Hamel
Plugging operations attended by agent? All[X], Part[], None[]

Completed: Hour: 3:15P.M., Day: 11, Month: April, Year: 93

Actual plugging report: R.I.H. with tubing to 3600' spot 50 sx. cement
w/300# hulls mixed in cement. Pull tubing to 3200'. Spot 10 sx. gel.
Pull tubing to 1600'. Spot 200 sx. cement to circulate @ surface.
P.O.O.H. with tubing, squeezed 75 sxs. cement in casing from surface.
Max. 800#. S.I. 500#. Hooked-up to 10 3/4" S.P. Pumped in 500 sx.
cement w/100# hulls. Max. 400#. S.I. 300#.

Remarks:
Condition of casing(in hole): GOOD BAD Anhy. plug: YES X NO
Bottom plug(in place): YES X, CALC , NO Dakota plug: YES X, NO
Plugged through TUBING X, CASING . Elevation: GL

I did X / did not observe the plugging.

Dennis L. Hamel STATE CORPORATION COMMISSION

INVOICED

DATE 6-11-93

INV. NO. 37879

(agent)
Form CP-2/3 6-9-93
RECEIVED
JUN 9 1993
CONSERVATION DIVISION
Wichita, Kansas