

TO:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING
130 SOUTH MARKET, SUITE 2078
WICHITA, KANSAS 67202

API Well Number: 15-051-23776-00-00
Spot: E2NWNW Sec/Twnshp/Rge: 8-13S-18W
4620 feet from S Section Line, 4290 feet from E Section Line
Lease/Unit Name: POLIFKA B Well Number: 1
County: ELLIS Total Vertical Depth: 3832 feet

Operator License No.: 7064
Op Name: CATTLEMANS OIL OPERATIONS
Address: 2260 CATHERINE RD.
HAYS, KS 67601

Conductor Pipe: Size feet: 124.54
Surface Casing: Size 8.625 feet: 201 150 Sx
Production: Size 5.5 feet: 3829 175 sx
Liner: Size feet:

Well Type: OIL UIC Docket No: Date/Time to Plug: 02/06/2002 10:00 AM
Plug Co. License No.: 7064 Plug Co. Name: CATTLEMANS OIL OPERATIONS
Proposal Rcvd. from: LEO DORZWEILER Company: CATTLEMANS OIL OPERATIONS Phone: (785) 625-5394

Proposed Plugging Method: According to KCC Rules and Regulations.
Order 250 sxs cement - 18 sxs gel - 500# hulls.

Plugging Proposal Received By: ROGER MOSES WitnessType: Plugging Operations 100% Witnessed (Complete)
Date/Time Plugging Completed: 02/06/2002 11:30 AM KCC Agent: ROGER MOSES

Actual Plugging Report:

8 5/8" S.P. set at 201' w/150 sxs cmt. 5 1/2" casing set at 3825' w/175 sxs cmt.
D.V. Tool at 1467' w/425 sxs - did circulate.
Tied to 5 1/2" x 8 5/8" annulus - pressure to 200#. Solid.
Tied to 5 1/2" casing and pumped 50 sxs cement with 400# hulls - 15 sxs gel and 100# hulls.
Pumped 200 sxs cement to Max. P.S.I. 500#. S.I.P. 250#.
Total of 250 sxs 60/40 pozmix with 10% gel - 15 sxs gel and 500# hulls.

RECEIVED
FEB - 8 2002
KCC WICHITA

Remarks: LEASE READS AS FOLLOWS: 30'N.OF CE/2NWNW 08-13-18W. ALLIED CEMENTING COMPANY.

Plugged through: CSG

District: 04

Signed

Roger Moses
(TECHNICIAN)

INVOICED

Form CP-2/3

DATE Feb 12, 02

INV. NO. 2002061371

FEB 06 2002

RECEIVED

FEB - 8 2002

KCC WICHITA

CATTLEMANS OIL OPERATIONS
HC 39, BOX 74 #1 "B" POLIFKA 8-13-18W
HAYS, KS 67601 C E/2 NW NW
CONTR RANGER DRILLING, INC. CTY ELLIS
GEOL FIELD POI
ELV 2187 KB SPD 1/28/84 CARD ISSUED 6/14/84 IP P 3.5 BO & 31.5BWPD
2182 GL LKC 3512-3566 OA

+	+	+
+	+	+
+	+	+

LOG	Tops	Depth/Datum	API 15-051-23,776
			8-5/8" 201 / 150SX, 5 1/2" 3829 / 175SX, DV TOOL AT 1467 / 425SX
ANH	1487+	700	DST (1) 3508-3540 (LKC) / ?-30-?-60, REC 420' MUD, SIP 543-558#, FP NOT RECORDED
TOP	3205	1018	
HEEB	3443	1256	DST (2) 3552-3585 (LKC) / 45-45-45-45, WB BOTH OP'S, REC 345' HO & GCM, SIP 427-413#, FP 72-130 / 151-159#
TOR	3464	1277	
LANS	3491	1304	MICT - CO, PF (LKC) 3563-66, 3550-52, W/3 SPF, AC 1500G (14% INS), SWB LD, SO, PF (LKC) 3512-20, W/3 SPF, AC 1500G (14% INS), SWB LD, SO, SET 2 7/8" TBG AT 3780', POP, P 3:5 BO & 31.5 BWP, 3/15/84
BKC	3713	1526	
MARM CHT	3746	1559	
ARB	3817	1630	
RTD	3832	1645	

CORRECTION: 6/14/84 - ORIGINALLY FIRST REPORTED IN C E/2 NW NW