KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

ORIGINAL

Form ACO-1 June 2009 Form Must Be Typed Form must be Signed All blanks must be Filled


WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License # 32461	API No. 15 - 003-24862-0000
Name: Tailwater, Inc.	
Address 1: 6421 Avondale Dr., Ste. 212	Spot Description: Sweet as Sw Sw Sec. 15 Twp. 20 S. R. 20 East West
Address 2:	825 449 Feet from North / South Line of Section
City: OKC State: OK Zip: 73116 +	825 4807 Feet from East / West Line of Section
Contact Person: Christian L. Martin	Footages Calculated from Nearest Outside Section Corner:
Phone: (405) 810-0900	NE □NW □SE □SW
CONTRACTOR: License # 8509	County: Anderson
LIANA LAAMAI I Jarralanmant Ina	│ West Wiftman 10-T
- 1-	Lease Name: Well #: 1001 Field Name: Garnett Shoestring
Purchaser: Pacer Energy	Producing Formation: Squirrel
Designate Type of Completion:	Elevation: Ground 952 est Kelly Bushing: n/a
New Well Re-Entry Workover	Total Depth: 737' Plug Back Total Depth: n/a
☑ Oil □ wsw □ swd □ slow	Amount of Surface Pipe Set and Cemented at: 24.2
☐ Gas ☐ D&A ☐ ENHR ☐ SIGW	Multiple Stage Cementing Collar Used? 🔲 Yes 🗹 No
☐ OG ☐ GSW ☐ Temp. Abd.	If yes, show depth set: Feet
CM (Coal Bed Methane)	If Alternate II completion, cement circulated from:
Cathodic Other (Core, Expl., etc.):	feet depth to: 24.2' w/ 6 sx cmt.
If Workover/Re-entry: Old Well Info as follows:	
Operator:	Drilling Fluid Management Plan
Well Name:	(Data must be collected from the Reserve Pit)
Original Comp. Date: Original Total Depth:	Chloride content:ppm Fluid volume:bbls
☐ Deepening ☐ Re-perf. ☐ Conv. to ENHR ☐ Conv. to SWD	
Conv. to GSW	Dewatering method used:
Plug Back: Plug Back Total Depth	Location of fluid disposal if hauled offsite:
Commingled Permit #:	Operator Name:
Dual Completion Permit #:	Lease Name: License #:
SWD Permit #:	QuarterSecTwpS. R East
ENHR Permit #:	County: Permit #:
GSW Permit #:	Former.
Spud Date or Date Reached TD Completion Date or	
Recompletion Date Recompletion Date	
INSTRUCTIONS: An original and two copies of this form shall be filed with Kansas 67202, within 120 days of the spud date, recompletion, workover or copy of side two of this form will be held confidential for a period of 12 months if rectiality in excess of 12 months). One copy of all wireline logs and geologist well BE ATTACHED. Submit CP-4 form with all plugged wells. Submit CP-111 for	onversion of a well Rule 82-3-130, 82-3-106 and 82-3-107 apply. Information quested in writing and submitted with the form (see rule 82-3-107 for confiden II report shall be attached with this form. ALL CEMENTING TICKETS MUST
AFFIDAVIT	KCC Office Use ONLY
I am the affiant and I hereby certify that all requirements of the statutes, rules and	regu
lations promulgated to regulate the oil and gas industry have been fully complied	1 1 () () () () () () () () ()
and the statements herein are complete and correct to the best of my knowledge	e. Confidential Release Date:
Stage & Mini	Wireline Log Received MAR 9.7 201
Signature: 1944 / Misley	Geologist Report Received
Title: Hace Mar, Date: 3-2-11	UIC Distribution

Side Two

Operator Name: 1al	lwater, Inc.			Leas	e Name:	vvest vvittin	ian	Well #: 1	<u>0-1</u>	
Sec. 15 Twp 20	s. R. <u>20</u>	Z Eas	t 🔲 West	Cour	nty: And	erson				
INSTRUCTIONS: Shiftime tool open and clarecovery, and flow ratiline Logs surveyed.	osed, flowing and shu tes if gas to surface to	ut-in press est, along	ures, whether s with final chart	shut-in pr	essure rea	ched static level	, hydrostatic _l	pressures, bottor	n hole tem	perature, fluid
Drill Stem Tests Taker			∕es ☑ No		ØL	og Formatio	on (Top), Dept	th and Datum		Sample
Samples Sent to Geo	ological Survey		∕es ☑ No		Nam Squi			Тор		Datum
Cores Taken Electric Log Run Electric Log Submitte (If no, Submit Cop	y) -					er's Log att	ached			
Gamma Rayn	Veutron	-179W-1	CASING	RECORU) N	ew Used			·	
		Rep			·	ermediate, produc	tion, etc.			
Purpose of String	Size Hole Drilled		ze Casing et (In O.D.)		/eight s. / Ft.	Setting Depth	Type of Cement			and Percent Additives
surface	9 7/8"	7"				24.2'	Portland	d 6		
completion	5 5/8"	2 7/8"				727'	Portland	107	50/5	0 POZ
Purpose: —— Perforate —— Protect Casing —— Plug Back TD —— Plug Off Zone	Depth Top Bottom	Тур	ADDITIONAL		TING / SQU	JEEZE RECORD		and Percent Additiv	es	
Shots Per Foot			RD - Bridge Plug Each Interval Per		e			ment Squeeze Rec	ord	Depth
2	668 - 678' (21					75 gal. 15% HCL			Бери	
		B1-4P				30 sx san	id - 120 b	obl H2O		
TUBING RECORD:	Size:	Set At	:	Packer	At:	Liner Run:				
	2 7/8" Production, SWD or EN	727'	Producing Man	and:			Yes 📝	No		
8/31/10	Froduction, SWD of EN	rin.	Producing Met	nod: Pump	oing [Gas Lift 🔲 C	Other (Explain) _			
Estimated Production Per 24 Hours	0ii 10	Bbls.	Gas O	Mcf	Wat r	er B 1 /a	bls.	Gas-Oil Ratio		Gravity
Vented Sold	ON OF GAS: Used on Lease		_	METHOD (OF COMPLE Dually (Submit i	Comp. Cor	nmingled mit ACO-4)	PRODUCT		CEIVED 0 7 2011

KCC WICHITA



Oil & Gas Well Drilling Water Wells Geo-Loop Installation

> Phone: 913-557-9083 Fax: 913-557-9084

Paola, KS 66071

WELL LOG
Tailwater, Inc.
West Wittman #10-T

API# 15-003-24,862

August 16 - August 17, 2010

Thickness of Strata	<u>Formation</u>	<u>Total</u>
2	soil & clay	2
87	shale	89
31	lime	120
12	shale	132
5	lime	137
32	shale	169
13	lime	182
3	shale	185
4	lime	189
3	shale	192
4	lime	196
6	shale	202
30	lime	232
8	shale	240
23	lime	263
6	shale	269
16	lime	285 base of the Kansas City
169	shale	454
21	lime	475 good oil show
· 27	shale	502
16	oil sand	518 good bleeding
10	shale	528
6	lime	534
16	shale	550
3	lime.	553
20	shale	573
8	lime	581
21	shale	602
3	lime	605
17	shale	622
2	lime	624
43	shale	667
10	oil sand	677 light brown, good bleeding
60	shale	737 TD
	•	

Drilled a 9 7/8" hole to 24.2' Drilled a 5 5/8" hole to 737'.

Set 24.2' of 7" surface casing with 6 sacks of cement.

Set 727' of 2 7/8" 8 round upset tubing including 3 centralizers, 1 float shoe and 1 clamp.

RECEIVED

MAR 07 2011



TICKET NUMBER 27105

LOCATION O Hawa KS

FOREMAN Fred Wader

PO Box 884, Chanute, KS 66720 620-431-9210 or 800-467-8676

FIELD TICKET & TREATMENT REPORT

320-431-9210	or 800-467-8676	1		CEMEN	T			
DATE	CUSTOMER#	WELL	NAME & NUM	IBER	SECTION	TOWNSHIP	RANGE	COUNTY
8/17/10	7806	within	an #10	٠7	SW 15	20	20	AN
CUSTOMER								
To	ilwater	- Inc			TRUCK#	DRIVER	TRUCK#	DRIVER
MAILING ADDRI	ESS				506	Fred		
6421	Avonda	4 Dr St	e 212	_	495	Casen		
CITY		STATE	ZIP CODE		370	Derek		
OKlorho	ma City	OK	73116		510	Anlen		
JOB TYPE_LO		HOLE SIZE	57/5	 _ HOLE DEPTH	<u> 737'</u>	CASING SIZE & W	EIGHT 2%	EVE
CASING DEPTH	727'	DRILL PIPE		TUBING			OTHER	
SLURRY WEIGH	1T	SLURRY VOL_		WATER gal/s	k	CEMENT LEFT In	CASING 24	Plug
DISPLACEMENT	T 4.2BB	DISPLACEMEN	T PSI	MIX PSI		RATE 4BP	M	
REMARKS: E	stablish	Kolusvis	ion. N	lix+ Pun	100# A	remium	Gal Flu	sh
Mi	x + Pum.	0 109		50/50 /		Coment	2% Cal	
Can	nent to	Surface	Elu	shou	ma + 1.8	es elean	Disal	lace
24	" Rubl	ver alua	toc	as, we -	TO W/ 4	2 BBL F	resh we	Her.
PV	essure	to Food	₩ PS1.	Rolea	so Pres	sure to s	ex Float	Value.
Sh	utim co	asika						
		Ø				1		
						Fryl	Mode	
Eur	us Ener	ay Dov.	Luc.			, ,		
		0						
ACCOUNT CODE	QUANITY	or UNITS	D	ESCRIPTION of	SERVICES or PR	ODUCT	UNIT PRICE	TOTAL
5401		,	PUMP CHAR	GE				92500
5406		. o·	MILEAGE	Truck o	n lease			NC
	1		1				1	

	- 0				
ACCOUNT CODE	QUANITY or UNITS	DESCRIPTION of SERVICES or PRODUCT		UNIT PRICE	TOTAL
5401	,	PUMP CHARGE			9250
5406	۰۰ بر	MILEAGE Truck on lease			NC
5402	727	Casing footage			N/C
54074 1	2 Minimum	Ton Miles			1575
55020	1/2 hrs	80 BBL Vac Truck			150
1124	1075KS	50/50 Por Mix Cement			1052
11183	283#	fremium Gel			56
4402		50/50 Por Mix Coment Premium Gel 2/2/Rubber Plug			232
		ttogs of		REC	iven
		W04 236 028		MAR (7 2011
			·	KCC W	CHIA
			7.8%	SALES TAX	883
vin 3737		1		ESTIMATED TOTAL	2453
UTHORIZTION 💆	WILL	TITLE		DATE	

I acknowledge that the payment terms, unless specifically amended in writing on the front of the form or in the customer's account records, at our office, and conditions of service on the back of this form are in effect for services identified on this form.