

To:  
STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION  
130 S. Market, Room 2078  
Wichita, Kansas 67202

API NUMBER 15-205- 19990-00-00  
SW SW NW Sec/Twp/Rge Sec 3 T28S R17E  
3084 (gps) feet from south section line  
4631 (gps) feet from east section line

## TECHNICIAN'S PLUGGING REPORT

Operator License # 101Lease/Well# Stover STO 18 (gps)County WilsonOperator: State Of Kansas Fee FundWell Total Depth 1000 feetName & Stover Lease ProjectProduction Pipe: NA Size Feet NA

Address \_\_\_\_\_

Surface Casing: 8 Size Feet NAAB oil well XXXXXX Gas Well \_\_\_\_\_

SWD Well/ Input Well \_\_\_\_\_

D &amp; A \_\_\_\_\_

Other well as hereinafter indicated: \_\_\_\_\_

Plugging Contractor: Kepley Well Service, LLCLic. # 33749Address: 19245 Ford Road, Chanute, Kansas 66720Company to plug at: Hour: \_\_\_\_\_ Day: 22 Month: 11 2010Plugging proposal received from: Mike KepleyCompany Name: Kepley Well Service, LLCPhone: 620-431-8945Were: Clean well to TD and pump full of portland cement.

Plugging Proposal Received by: \_\_\_\_\_

Alan M. Dunning

TECHNICIAN

Plugging attended by Agent: All \_\_\_\_\_ Part \_\_\_\_\_ None XXXXXXOperations Completed: Hour: \_\_\_\_\_ Day: 22 Month: 11 2010Actual Plugging Report: The pulling unit attempted to wash down on well but could only reach 11'.

The drill rig was moved to location and the well drilled to 500' thru rocks, wood and cement. At 500' the bit hit steel. The drill pipe was removed and a 1" cement string washed to 500'. The well was then pumped full of cement from btm to top thru the cement string. A total of 101 sacks of portland cement were used to plug well. The well was cut off below plow depth and the location restored.

RECEIVED

Remarks: Control #20110002-018

FEB 22 2011

(If additional description is necessary, use BACK of this form.)

I did not observe this plugging.

Signed: \_\_\_\_\_

Alan M. Dunning  
TECHNICIAN

KCC WICHITA