

6070443

PLUGGED

API NUMBER 15-195-21, 702-00-00

To: STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

SE-NE-SE, SEC. 23, T 13 S, R 21 W

1650 feet from S section line

230 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 8262

Lease Name Kroeger Well 123-9-"0"

Operator: Held By Production Inc./SETCO (Joint)

County Trego 131.63

Name & Address 1625 Broadway #410

Well Total Depth 4050 feet

Denver, Colorado, 80202

Conductor Pipe: Size 0 feet

Mack Eckles.

Surface Casing: Size 8 5/8" feet 251

Abandoned Oil Well ☒ Gas Well ☐ Input Well ☐ SWD Well ☐ D&A ☐

Other well as hereinafter indicated

Plugging Contractor Halliburton Cementing Co License Number

Address East Hwy 40 - Aday, Kans. 67601

Company to plug at: Hour: 1:00 PM Day: 10th Month: Jan Year: 1986

Plugging proposal received from Mack Eckles.

(company name) Production Inc. (Setco/Joint) (phone) 308-534-4445

were: 8 5/8" 251' SP. CUL #165' 4 1/2" Csg Set @ 4049' 400' CUL

P.A.T.D 2982' - Perf's 2863' Annulus circulated w/ cement

SLV 2285 - only 1673'

Recommended 150' 5/8" 40 Formix Gel - CaCl₂, 12' 6", 5' Nulls and 8 5/8" Plug

Load Annulus and Pressure with Cement, Pump in and load 4 1/2" csg

with Pump Shut. Plugging Proposal Received by Marion Schmidt (TECHNICIAN)

Plugging Operations attended by Agent?: All ☒ Part ☐ None ☐

Operations Completed: Hour: 2:30 PM Day: 10th Month: Feb Year: 1986

ACTUAL PLUGGING REPORT Ordered 150' 5/8" 40 Formix Gel - CaCl₂ - 12' 6" - 5 Nulls and 8 5/8" Plug

Pumped in Annulus 6' 5" CUL, Max Pressure 600 PSIG Shut in @ 600 PSIG

Pumped in 4 1/2" csg - 50' 5" CUL 1/2" Nulls, 12' 5" Gel 1/2" Null's

Released Plug and 94' 5" CUL max pressure 650 PSIG

Shut in @ 200 PSIG. Cemented by Halliburton, Cmt

Remarks: (If additional description is necessary, use BACK of this form.)

INVOICED

DATE FEB 14 1986

INV. NO. 12570

2-10

APR 10 1986

FEB 14 1986

02-14-86

AUG 7 1986

Signed

Marion Schmidt (TECHNICIAN)

FORM CP-2/3
Rev. 01-84