STATE OF KANSAS STATE CORPORATION COMMISSION 200 Colorado Derby Building Wichita, Kansas 67202	WELL PLUGGING RECORD K.A.R82-3-117			API NUMBER 15-195-20,099-00-1				
wichija, kansas silva)DIC	
	TYPE OR PRINT NOTICE: Fill out completely and return to Cons. Div. office within 30 days.			WELL NU	IMBER			
				3630	3630 Ft. from S Section Line			
				330	330 Ft. from E Section Line			
EASE OPERATOR Leben Oil Corporation				SEC. 20 TWP. 135 RGE. 21 XX) of (W)				
ADDRESS P. O. Box 21468, Tulsa, OK 74121-1468					COUNTY Trego			
PHONE#(918) 494-0000 OPERA	TORS LICENSE	NO	6566	Date We	II Comp	beted	1/11/69	
character of Well <u>Oil</u>				Pluggin	Plugging Commenced 6/26/86			
(Oll, Gas, D&A, SWD, Input, Water Supply Well)				Pluggin	Plugging Completed 6/26/86			
Did you notify the KCC/KDHE Jo	int District (Office	prior to	plugging	this we	117	Yes	
which RCC/KDHE Joint Office di	d you notify?_	Di	strict 6	, Hays				
is ACO-1 filed? on old form f	not, is well	log a	ttached?					
Producing Formation <u>Checkerb</u> Show depth and thickness of al OIL, GAS OR WATER RECORDS	Lime		s formatio			<u>) </u>	4033	
Formation Content	From	То	Size	Put in	Pulled	out		
Marmaton Oil	3941	50	8-5/8	201	-0-			
Checkerboard Oil Lime	3848	70	5-1/2	4031	162	20		
DIME								
locasibo in dotali the manner		rell W	as plugged	, indicat o the hol	ing whe	ement	or other pluc	
placed and the method or metho were used, state the character Bottom hole plug from PB'	ds used in int of same and o TD to 3798' hulls from 1	roduc depth w/sa: L620 '	ing it int placed, fr nd + 5 S -SURF.	om feet	tofe	et eac imped		
placed and the method or method were used, state the character Bottom hole plug from PB'	ds used in into of same and of TD to 3798' hulls from J	roduc depth w/sa L620'	ing it int placed, fr nd + 5 S -SURF. PLETE	om feet XS cemen	to fe	et eac imped		
Bottom hole plug from PB' SXS thrifty-mix + 6 SXS	ds used in into of same and of TD to 3798' hulls from I	roduc depth w/sa L620' B COM	ing it interpretation of the placed, from the placed, from the placed of	om feet XS cemen	to fe	et eac imped	135	
laced and the method or method ere used, state the character Bottom hole plug from PB' SXS thrifty-mix + 6 SXS (if additional descharge of Plugging Contractor Karame of Plugging Contractor Co	ds used in into of same and of TD to 3798' hulls from I JOH ription is necessariser-Franci	depth w/sa L620' COM cessar	ing it interpretation of the placed, from the placed, from the placed of	om feet XS cemen	to fe t. Pu form.)	et eac imped	135	
Describe in detail the manner of laced and the method or method vere used, state the character Bottom hole plug from PB'SXS thrifty-mix + 6 SXS (if additional described of Plugging Contractor Kanddress P. O. Box 21468, STATE OF Oklahoma	ds used in into of same and of TD to 3798' hulls from I JOH ription is necessariser-Franci	depth w/sa L620' B COM cessar Ls Oi	Ing it insplaced, from the surf. PLETE y, use BAC 1 Compan	om feet XS cemen CK of this	form.)	et eac imped	135	

the same are true and correct, so help me God.

SUBSCRIBED AND SWORN TO before

My Commission Expires:

JUL 2 5 1986

2/11/89

Form CP-4 Revised 08-84

Box 21468, Tulsa,