

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

1048200

Form ACO-1 June 2009 Form Must Be Typed Form must be Signed All blanks must be Filled

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License # 4824			API No. 15 - 15-189-22743-00-00
Name: Pioneer Natural Resource	ces USA, Inc.		Spot Description:
Address 1: 5205 N O CONNOR BLY	VD		SW_SW_NE_SW_Sec16_Twp31_SR38East wes
Address 2:			1600 Feet from North / South Line of Section
City: IRVING State:	TX Zip: 75	3707	1390 Feet from East / West Line of Section
4 4.1.14.			Footages Calculated from Nearest Outside Section Corner:
Phone: (972) 969-3941	-		□NE □NW □SE ☑SW
CONTRACTOR: License # 4824			County: Stevens
Name: Pioneer Natural Resources			Lease Name: Lucas Well #: 4-16
			Field Name: Hugoton Panoma
Purchaser: Pioneer Natural Resource		-	Producing Formation: Chase Council Grove
Designate Type of Completion:			Elevation: Ground: 3097 Kelly Bushing: 4007
New Well Re-Entr	rv 🗆 1	Vorkover	Total Depth: 2950 Plug Back Total Depth: 2872
	n swo	□ slow	Amount of Surface Pipe Set and Cemented at: 2830 Fee
] SWD	☐ SIGW	Multiple Stage Cementing Collar Used? ☐ Yes No
	GSW	Temp. Abd.	If yes, show depth set: Fee
CM (Coal Bed Methane)	-		If Alternate II completion, cement circulated from:
Cathodic Other (Core, Exp	pl., etc.):		feet depth to: sx cm
If Workover/Re-entry: Old Well Info as	s follows:		W/SX G//
Operator:			
Well Name:			Drilling Fluid Management Plan (Data must be collected from the Reserve Pit)
Original Comp. Date:	Original Total D	epth:	Chloride content: 24000 ppm Fluid volume: 1000 bbl
Deepening Re-perf.	Conv. to ENH	R Conv. to SWD	Dewatering method used: Hauled to Disposal
ŀ	Conv. to GSV	v	Dewatering method used:
Plug Back:	Plug Bad	ck Total Depth	Location of fluid disposal if hauled offsite:
Commingled Pe	ermit #:		Operator Name: Hayden Operating
Dual Completion Pe	ermit #:		Lease Name: Liz Smith #3 License #: 33562
SWD Pe	ermit #:		
☐ ENHR Pe	ermit #:		Quarter NE Sec. 26 Twp 30 S. R. 34 East West
☐ GSW Pe	ermit #:		County: Haskell Permit #: D26802
7/8/2010 7/14/2010	9/	23/2010	•
Spud Date or Date Reached	d TD Co	mpletion Date or	

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY
Letter of Confidentiality Received
Date:
Confidential Release Date:
Wireline Log Received
Geologist Report Received
UIC Distribution
ALT II III Approved by: Deanes Gardson Date: 06/08/2011

Side Two



Operator Name: Pior	neer Natural Resc	ources USA, Inc.	Lease N	lame; _l	Lucas		Well #: 4-16					
Sec. 16 Twp.31	s. r. <u>38</u>	☐ East	County:	Steve	ens							
time tool open and clo	sed, flowing and shutes if gas to surface tes	I base of formations per in pressures, whether s it, along with final chart(well site report.	hut-in press	ure read	ched static level,	hydrostatic pressu	ıres, bottom h	ole temp	erature, fluid			
Drill Stem Tests Taken (Attach Additional S		Yes No		□L(og Formation	(Top), Depth and	l Datum		Sample			
Samples Sent to Geol Cores Taken Electric Log Run Electric Log Submitted (If no, Submit Copy,	d Electronically	Yes No Yes No Yes No Yes No		Nam Attach		,	Top Attached		Datum Itached			
List All E. Logs Run:												
GR-CCL-CBL=VDL NEUTRON OPEN HOLE												
		CASING Report all strings set-	RECORD	√ Ne	_							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Welg	ht	Setting Depth	Type of Cement	# Sacks Used		and Percent			
Surface		8.6250	24	16	603	POZ/Class G	352		ddiaves			
Production	7.8750	5.5	15.5		2830	POZ/Class G	G 417					
		ADDITIONAL	L CEMENTIN	IG / SQL	JEEZE RECORD			<u> </u>				
Purpose: —— Perforate —— Protect Casing	Depth Top Bottom	Type of Cement	# Sacks	Used	Type and Percent Additives							
Plug Back TD Plug Off Zone	-											
Shots Per Foot		ON RECORD - Bridge Plu ootage of Each Interval Pe				cture, Shot, Cement nount and Kind of Mat		d	Depth			
Attached	Attached				Attached				Attached			
		<u> </u>										
TUBING RECORD:	Size:	Set At:	Packer At	:	Liner Run:	Yes No						
Date of First, Resumed	Production, SWD or ENI	IR. Producing Met	hod:		Gas Lift O	ther (Explain)						
Estimated Production Per 24 Hours	Oil 8	Bbls. Gas	Mcf	Wat	er Bl	xls. G	as-Oil Ratio		Gravity			
DISPOSITION OF GAS: METHOD OF COMPLETION: PRODUCTION INTERVAL: PRODUCTION INTERVAL: PRODUCTION INTERVAL: Submit ACO-4)												
(If vented, Sut	omit ACO-18.)	Other (Specify)				· —						

Form	ACO1 - Well Completion
Operator	Pioneer Natural Resources USA, Inc.
Well Name	Lucas 4-16
Doc ID	1048200

Tops

Glorieta	1179	КВ
Hollenberg	2328	КВ
Herington	2351	КВ
Krider	2377	КВ
Towanda	2493	КВ
Ft. Riley	2548	КВ
A1 Lime	2682	КВ
B1 Lime	2739	КВ
B2 Lime	2763	КВ
Base B2 Lime	2776	КВ

Form	ACO1 - Well Completion
Operator	Pioneer Natural Resources USA, Inc.
Well Name	Lucas 4-16
Doc ID	1048200

Perforations

3	Chase	Shot & Fractured	2515-2524
3	Chase	Shot & Fractured	2526-2530
3	Chase	Shot & Fractured	2556-2588
3	Chase	Shot & Fractured	2612-2624
3	Chase	Shot & Fractured	2646-2650
3	Chase	Shot & Fractured	2656-2666
3	Council Grove	Shot & Fractured	2746-2760
3	Council Grove	Shot & Fractured	2770-2780

CEMENTING TRU	EATMENT	REPORT					14				DUATMENTNEM	BER		DATE									
					S02010017				711/2010 JOB TYPE Long Saling														
WILLYAMEAN	MO.				(OCCUPANT)	(IACAL)		_	NIC NAME:					CLMLN									
TIELD	Learn 4-16 Sec.14, TO18, RVIW FORMATION						L PYTO	_	WELL DATA	Piroca N	and Resources Riz # 3	вотточ	<u>, </u>		FI	IFT							
	Įħ,	got a <u>-Pau m</u>	•		L				BIT SIZZ	77	CSG/Liner Size	512						1					
COUNTY		•			STATE		API NO.		TOTAL DEPTH	2950	WEIGHT	15.5	<u> </u>				1	Į.					
		Stevens				Ones	1517912741	_	MID TYPE DBST	_	FOOTAGE GRADE	2930 3-55	├					ł					
RED FOREMEN				Denick	Deny/Ten D	constitutely.			Пенст	<u> </u>	THREAD	LTAC	†					1					
									MUD DENSITY		Latanon	42						TOTAL:					
CLAUNT SUZZAVI	EOR				Stra Owers			_	MED VISC Inchase Footage From George I	evel To Head b	Disp. Capacity	£1,7	L					63.7					
									ÿ TYF#I]	240111111111	e Dept Capacity	j	TYPE [
									2 ORPIN				DEPTH TYPE										
LELCIAL DISTRUC	צאטווי								CC PTIL		-		DEFTH										
	-							_	Head & Hings		SUZE	□ръ		TYPI]_									
									Double Box 6	WEIGHT	I.			DEFIN									
		, .			·				Single	GRADE	ļ		TAIL PIPF:			SIZE.		DEPTH					
			•	-					Swage Knodout	THREADS New	Used		CSG VOL BE		MI.			BBLs					
LIPT PRESSURE			FM	lić.						DEPTH	.I.		TOTAL	-011	,,,,,			RELL					
PRESCRETING	1		15.70	Į×.	BUMPHA		2001		CEMENT TO MPERATURE			,	ANNUARY				Ĺ	BBLs					
TIME	PRES	SURE	VOLUME	PUMPED	NO. of Con-	DULED FOR	12	_	WATER QUALITYS ARRIVE ON LOCATION			RIG UP	327		9G	CONTR	CATION	TEMP	FS				
0001 to 2400	TBG	CSG	INCR.	CEDI	TIME	20:00	DATE: 7:12'2	10	TIME: 1F:00	DATE	7/12/2010	TIME	130	DATE:	7/14/2010	TIME		DATE:	7/13/2010				
					RATE.	רו מוטול	THE DUNS	ITY_	T														
12:00						1						Pre ich	safety mee	tina									
12.00				-	· ·	<u> </u>		_				110 100	saicty line	aug.									
12:27		2000	0.5		0.5	H20	8.3	,	1		Test Pumps and Lines.												
									1		rest 2 with 5 and Edites.												
12:30		50	20		_3	H20	8.3	,				Pun	p H20 ahea	ıd,									
													<u> </u>										
12:37			110		3	СМТ	12.	5			Mix	and pump l	lead cement	(d) 12	.5 ppg.								
13:13		50	45		3	СМТ	15		Mix and pump tail cement (a) 15 ppg,														
13:28					<u> </u>						Shu	t down and	wash pum	ps and	lines.								
		ļ	ŀ																				
13:30		ļ	<u> </u>		ļ			_	Drop top plug,														
					_		l .																
13:35		 	68.7		3	KCL	. 8.3		ļ		Рипр displacement,												
12.56		1500	<u> </u>		١,	va	١.,				b	Burn plug and check floate (Did not hold)											
13:56		1300			2	KCI	. 8.3	_		Bump plug and check floats. (D							id.)						
14:00		2000	Į.		2	KCL	. 8.3				Pome	sasin to c	tose floats.	(Held	IOK)								
14,00		2000	•				·				1 4014	, again 10 c	iose nons,	Litere	(U.K.)								
		1																					
-					1												_						
		1					l		l														
		<u> </u>			<u> </u>																		
			ŀ				1																
	ļ	 	 	<u> </u>	 	ļ																	
		 	 		 																		
										. 00 511	800 D : 40 T :							**** ·					
		 	 	-	 	-	-+	_	Call Out	s 20 Bbls	200 Psi. 50 Bt	13 340 Psi	68 Bt	ola Fin	nal 800 Pr	<u>u, </u>	Bumped @ 1	500 psi.					
			I								ومراجبته الملا	d a	AN 121- PA	ne -#:-	-l								
	\vdash	 	 	 	 						Well circulate	ı cemeni al	+U DOIS K	L.L. 01S	pracemen	away.							
		l '	1						1		D.	ned 25 kbl	s good cem	ent to	the mir								
		 			 			_	 		rum	PAG 23 001	s Kood cem	cut to	ue pit.								
14:30												Post in	safety me	etina.									
Byston Ched	i nei	1 100 H	i	•	•	•	-		Post job safety meeting. COMPOSITION OF SYSTEM LICENSY MIXED														
	Jecks	n²∧s.	-					_	RBLS DENSITY														
770 2.06									SDC 110 12.5														
$\overline{}$	200	125	 						Rorfou Cerreca 43 (5								15						
		\vdash	 													 		 					
			 															 					
CPCCIATION	۷	(e) [No.	WASIIED CA	CTC/2 PARTY		Oyes O	No		*	Dht Ll'hous					-	4000	Ь.					
					TAN DELIN	` -	RETURNED	10	SURFACE		BREAKDOWN HENORE PLUG BLM			PSI	FIVAL.		7310		PS1				
DISPSACEMENT	vot.		0.7	BBLS	<u> </u>		23 1000				PRESSURE		100	PSI	RATE			BPM					

CEMENTING TREATMENT REPORT						2					TREATMENT NEXT	EEN 02709016		DATE			7**2010		
							STAGE				PORTYPE S. Surgar								
WELLNAMEAN					ZOCATION	(LECAL)		RIG KAME	1			CEMENT PUMPER							
и пли		In:m 444	-		PORMATK	Sec.15, TS15, R55W		WIIIZ, DAT	A	Pinner Na	al Reserve Rig # 3	BOTTON		<u> </u>	Υſ	107	2303	л	
	Įħ.	् भाग ाः नि हत्समार	,					BIT FLTE			CSG/Liner Stee	827			L			•	
COUNTY					STATE	API NO.		TOTAL DE		613	WEIGHT	24	 					1	
		Crant			K	arron 1506	-7217-13	ALLD TYPE		 	FOOTAGE	537.36	-						
REJ FOREMAN					Berry/Toni Bo			BACT			GRADE THREAD	I-55 LT&C	<u> </u>					l	
KIJ POKLEDAN				LANKE	pery/toni oc			MUD DENS	TPV		LINEAR ELECT	43	t				 	TOTAL:	
CEMENT SUPERVI	ISOR				State Owens			MUDVISC	1		Disp. Capacity	34.7						34.7	
						•			ge From Ground	Level To Head It	Dap Capacity		Imaai	_					
	•							DEPTH DEPTH				7	HT9 KI	.					
								I IALR			• • • • • • • • • • • • • • • • • • • •	1 th	ТУРБ	\vdash					
SPLCIAL INSTRUC	TIONS							DEPTH 1 kmd & Pin			[∐πεσ] # ∐p.e.	DEPTH	l .	<u> </u>				
							_				SIZE		8	TYPE					
								Double	Bax 6	WEIGHT	ļ		<u> </u>	DEPTH					
								☐ Singta ☐ Swage	,	GRADE THREADS	 		TAIL PIPE			\$0 2 15		DI PILI BBLa	
								Knock		☐ New	Used		CSC VOL.		001.			BBL	
LIFT PRESSURE			210	Ţ¢.						DEFTH		•	TOTAL					BBL4	
PRESSURE LIMIT	T		D00	<u></u>	BUMPHA		900		TMPTRATER	Et		pili	ANNULAR 32			,		BBL	
TDAK	Pers	SLRE	wilwi	PUMPED	NO. of Com-	DLLED FOR	4	WATER QUARRENT OF	LOCATION			RIG UP	32		ec.	LEFT	OCATION	TEMP	,
0001 to \$4.0	100	CHO	INCR	CCZI	TTME	1230 DATE:		TIME	15:00	DATE:	672 2010	TIME	ites.	DATE	6302010	TIME	23.90	DATE:	71710
	ļ . —	,——		1	KATE	HU.a Trni	D. NAMY						_						
		•						1				n (-)							
20:30				 	-			+				Pre jot	safety me	eting.					
	i !		Ì		١ ا									• •					
20:45			 -	 -	0.5	H20	8.3	1				1est P	umps and	Lines.					
		١			1 . 1														
20:55		80	20	-	4	H20	8.3					Pun	p H20 ahe	30.					
		١	۱		١														
21:01		60	86	 -	4	СМТ	12.5				Mix	and pump	lead ceme	nt (a) 12	2.5 ppg.				
				1				}											
21:32		60	33	-	4	CMT	15	 			Mix	and pum	tail ceme	nt (d) 1	5 թթք.				
		i						1				.							
21:45			<u> </u>	 -	ļ			1-				Shut down	and drop	top ph	18				
								1				_							
21:46		220	14.6	 	4	H20	8.3	-				Pum	displacer	neni,					
		l	1		١														
21:55		900		-	2_	H20		+			Bump pii	ig and che	CK HOOTS.		(Held OK	<u> </u>			
					ì														
	├	├──		1	+														
	1			1	1		İ												
	 	├──	 	┼──	_		 	+											
		ļ .						1											
	\vdash	├						╁											
	 	├──	 	†	 		-	+											
					-														
	1	 		 	+		 	 											
				1	1														
	 	┼	 	 -	 		 	 					-						
				1	i		i		C	II Oute 10	Bbls 60 Psi. 20	BNs 120	Dei	Final	220 Psi.	R ₂₁₁	mped @ 900 ;	nei	
				1	 	1		t		0003 10			- 141			-			-
	1			1	1	}		1											
				1	\vdash		\vdash	t				<u> </u>							
	1			1	1						Well circu	lated cem-	ent at 5 hh	la lead :	centent so	uav.			
	1	\vdash	1	1	\vdash	1		1			***************************************		21 2 50			/-			
				1	1			1			Porm	ped 45 bb	a ened ce	ment to	the pit				
		 	 	1	1	1		1			= u/li	<i>-</i> / 40	_B 6G		are pro				
]		1	1			1											
	1	 	1	1	+-	 		1 											
22:30	l	1		1	1			1				Post in	b safety m	ectino					
22:30 System Used	Nast	Mar/	 	-		·	L	Post job safety meeting. COMPOSITION OF SYSTEM MATRIX MIXED											
oysean Used	Seria	n'ak	-					BBIS DENSITY											
	220	2.06	-														12.5		
	1,50	12	1						Surface Cement							ļ	31	 	15
	<u> </u>															₩		₩	
	<u> </u>	<u> </u>	<u> </u>													ــــــــ		Ļ	
			<u> </u>	,												l			
CIRCULATION	1	Yes [СМ	WASIFDC	ASING DOW	N □Yes	□ Ko				BREAKDOWN			PSI	FINAL		900		PSI
DISPLACEMENT	. VOL		34.7	BULS	1		TURNED TO U DAL	SURFACE		_	PRESSURE	ľ	220	PKI	RATE			EPM_	